



Harmless Auto Paint Hardener Multiscene , Practical Fast Hardener For Clear Coat

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: PORSHICHE
- Certification: iso9000
- Model Number: P-12X
- Minimum Order Quantity: 200L
- Price: 4.1USD/L-7.26USD/L
- Packaging Details: carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 200L per day




Product Specification

- Produce Name: P-12X Crystal Hardener
- Net Weight: 0.95KG
- Form: Liquid
- Level: Medium
- Color: Transparent
- Dry Time: According To The Season
- Specification: 1L/4L/5L
- Highlight: clear paint hardener, automotive clear coat and hardener, hardener for clear coat



More Images



for more products please visit us on refinishcarpaint.com

Product Description

Meklon High Quality Fast/Standard/Slow Crystal Hardener

Are you looking for a high-quality hardener to enhance the durability and strength of your coatings and paints? Look no further than Meklon Crystal Hardener hardener, designed to deliver outstanding results for a wide range of applications.

Meklon hardener are available in a variety of formulations, each designed to meet the specific needs of your project. There are fast/Slow/Standard drying hardener for quick turnaround times to high-performance hardeners for extreme environments, we have the perfect solution for you.

At our company, we are committed to delivering the highest quality products and exceptional customer service. Our hardener are backed by our satisfaction guarantee, so you can try them with confidence and experience the difference for yourself.

Whether you're a professional painter or a DIY enthusiast, Meklon hardeners are the perfect solution for enhancing the durability and strength of your coatings and paints. Try them today and see the difference for yourself!

P-12X Crystal Hardener Effect

Paint hardener is a material specially used in paint, which can accelerate the drying of paint and accelerate the drying speed of paint.

The paint hardener can be used for physical drying, through the direct reaction of the internal molecules of the paint with the oxygen in the air to achieve the purpose of drying. It can also be chemically cured. The hardener reacts with the main paint, which can increase the hardness, brightness and Adhesion.

Paint hardener can be divided into room temperature hardener and heating hardener according to their uses. In addition, there are medium-temperature hardeners and high-temperature hardener. The use of these two hardeners should be selected based on the heat resistance of the substrate, the heat resistance of the hardened product, adhesiveness, and anti-bacterial properties.

Precautions

In winter, use a quick-drying curing agent. If it is not heated, it will take three hours, and it will be heated within two hours;

In summer, use a standard curing agent, do not heat for one and a half hours, and heat for about 40 minutes.





Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province