

2K Stand Blue Paint High Performance Automotive Paint Spraying 2K Paint

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:

Our Product Introduction

- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

- Application Method:
- · Coats Required:
- Color:
- Coverage:
- Dry Time:
- Finish:
- Product Name:
- VOC Level:

- Brush, Roller, Or Spray 2
- Blue

China

Faralli

206

5-8days

500000L/month

T/T

ISO,MSDS,SGS

Could be negotiated

Could be negotiated

1L*12tins, 4L*6tins, 4L*4tins,

0.5L*24tins,10L, 20L, 200L

- 400 Sq. Ft. Per Gallon
- 2 Hours
- Glossy
- Car Paint Topcoat
- Highlight:
- Low 2K Stand Blue Paint Spraying, 2K Stand Blue Paint,
- 2K Stand Blue Paint Automotive



More Images



2K Stand Blue Paint Topcoat High Performance Automotive Paint Spraying 2K Paint

Automotive paint Basecoat:

Meklon Basecoat is easy to mix, easy to apply and provides excellent coverage and good metallic orientation for imitating OEM solid, metallic and pearl colour effects.

Meklon basecoat provides optimal colour match.

Meklon Basecoat must be used in combination with a Meklon clearcoat to provide durability.

Surface Prepartion:

Old or original paintwork well sanded and cleaned.

Primer-surfacer or Surfacer, sanded and cleaned Primer-Surfacer or Surfacer, unsanded in a wet-on-wet process. Surfaces must be prepared and cleaned correctly before application.

Repair areas should be sanded with P500-P600 (by machine) or P800-P1000 (by hand) and cleaned.

Product Features:

Hard paint film, good leveling performance, easy construction, strong adhesion, excellent outdoor weather resistance, long anti-oxidation time, can be mixed with a variety of plain color, metal effect, pearl effect one-component base paint, with excellent Adhesion between layers

PHYSICAL PROPERTIES	
Specific Gravity	0.95-1.0KG/L
Viscosity	140-180S
Ingredients	Acrylic resin, CAB, pigment, solvents, addition agents
Colour	All kinds of colors. For detailed information please refer to Roch® Tinters in the catalog
Mix Ratio (by volume)	2K paint: 2 part Hardener:1 part Thinner(RC-X110, RC-X111, RC-X112): 0.3~0.5 parts
Pot Life	48 hours@20°C
Spray Gun & Air Pressure	2-3 single coating to coverage (volatilization time of each layer: 15-20 minutes)
Drying Time	Clearcoat can be sprayed within 15 minutes to 5 hours
Sanding	Before spray: P600-800 by dry sanding After spray: P1000 by wet sanding
Substrate	OEM paint, Roch® brand primer surfacer
Unapplicable Substrate	Thermal plasticity acrylic paint or alloy base coat
Packaging	1L x 12 tins/ctn, 4L x 4 tins/ctn
Shelf Life	5 years

Meklon Topcoat is a high-quality automotive paint that is easy to mix, apply, and provides excellent coverage with good metallic orientation. It is designed to imitate OEM solid, metallic, and pearl color effects, providing an optimal color match. For optimal durability, Meklon Topcoat should be used in combination with a Meklon clearcoat. Before application, surfaces must be properly prepared and cleaned to ensure maximum adherence and longevity. Old or original paintwork should be well-sanded and cleaned, while repair areas should be sanded with P500-P600 (by machine) or P800-P1000 (by hand) and thoroughly cleaned.

Meklon Topcoat offers several features that make it an excellent choice for automotive use. It has ahard paint film, good leveling performance, and strong adhesion. Additionally, it boasts excellent outdoor weather resistance and a long antioxidation time. It can be mixed with a variety of plain color, metal effect, and pearl effect one-component base paint, providing excellent adhesion between layers.

Overall, Meklon Topcoat is an easy-to-use, high-quality automotive paint that provides excellentcolor matching and durability when used in combination with a Meklon clearcoat. Its features make it an excellent choice for automotive use, providing a hard paint film, strong adhesion, and excellent outdoor weather resistance.













