



Acrylic Resin Car Clear Coat Varnish Mirror Effect Moistureproof

Our Product Introduction

Basic Information

- Place of Origin: GUANGDONG CHINA
- Brand Name: Ferrari series
- Certification: ISO,SGS,MSDS
- Model Number: 8800
- Minimum Order Quantity: 100 L
- Price: 3.26USD-5USD
- Packaging Details: 0.5L/1L/4L/10L/20L/200L
- Delivery Time: 7-30days
- Payment Terms: T/T
- Supply Ability: 50000L/month



Product Specification

- Main Raw Materials: Acrylic Resin,Polyurethane Resin
- Feature: High Leveling,high Glossy,high Fullness,good Covering,high Adhesion
- Color: Transparent,transparent With Light Yellow
- Substrate: 1k Base Coat
- Shelf Time: 2 Years,at 20
- Component Style: Bi-component
- High Light: Anti Scratch Auto Base Paint, Oil Based Auto Base Paint, Acrylic Car Primer High Adhesion
- Highlight: home auto paint, Car Clear Coat Varnish Mirror, mixing auto paint



More Images



for more products please visit us on refinishcarpaint.com

Product Description

Africa Popular automotive refinish paint Mirror Effect Clear Coat Acrylic Resin 2K Varnish

The varnish product in Meklon automotive paint is a high-performance transparent coating, usually using advanced polymer technology and UV absorbers, with excellent properties such as UV resistance, scratch resistance and chemical corrosion resistance, and can be used in extreme weather and Maintain the original color and gloss of car paint in harsh environments. The coating has a high degree of gloss, which can reflect more light and colors, making the surface of the vehicle more dazzling, and improving the appearance texture and sense of grade of the vehicle. In addition, varnish products in high-end automotive paints also have the following characteristics:

Easy maintenance: The varnish products in Meklon automotive paint have good self-cleaning performance and anti-fouling performance, which can reduce the adhesion of stains, sediments and dust, making the vehicle surface easier to clean and maintain.

Super durability: The varnish products in Meklon automotive paint can effectively protect the car paint surface, prolong the service life of the vehicle, and at the same time prevent the oxidation reaction and color change of the car paint surface.

Flexible color matching: The varnish products in Meklon automotive paint can be perfectly matched with the base coat to maintain consistent color and gloss. At the same time, it also has good color matching flexibility and can be personalized and customized according to customer needs.

Strong environmental protection The varnish products in Meklon automotive paint adopt environmentally friendly formulas and processes, do not contain harmful substances and volatile organic compounds, and meet environmental protection standards and requirements.

To sum up, the varnish products in Meklon automotive paint have multiple advantages, which can provide high-quality and high-performance coating solutions for car manufacturers and car owners, and at the same time protect the appearance and value of vehicles. Indispensable and important component.

Product Description:

Clear coat series(varnish)

High performance and heat resistant clear coat, suitable for overall refinishing or panel repairs with high gloss. It has good chemical and weathering resistance to ensure durable gloss.

Substrates	1k basecoat				
Mixing Ratio	<18°C<> Clear coat 100 parts Fast hardener 50 parts Thinner 10-30 parts		18-24°C Clear coat 100 parts Standard hardener 50 parts Thinner 10-30 parts		
	25-30°C Clear coat 100 parts Standard hardener 50 parts Thinner 10-30 parts		>30°C Clear coat 100 parts Slow hardener 50 parts Thinner 10-30 parts		
Pot Life	25°C , Diamond clear coat + Fast hardener :1.5 hours; Diamond clear coat + Standard or Slow hardener : 2 hours.				
	25°C, Special grade clear coat (or Mirror effect clear coat)+ Fast hardener :2 hours; Diamond clear coat + Standard or Slow hardener : 4 hours.				
Spraying coat	2-3 coats, total 40-60 um				
Interval	At 25°C, 5-10 minutes between coats, allow 15-20 minutes air-drying time before baking				
Spray Gun & Pressure	Gravity Feed 1.2-1.5mm 3-5 bar Siphon Feed 1.4-1.7mm 3-5 bar				
Drying Time	Temperature	Dust Time	Tack Free	Dry to Handle	Thorough Dry
	25°C	40 minutes	2-3 hours	10 hours	48 hours
	70°C	5 minutes	15 minutes	30 minutes	60 minutes
Shelf Life	2 years in original sealed can at cool and dry place at 20°C				
Packaging	1L, 4L				



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province