



Automotive refinish paint System Car Spray Coating Paint Supplier 2K Acrylic Basecoat Auto Car Paint

Our Product Introduction

for more products please visit us on refinishcarpaint.com

Basic Information

- Place of Origin: GUANGDONG CHINA
- Brand Name: Ferrari series
- Certification: ISO,SGS,MSDS
- Model Number: 113
- Minimum Order Quantity: 100 L
- Price: 3.26USD-5USD
- Packaging Details: 0.5L/1L/4L/10L/20L/200L
- Delivery Time: 7-30days
- Payment Terms: T/T
- Supply Ability: 50000L/month



Product Specification

- Main Raw Materials: Acrylic Resin,Polyurethane Resin
- Feature: High Leveling,high Glossy,high Fullness,good Covering,high Adhesion
- Color: Transparent,transparent With Light Yellow
- Substrate: 1k Base Coat
- Shelf Time: 2 Years,at 20
- Component Style: Bi-component
- High Light: Anti Scratch Auto Base Paint, Oil Based Auto Base Paint, Acrylic Car Primer High Adhesion
- Highlight: **Automotive refinish paint System Basecoat, Car Spray Coating Paint Basecoat, 2K Acrylic Basecoat**



More Images



Product Description

Automotive refinish paint system: Car spray coating paint supplier 2K acrylic basecoat auto car paint

Meklon 1K Red Metallic is a high-quality, single-component automotive refinish paint designed for general motor vehicle repair. It features a vibrant red metallic finish with a captivating crystal-like effect. This paint exhibits excellent air-drying speed, exceptional leveling properties, and smooth application.

Product description of car paint

1. Our car paint gives eco-friendly paint remover.
2. Non-corrosive, use safety, and operate easily
3. Does not contain acid, benzene, and other harmful material
4. Can be reutilized by cleaning the paint film and paint slag in solution
5. Can remove the phenolic resin, acrylic, epoxy, polyurethane finishing paint, and premier paint quickly.

Features of car paint

1. High solids
2. High build
3. Good hiding power
4. ISO TS 16949 certified
5. Color: customized

Product Description:

| Model | Meklon 1K Metallic Paint | | |
|------------------|---|--------------------------------------|----------|
| | Ambient Temperature | Base coat | Thinner |
| Mixing Ratio | <15°C | 2 Meklon 1K Metallic Paint | 1 602 |
| | 15-30°C | Meklon 1K Metallic Paint | 602 |
| | >30°C | Meklon 1K Metallic Paint | 602 |
| | | | |
| Pot Life | 24 Hours, 25°C | | |
| No. of Coats | 2-3 coats | | |
| Flash-off Time | 2-3 mins at 25°C | | |
| Film Thickness | 10–20 microns | | |
| Spraying Tool | Gravity feed: 1.2–1.5 mm | | |
| | Suction feed: 1.2–1.7 mm | | |
| | spraying pressure: 3-5 kg/square centimeter | | |
| Drying Time | At 25 °C, after 15 minutes, spray varnish within 1 hour. | | |
| Using Substrates | The surface of old paint or primer after sanding with the P1000# sandpaper or removing the oil | | |
| Others | After spraying Meklon 1K metal paint , spray varnish within 1 hour as much as possible to ensure the accuracy and repeatability of the color formula; stir evenly before application. | | |



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province