



## 1K Color Coating Car Detailing Supplies Paint Filler Multi Function

### Our Product Introduction

#### Basic Information

- Place of Origin: GUANGDONG CHINA
- Brand Name: Ferrari series
- Certification: ISO,SGS,MSDS
- Model Number: 350
- Minimum Order Quantity: 100 L
- Price: 3.26USD-5USD
- Packaging Details: 1L/4L/10L/20L
- Delivery Time: 7-30days
- Payment Terms: T/T
- Supply Ability: 50000L/month



#### Product Specification

- Main Raw Materials: Acrylic Resin,Polyurethane Resin
- Feature: High Leveling,high Glossy,high Fullness,good Covering,high Adhesion
- Color: Transparent,transparent With Light Yellow
- Substrate: 1k Base Coat
- Shelf Time: 2 Years,at 20
- Component Style: Bi-component
- High Light: Anti Scratch Auto Base Paint, Oil Based Auto Base Paint, Acrylic Car Primer High Adhesion
- Highlight: **1K Car Detailing Supplies,  
Color Coating Car Detailing Supplies,  
Multi Function Paint Filler For Car**



#### More Images



## Product Description

### Car Paint Automotive Coating Wholesale Car Refinishing Products 1K Color Coating Car Paint Auto Body Filler

#### Product Description

#### Body Filler for Paint for Car

1. BASF raw materials
2. Easy application
3. Accurate color matching
4. Long-lasting bright color

We have a complete set of tinting system and mixing system includes 1K basecoat toners (solid, silver and pearl colors), 2K topcoat toners, primers (1K primer surfacer, 2K primer surfacer, epoxy primer and plastic prime), clear coats, hardeners, thinners, binders, ancillaries, etc.

And our system has contained all the recipes for the car auto market for example, Nissan, Honda, Toyota, Ford, Chrysler, Fiat, Peugeot, Citroen, Renault etc.

BPO Putty/BPO Car Body Filler	
Feature	Easy to scratch, quick-drying at room temperature, easy to sand, strong adhesion, high temperature resistance, good filling ability, no cracking, no shrinkage, Good matching and other advantages.
Application	All kinds of metal surfaces, all kinds of primers and old paint surfaces, etc.
Shelf Life	12 months in its original sealed can at cool and dry place at 20°C.
Application Method	Mix the main putty and hardener in proportion and complete it within the gel time. Scrape the adjusted putty on the polished two-component primer or the surface of the treated base. If thick coating is required, it is better to scrape several times. If air bubbles appear during the coating , must scrape thoroughly with a scraper.
Package	2 kg/tin, 4 kg/tin.





- Note:**
1. Stir evenly before use. Do not put the used ash body into the original product tank;
  2. The ratio of putty and curing agent must be appropriate before scraping, and must be mixed well and uniformly to avoid cracking or softening;
  3. Putty hardener is a product that is flammable, explosive and has strong irritation to the skin, please do not directly contact the skin;
  4. Putty coating is not easy to apply too thick at one time, and if the pit is deep, it should be applied in multiple passes.
  5. Do not spray the topcoat directly on the putty, so as not to cause the topcoat to lose gloss.

**Several factors that cause putty to deteriorate easily:**

1. The isocyanate in the main component is easy to react with moisture in the air and deteriorate.
2. The additives (inhibitors, accelerators) have an impact on the quality of the product itself.
3. The formula system needs to be proportioned according to the environment and climate of each place.
4. Storage conditions must be in a dry environment and sensitive to climate.
5. The poor quality of its product packaging jars affects the product quality of putty.



**Guangzhou Meklon Chemical Technology Co., Ltd.**



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province