



SGS Durable Automotive Paint Hardener , Multiscene Clear Coat Spray With Hardener

Our Product Introduction

for more products please visit us on refinishcarpaint.com

Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: P-800X
- Minimum Order Quantity: 200L
- Price: 4.64USD/L-6.92USD/L
- Packaging Details: Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500L per day



Product Specification

- Features: High Hardness
- Brand: PORSHICHE
- Color: Transparent
- Name: Enviromentally Hardener
- Material: Resin
- Net Weight: 0.95kG
- Shelf Life: 2 Years
- Storage Temperature: Room Temperature
- Highlight: automotive paint hardener, car paint hardener, automotive paint with hardener



More Images



Product Description

Environmentally Hardener-Cost Effective Glossy

product description:

Meklon car paint manufacturer is a company focused on producing high-quality car paint, with 6 brands, namely CarCharm, poshiche, ferria, Meishilianke, Meiguanda and Meklon, each brand has its own unique packaging and characteristics. The company's R&D team consists of its own R&D engineers, who have developed car paint products from low to high quality according to the standards.

P-800X Environmentally Hardener is a low-to-medium quality automotive curing agent produced by the company. It is cost-effective and suitable for some markets with relatively high price requirements. Because of its price, it is a low-to-medium product, but even if our products are low-to-medium, we will guarantee the quality and gloss.

product details:

Product name: Enviromentally Hardener Model : P-800X	
Product features	1 Eco-friendly and smooth like mirror 2 Resistant to acid, salt, chemical solvent and oil corrosion, esp. to strong 3 Hardness, abrasion resistant, flexible.
Application	Suitable for cars, cars, buses, trucks, ships, planes, tanks, etc.
Application Method	Spray/Roll/brush
Technical Parameter	Mixing Ratio: paint : Hardener = 2 : 1 Coverage: 3-3.5sqm/kg
Construction process	1 Polish and clean the floor before painting 2 Prime the floor with VIT General Purpose Epoxy Primer WGM-9563 3 Apply middle layer with mixture of primer/paint & quartz mortar 4 Polish and clean the surface Paint one time or twice with General Purpose Epoxy Floor Top Paint WGM-9562

Drying Time			
Temperature	Dust Free	Dry to Handle	Thorough Dry
20°C	30 minutes	10 hours	1 day
60°C	15 minutes	1 hours	1 hour

Sand ability and Polish ability	wet sanding P800 P1000 sand paper if need polish
Shelf Life	5 years in original sealed
Packaging	1L*12 tins /ctn 4L*4tins /ctn

If you are interested, you can contact us, we can provide you with free samples
What packaging do you like, we can also customize the packaging for you.

Customs feedback





Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province