



Hot Sale acrylic car paint Liquid Auto Paints Ceramic Coating Pure white automotive paint

Our Product Introduction

for more products please visit us on refinishcarpaint.com

Basic Information

- Place of Origin: GUANGDONG CHINA
- Brand Name: Ferrari series
- Certification: ISO,SGS,MSDS
- Model Number: 1002
- Minimum Order Quantity: 100 L
- Price: 3.26USD-5USD
- Packaging Details: 0.5L/1L/4L/10L/20L/200L
- Delivery Time: 7-30days
- Payment Terms: T/T
- Supply Ability: 50000L/month



Product Specification

- Main Raw Materials: Acrylic Resin,Polyurethane Resin
- Feature: High Leveling,high Glossy,high Fullness,good Covering,high Adhesion
- Color: Transparent,transparent With Light Yellow
- Substrate: 1k Base Coat
- Shelf Time: 2 Years,at 20
- Component Style: Bi-component
- High Light: Anti Scratch Auto Base Paint, Oil Based Auto Base Paint, Acrylic Car Primer High Adhesion
- Highlight: Pure white car paint, Ceramic Coating car paint, Liquid Auto Paints car paint



More Images



Product Description

Hot Sale acrylic car paint Liquid Auto Paints Ceramic Coating Pure white automotive paint

Product Description

1K Pure White Color Primer is a high-quality one-component paint, commonly used for primer spraying on automotive surfaces. It has the following properties:

High whiteness: 1K pure white color primer has high whiteness and can present bright and pure white, making the surface of the car look fresher and more fashionable.

Good coverage: 1K pure white color primer has strong coverage and can well cover the original color and blemishes, laying a good foundation for subsequent painting operations.

Strong durability: 1K pure white color primer has good anti-ultraviolet, wear-resistant and corrosion-resistant properties, which can effectively protect the surface of the car from the influence of the external environment, making the coating effect more durable.

Quick Drying: 1K Pure White Color Primer dries quickly and can form a flat, smooth surface in a short time, thereby improving the overall appearance quality and value of the car.

Easy to operate: 1K pure white color primer is easy to use, no need to add other substances for mixing, just paint directly on the surface of the car when using it. At the same time, it can also be used in conjunction with other paints in the painting system to produce more colorful effects.

In short, 1K pure white color primer is a high-performance, easy-to-operate paint that can provide excellent protection and aesthetic effects for the coating of automobile surfaces, and is one of the indispensable and important materials in modern automobile manufacturing and maintenance.

Construction technology of 1K solid color basecoat

1K Solid Color Basecoat

The construction process of 1K primer mainly includes the following steps:

Surface treatment: Before 1K primer coating, the surface of the car needs to be cleaned and treated to ensure that the surface is clean, smooth, free of oil and rust and other adverse conditions.

Spray primer: Pour 1K primer paint into the spray gun and spray according to the painting requirements. During the spraying process, it is necessary to control the spray pressure and spraying distance of the paint to ensure that the paint is evenly and finely sprayed on the surface of the car.

Drying: After the 1K primer is applied, it is necessary to wait for the primer to dry completely. The drying time is generally 6-8 hours, and the specific time depends on environmental factors such as temperature and humidity.

Sanding: After the primer has dried, sanding is required to remove surface grain and uneven imperfections. Before grinding, you need to choose the appropriate sandpaper and grinding machine to ensure a good grinding effect.

Coloring: After sanding, coloring is required. If multiple coats of color are required, sanding and washing between coats will be required to ensure a good finish.

Clearcoating: Finally, clearcoating is required to protect the color and finish of the car's surface. Before applying varnish, it needs to wait for the color to dry, and carry out proper sanding and cleaning treatment.

The above is the general construction process of 1K primer, and the specific operation steps need to be adjusted and changed according to the actual situation. In order to ensure the coating effect and coating quality, it is recommended to make adequate preparations and planning before construction, and select suitable coatings and tools.

Packaging Information

Storage
Sealed stored in dry conditions within the temperature range 15°C to 20°C and relative humidity range 55% to 75%.
Shelf Life
24 months (Original sealed under above storage conditions)
Packaging (per carton)
3.75L * 4 can







Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province