



Anti Abrasion Auto Paint Primer Chemical Resistant Weatherproof

Our Product Introduction

for more products please visit us on refinishcarpaint.com

Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: C-506+507
- Minimum Order Quantity: 200L
- Price: 4.23USD/L-4.77USD/L
- Packaging Details: Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500 boxes per day



Product Specification

- Brand: CarCharm
- Name: Two Component Primer
- Net Weigh: 1.2KG+0.3KG
- Application: Brush, Roller, Or Airless Sprayer
- Color: Gray
- Durability: Excellent
- Finish: Smooth
- Highlight: **acrylic auto primer,
Auto Paint Primer Chemical Resistant,
Weatherproof Automotive Paint Primer**



More Images



Product Description

C-506+507 Two Component Primer Good Adhesion Abrasion Resistance Chemical Resistance Good Filling

Two Component primer is a two-component primer, usually consisting of a primer and a curing agent.

performance:

Two Component primer has the following main properties:

Good adhesion: Two Component primer can be firmly attached to the surface of the car body and not easy to fall off.

ABRASION RESISTANCE: Two Component primer has strong abrasion resistance, which can resist the scuffs and scratches of daily use.

Chemical resistance: Two Component primer can resist the erosion of chemicals, such as acid, alkali and so on.

Good filling: Two Component primer can fill tiny depressions and defects on the surface of the car body.

Fast Drying: Two Component primers cure quickly and dry in a short time.

effect:

The main function of Two Component primer is to provide protection and aesthetic effect for the body. It protects the surface of the car body from the external environment, such as ultraviolet rays, oxidation, corrosion and chemicals, etc., while also providing a beautiful appearance to the car body.

Instructions:

Clean the surface of the car body to ensure that the surface is free of impurities such as oil and dust.

Use sandpaper or a sander to smooth the surface of the body.

Mix the primer and curing agent evenly according to the ratio requirements.

Apply the Two Component primer to the body surface with a spray gun or roller.

After the Two Component primer dries, the previous layer of paint can be applied.

Storage conditions:

Two Component primer needs to pay attention to the following points when storing:

It should be stored in a dry, ventilated and cool place, away from fire and high temperature environment.

Long-term storage should be avoided, and it is generally recommended to use it within 1 year.

The opened paint should be sealed and stored to prevent air from entering and affecting the quality.

Two Component primer is an excellent automotive coating material with good properties and characteristics to provide protection and aesthetics to the car body. When using and storing, you need to pay attention to the relevant points to ensure the quality and effect of the paint.



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province