



## UV Proof Durable Car Paint Primer , Anti Oxidation Automotive Epoxy Spray Paint

Our Product Introduction

for more products please visit us on [refinishcarpaint.com](http://refinishcarpaint.com)

### Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: P-508+509
- Minimum Order Quantity: 200Boxes
- Price: 4.91USD-5.54USD
- Packaging Details: Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500 boxes per day



### Product Specification

- Brand: Meiguanda
- Name: Epoxy Primer
- Net Weigh: 1.2KG+0.3KG(set)
- Application: Brush, Roller, Or Spray
- Color: Gray
- Coverage: 400-600 Sq. Ft.
- Interior: Interior/Exterior
- Voc: Low VOC
- Highlight: UV Proof Car Paint Primer, paint and clear coat, 1k and 2k paint



### More Images



## Product Description

### Epoxy Primer For Car Body Protection From UV Rays And Oxidation

#### Product introduction:

Epoxy Primer is an epoxy primer whose main components are epoxy resin and curing agent, with excellent performance and characteristics

#### performance:

Good adhesion: Epoxy Primer can be firmly attached to the surface of the car body and not easy to fall off.

ABRASION RESISTANCE: Epoxy Primer is highly abrasion resistant and resistant to scuffs and scratches from everyday use.

Chemical resistance: Epoxy Primer can resist the erosion of chemicals, such as acid, alkali and so on.

Good corrosion resistance: Epoxy Primer can resist water, humidity and corrosion, prolonging the life of the car body.

Good filling: Epoxy Primer can fill tiny depressions and defects on the surface of the car body.

#### effect:

The main function of Epoxy Primer is to provide protection and aesthetic effect to the car body. It protects the surface of the car body from the external environment, such as ultraviolet rays, oxidation, corrosion and chemicals, etc., while also providing a beautiful appearance to the car body.

#### Instructions:

Clean the surface of the car body to ensure that the surface is free of impurities such as oil and dust.

Use sandpaper or a sander to smooth the surface of the body.

Mix the epoxy resin and curing agent of Epoxy Primer evenly according to the ratio requirements.

Apply Epoxy Primer to the body surface with a spray gun or roller.

After the Epoxy Primer dries, the previous coat can be applied.

#### Storage conditions:

Epoxy Primer needs to pay attention to the following points when storing:

It should be stored in a dry, ventilated and cool place, away from fire and high temperature environment.

Long-term storage should be avoided, and it is generally recommended to use it within 1 year.

The opened paint should be sealed and stored to prevent air from entering and affecting the quality.

Epoxy Primer is an excellent automotive coating material with good properties and characteristics to provide protection and aesthetics to the car body. When using and storing, you need to pay attention to the relevant points to ensure the quality and effect of the paint.



# Epoxy primer



**Guangzhou Meklon Chemical Technology Co., Ltd.**



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province