

## Oil Based Acrylic Car Paint Top Coat 2K Pure Black Mildewproof

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: Faralli
- Certification: ISO,MSDS,SGS
- Model Number: 237
- Minimum Order Quantity: 100 L
- Price: 3.26USD-5USD
- Packaging Details: 1L\*12tins, 4L\*6tins, 4L\*4tins, 0.5L\*24tins,10L, 20L, 200L
- Delivery Time: 5-8days
- Payment Terms: T/T
- Supply Ability: 500000L/month



### Product Specification

- Application Method: Brush, Roller, Or Spray
- Coats Required: 2
- Coverage: 400 Sq. Ft. Per Gallon
- Dry Time: 2 Hours
- Finish: Glossy
- Product Name: Car Paint Topcoat
- VOC Level: Low
- Color: White
- Highlight: Oil Based Car Paint Top Coat, Acrylic Car Paint Top Coat, color correction car paint



### More Images



for more products please visit us on [refinishcarpaint.com](http://refinishcarpaint.com)

## Product Description

### High Application Solvent Oil Based High Gloss Acrylic 2k Pure black Car Paint Auto Refinish Paint

#### Product Description

Pot Life	24 Hours,25°C
No.of Coats	2-3 coats
Flash-off Time	2-3 mins at 25°C
Film Thickness	10~20 micron
Spraying Tool	Gravity feed: 1.2~1.5mm
	Suction feed: 1.2~1.7mm
	spraying pressure: 3-5kg/square centimetre
Drying Time	At 25 °C, after 15 minutes, spray varnish within 1 hours
Using Substrates	The surface of old paint or primer after sanding with the P1000# sandpaper or removing the oil
Others	After spraying 2K metal paint, should spray varnish within 1 hour as much as possible,to ensure the accuracy and repeatability of color formula, stir equably before application

Type	2K car paints and refinishes		
Substrates	Well-Sanded,Completely dried and good existing finishes as below:		
	A. Original paint	B.Old paint firm	C.1K or 2K primer
Mixing Ratio	2K Solid Colors(2)	Hardener(1)	Thinner(0.2-0.4)
<15°C	2K Solid Colors	120 Fast Hardener	602 Fast Thinner
15-30°C	2K Solid Colors	120 Standard Hardener	602 Standard Thinner
>30°C	2K Solid Colors	120 Slow Hardener	602 Slow Thinner
Spray Viscosity	16-19s to drop off, in 4# viscosity cup at 25°C		
Re-Treatment	There are particles or runs after spray, sand affected area with P2000 sand paper after thorough dring, then polish to solve it.		
Spray Gun	Gravity Feed: 1.2-1.5mm	3-5kg/cm <sup>2</sup>	
Set Up	Gravity Feed: 1.4-1.6mm	3-5kg/cm <sup>2</sup>	
Spray	Coats & Thickness: 2-3 coats, total 35-50um		
Technology	Flash-Off Time: At 25°C ,5-10 minutes between two coats		
	Air-Drying Time: Allow 10-15 minutes air drying before force drying		

#### Characteristic:

High gloss and build, good performance of leveling property, easy construction, excellent protective and covering power, long lasting bright color. excellent weathering and chemical resistance.

Mainly applies to intermediate cars, MPV and bus.

#### Why Us:

- 1.The leading professional manufacturer of automotive refinish paints in China .
- 2.Up to 30% increase annually in overseas market .
- 3.China famous Influentail & Innovative Brand in Car Paint Industry.
- 4.Strict quality control and steady product performance .
- 5.Great brand image, advanced color mixing system and excellent customer service system.



**2K  
237**

**2K Pure Black**

***Product Features***

- Commonly used black, slightly brownish-yellowish, used to mix dark colors and metallic colors





**Guangzhou Meklon Chemical Technology Co., Ltd.**



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province