

Mildewproof Metallic Automotive Paint Glossy , Durable Ceramic Top Coat For Cars

Basic Information

- Place of Origin:
- Brand Name: Certification:
- Model Number:
- Minimum Order Quantity: 100 L 3.26USD-5USD
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

- Application Method:
- Coverage:
- Finish:
- Product Name:
- VOC Level:
- Color:
- Material:
- Chemical Resistance:
- Dry Time:
- Coating Type:
- Highlight:



Acrylic

China

Faralli

209

5-8days

500000L/month

T/T

ISO,MSDS,SGS

1L*12tins, 4L*6tins, 4L*4tins,

0.5L*24tins,10L, 20L, 200L

base clear automotive paint, 2 stage automotive paint, car paint and clear coat



More Images



Our Product Introduction

Superior Durability Tinting Mixing System Automotive Refinish HS Low Voc Spray Paint 2K Purple Blue Topcoat

Product Description

Our 2K topcoat is a high-quality paint designed for use in automotive body shops. It offers excellent protective and covering power with longlasting bright color, ensuring that your car's finish looks great for years to come.

Our 2K topcoat also has outstanding mechanical and chemical resistance, which means that it can withstand the wear and tear of everyday use, as well as exposure to harsh chemicals and other contaminants.

The tough and durable film created by our 2K topcoat provides strong anti-UV stability and gloss retention. This means that your car's finish will remain vibrant and glossy even after prolonged exposure to sunlight and other environmental factors.

Our 2K topcoat also delivers a splendid and durable color performance, ensuring that your car looks great and stands out on the road. At our factory, we use only the highest quality raw materials and employ experienced technicians to ensure that our paint products meet strict quality standards. We are committed to providing our customers with high-quality, reliable, and long-lasting automotive coating solutions that meet their specific needs.

Substrates Surface Cleaning	Dried and sanded existing finishes, 1K or 2K Primer Remove wax, silicon and other contaminations with degreaser.
Mixing Ratio	below 18 degree 2K Solid Colors 100 parts Fast Drying Hardener 50 parts Thinner 10-30 parts
	25-30 degreeAbove 30 degree2K Solid colors100 parts2K Solid Colors100 partsStandard Hardener50 partsSlow Drying Hardener50 partsThinner10-30 partsThinner10-30 parts
Pot Life	2 hours, 25 degree; 4 hours, 25 degree
NO. of Coats	2-3 coats, 40-60um
Flash-off time	At 25 degree, 5-10 minutes between coats, allow 15-20minutes flash-off time before baking
Sandability and Polishabiility	Dust particles and minor damages or sagging area can be sanded out with P2000 paper wet after the finish is completely dry. Compound and polish to restore gloss.
Spray Gun &	Gravity Feed 1.2-1.5mm 3-5kg/cm 2
Pressure	Siphon Feed 1.4-1.7mm 3-5kg/cm 2
	Temperature Dust Free Tack Free Dry to Handle Thorough Dry
Drying Time	25 degree 45 minutes 2-3 hours 10 hours 7 days
Shelf life	70 degree 5 minutes 10 minutes 25 minutes 60 minutes 2 years in original sealed can at cool and dry place at 20 degree
	1L, 4L,1Gallon
Packaging	

Packaging Information

Storage Sealed stored in dry conditions within the temperature range 15°C to 20°C and relative humidity range 55% to 75%. Shelf Life 24 months (Original sealed under above storage conditions) Packaging (per carton) 3.75L * 4 can

We specializing in automotive paint, industrial paint, putty, auto & motorcycle & electric vehicle batteries, special hardener, car care products. special unsaturated resin, various types of cans, cartons etc.

Our sales network covers more than 30 countries, and we have more than 1,000 customers in China. We has established good business relationship with the well-known automobile manufacturer, shipbuilding and machinery manufacturer. Our products are favored by domestic and foreign customers for years.













