

Practical Acrylic Car Paint Top Coat Weatherproof Fade Resistant

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 100 L
- Price:

Our Product Introduction

- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

- Application Method:
- Coverage:
- Finish:
- Product Name:
- VOC Level:
- Color:
- Material:

• Dry Time:

• Highlight:

- Chemical Resistance:
- 1-2 Hours

Glossy

Low

Acrylic

Excellent

China

Faralli

210

5-8days

T/T

ISO,MSDS,SGS

3.26USD-5USD

500000L/month

Brush, Roller, Or Spray

400 Sq. Ft. Per Gallon

Color Chart And Customized

Car Paint Topcoat

1L*12tins, 4L*6tins, 4L*4tins,

0.5L*24tins,10L, 20L, 200L

automotive paint hardener, Car Paint Top Coat Weatherproof, Fade Resistant Acrylic Car Coating



More Images



Superior Durability Tinting Mixing System Automotive Refinish HS Low Voc Spray Paint 2K Purple Blue Topcoat

Product Description

Excellent protective and covering power: Our 2K topcoat provides strong protection and coverage for your car's surface, ensuring a long-lasting bright color.

Outstanding mechanical and chemical resistance: Our 2K topcoat is highly resistant to mechanical and chemical damage, making it an ideal solution for use in harsh environments.

Tough and durable film: Our 2K topcoat creates a tough and durable film that provides strong anti-UV stability and loss retention, ensuring that your car's finish remains vibrant and glossy even after prolonged exposure to sunlight. Splendid and durable color performance: Our 2K topcoat delivers a splendid and durable color performance, ensuring that your car looks great and stands out on the road.

At our factory, we take pride in using only high-quality raw materials and employing experienced technicians to ensure that our paint products meet strict quality standards. We are committed to providing our customers with reliable and long-lasting 2K topcoat solutions that meet their specific needs.

Substrates	Dried and sanded existing finishes, 1K or 2K Primer
Surface Cleaning	Remove wax, silicon and other contaminations with degreaser.
Mixing Ratio	below 18 degree 2K Solid Colors 100 parts Fast Drying Hardener 50 parts Thinner 10-30 parts
	25-30 degreeAbove 30 degree2K Solid colors100 parts2K Solid colors100 partsStandard Hardener50 partsThinner10-30 partsThinner10-30 parts
Pot Life	2 hours, 25 degree; 4 hours, 25 degree
NO. of Coats	2-3 coats, 40-60um
Flash-off time	At 25 degree, 5-10 minutes between coats, allow 15-20minutes flash-off time before baking
Sandability and Polishabiility	Dust particles and minor damages or sagging area can be sanded out with P2000 paper wet after the finish is completely dry. Compound and polish to restore gloss.
Spray Gun &	Gravity Feed 1.2-1.5mm 3-5kg/cm 2
Pressure	Siphon Feed 1.4-1.7mm 3-5kg/cm 2
	Temperature Dust Free Tack Free Dry to Handle Thorough Dry
Drying Time	25 degree 45 minutes 2-3 hours 10 hours 7 days
Shelf life	70 degree 5 minutes 10 minutes 25 minutes 60 minutes 2 years in original sealed can at cool and dry place at 20 degree
Packaging	1L, 4L,1Gallon

Packaging Information

Storage
Sealed stored in dry conditions within the temperature range 15°C to 20°C and relative humidity range 55% to
75%.
Shelf Life
24 months (Original sealed under above storage conditions)
Packaging (per carton)
3.75L * 4 can

We specializing in automotive paint, industrial paint, putty, auto & motorcycle & electric vehicle batteries, special hardener, car care products. special unsaturated resin, various types of cans, cartons etc.

Our sales network covers more than 30 countries, and we have more than 1,000 customers in China. We has established good business relationship with the well-known automobile manufacturer, shipbuilding and machinery manufacturer. Our products are favored by domestic and foreign customers for years.





