



Basic Information

Place of Origin: China Brand Name: Faralli

• Certification: ISO,MSDS,SGS

Model Number: 218Minimum Order Quantity: 100 L

• Price: 3.26USD-5USD

Packaging Details: 1L*12tins, 4L*6tins, 4L*4tins, 0.5L*24tins, 10L, 20L, 200L

Delivery Time: 5-8daysPayment Terms: T/T

Supply Ability: 500000L/month



Product Specification

Application Method: Brush, Roller, Or Spray
 Coverage: 400 Sq. Ft. Per Gallon
 Product Name: Car Paint Topcoat

• VOC Level: Low

Color: Color Chart And Customized

• Cleanup: Soap And Water

Fade Resistance: YesSolvent Resistance: YesCoating Thickness: 3-4 Mils

• Feature: Long Lasting, Moisture Resistant, Easy To

Clean, Fast Dry, Smooth

• Highlight: Red Car Paint Top Coat,

Car Paint Top Coat Waterproof,

Chemical Resistant Gloss Red Car Paint



More Images



Product Description

2K Bright Red Auto Paint | Fast Drying Time & High Gloss Coverage Automotive Acrylic

Product Description

2K Deep Red Automotive Paint is a high-quality two-component automotive coating with high gloss, excellent weather resistance, high film thickness, good hardness and excellent adhesion. Compared with traditional one-component paints, 2K deep red car paint can maintain its color and gloss for a long time. In addition, it can be cured at room temperature or by low-temperature baking. It has fast drying speed, strong covering power, and easy spraying. It is suitable for partial spraying of new cars or repairing of old cars. The advantage of 2K deep red car paint lies in its long-term maintenance performance and aesthetics, which can provide the ultimate surface protection for the car, and add high texture and luxury to the car.

Products Catalogue	Package Size	Mxing Ratio(by Volum)	il irv io Handie	Quality assurance time
Primer	1L*12&3.75L* 4	100:25:25	90-120 minutes	4 years
1K Base coat	1L*12&3.75L* 4	100:(10-20)	5 minutes	4 years
2K Solid color	1L*12&3.75L* 4	100:50:(20-30)	24 hours	4 years
Clear coat	5L*4/4L*6/1L*1 2	100:50:(10-20)	90-120 minutes	4 years

2K Automotive Paint Construction Process

Туре	2K	2K car paints and refinishes					
Substrates		Well-Sanded,Completely dried and good existing finishes as below: A. Original paint B.Old paint firm C.1K or 2K primer					
Mixing Ratio	2K	2K Solid Colors(2) Hardener(1)		Thinner(0.	Thinner(0.2-0.4)		
<15°C	2K	Solid Colors	120 Fast I	Hardener	602 Fast T	602 Fast Thinner	
15-30°C	2K	Solid Colors	120 Stand	ard Hardener	602 Stand	602 Standard Thinner	
>30°C	2K	2K Solid Colors 120 Slow Hardener 602 Slow Thinner		Γhinner			
Spray Viscosity	16-	16-19s to drop off, in 4# viscosity cup at 25°C					
Re- Treatment	There are particles or runs after spray, sand affected area with P2000 sand paper after thorough dring, then polish to solve it.						
Spray Gun Set Up		Gravity Feed: 1.2-1.5mm 3-5kg/cm ² Gravity Feed: 1.4-1.6mm 3-5kg/cm ²					
Spray Technolog y	Coats & Thickness: 2-3 coats, total 35-50um Flash-Off Time: At 25°C ,5-10 minutes between two coats Air-Drying Time: Allow 10-15 minutes air drying before force drying						
Drying Time		Temperature	Dust Free	Tack Free	Dry to Handle	Dry to Test	
		25°C	40minutes	2 hours	9 hours	6 days	
		70°C	5 minutes	10 minutes	25 minutes	50minutes	
OEM ODM As customers' or		der					
Shelf Life	Life 2 years in original sealed can, cool and dry place at 25°C						
Package Size 1L*12 Tins or 3.75L*4 Tins							

The 2K Top Coat is a high-quality acrylic paint designed for mid to high-end cars. It offers a range of characteristics that make it an excellent choice for automotive applications, including high gloss, excellent weather resistance, high film thickness, good hardness, and good adhesion. The top coat is suitable for use in both partial spraying of new cars and repairing old cars. Its high-quality formulation ensures a long-lasting finish that is resistant to weather and other external elements. Overall, the 2K Top Coat is a reliable and durable choice for automotive painting that offers excellent gloss and weather-resistant properties.

Advantages:

- 1.Excellent protective and covering power with long lasting bright color.
- 2. Outstanding mechanical and chemical resistance.
- ${\it 3.} \\ Tough and durable film provide strong anti-UV Stability and gloss retention$
- 4. Splendid and durable color performance.

Physical properties

Product Name	2K top coat
Density	0.92-1.25 kg/L
Raw materials	Acrylic Resin, Additive, Solvent,,Polyurethane resin
Colors	multiple colour. See the product list below for details.
Solid content	50%

Notes:

Clear coat should not be sprayed over light-colored paint to prevent the color from turning yellow. Use 800# fineness sandpaper to sand the primer before spraying the topcoat.

Ensure that the primer has thoroughly dried before spraying the topcoat to avoid blisters.























+8613392100968

Meklonpaint@gzmeklon.com

refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province