

Stable Harmless Auto Paint Top Coat , Weatherproof Red Gloss Car Paint

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Faralli
- Certification: ISO,MSDS,SGS
- Model Number: 219
- Minimum Order Quantity: 100 L
- Price: 3.26USD-5USD
- Packaging Details: 1L*12tins, 4L*6tins, 4L*4tins, 0.5L*24tins, 10L, 20L, 200L
- Delivery Time: 5-8days
- Payment Terms: T/T
- Supply Ability: 500000L/month



Product Specification

- Application Method: Brush, Roller, Or Spray
- Coverage: 400 Sq. Ft. Per Gallon
- Product Name: Car Paint Topcoat
- VOC Level: Low
- Color: Color Chart And Customized
- Cleanup: Soap And Water
- Fade Resistance: Yes
- Solvent Resistance: Yes
- Coating Thickness: 3-4 Mills
- Usage: Car Paint
- Highlight: color matched paint, epoxy automotive paint, 1 stage paint



More Images



for more products please visit us on refinishcarpaint.com

Product Description

2K Brilliant Red Car Paint | High Gloss, Fast Drying & Long-term Maintenance

Product Description

Characteristic: Faralli 2K Solid Colors, high gloss and build, good performance of leveling property, easy construction, excellent protective and covering power, long lasting bright color.
Mainly applies to intermediate cars, MPV and bus.

2K Automotive Paint Construction Process

Substrates	Well-Sanded, Completely dried and good existing finishes as bellow: A original paint B. Old paint firm C. 1K or 2k primer				
Surface Cleaning	Wash by warm soap, remove wax, silicon and other contaminations with degreaser, sanding with P800-P1000, wash with clean water then keep dry; again with degreaser.				
Mixing Ratio	Faralli 2K Solid Colors	Hardener	Thinner		
	2	1	0.2-0.4		
15	Faralli 2K Solid Colors	MS120 Fast Hardener	601 Fast Thinner		
15-30	Faralli 2K Solid Colors	MS120 Standard Hardener	602 Standard Thinner		
30	Faralli 2K Solid Colors	MS120 Slow Hardener	603 Slow Thinner		
Spray Viscosity	16-19s to drop off, in 4# viscosity cup, at 25°C,				
Pot-life	At 25°C				
	2 hours with fast hardener.				
	4 hours with standard or slow hardener.				
ReTreatment	There are particles or runs after spray, sand affected area with P2000 sand paper after thorough drying, then polish to solve the problem.				
Spray Gun Set Up	Gravity Feed: 1.2-1.5mm 3-5kg/cm 2				
	Suction Feed: 1.4-1.6mm 3-5kg/cm 2				
Spray Technology	Coats&Thickness: 2-3 coats, total 35-50um				
	Flash-Off Time: At 25°C, 5-10 minutes between two coats,				
	Air-Drying Time: Allow 10-15 minutes air drying time before force drying				
Drying Time	Temperature	Dust Free	Tack Free	Dry To Handle	Dry To Test
	+25°C	40 minutes	2 hours	9 hours	6 Days
	+70°C	5 minutes	10 minutes	25 minutes	50 Minutes
Shelf Life	2 years in original sealed can, cool and dry place at 25 .				
Package	1L×12 or 3.75L×4				

Note:

1. The substrate must be cleaned and sanded before spray, wet sanding P800-1000 and then dry.
2. At ambient temperature higher than 30 , add appropriate Retarder Solvent into thinner to avoid blushing. For more details, please refer to technical data sheet of Retarder Solvent.
3. The products mixed with hardener should be used up soon and can not be restore for future use; clean equipments immediately with thinner after application, otherwise it is very difficult to be





2K
219

2K BRIGHT RED

PRODUCT FEATURES

- COMPARED WITH THE STANDARD DARK RED, SLIGHTLY DARKER THAN BRIGHT RED, THE HIDING POWER IS GOOD



cleaned after dry.



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province