



Practical Multiscene Car Top Coat , Weatherproof Metallic Vehicle Paint

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Faralli
- Certification: ISO,MSDS,SGS
- Model Number: 221
- Minimum Order Quantity: 100 L
- Price: 3.26USD-5USD
- Packaging Details: 1L*12tins, 4L*6tins, 4L*4tins, 0.5L*24tins,10L, 20L, 200L
- Delivery Time: 5-8days
- Payment Terms: T/T
- Supply Ability: 500000L/month



Product Specification

- Application Method: Brush, Roller, Or Spray
- Coverage: 400 Sq. Ft. Per Gallon
- Product Name: Car Paint Topcoat
- VOC Level: Low
- Color: Color Chart And Customized
- Cleanup: Soap And Water
- Fade Resistance: Yes
- Solvent Resistance: Yes
- Coating Thickness: 3-4 Mills
- Usage: Car Paint
- Application Method: Spray, Brush
- Highlight: car paint supplier, Multiscene Car Top Coat, 2k automotive paint



More Images



Product Description

China Professional High Gloss 2K Fuchsia Car Paint Top Coat Automotive Paint

Product Description

Faralli 2K Solid Colors are a premium coating option that is ideal for painting intermediate cars, MPVs, and buses. These coatings offer several desirable characteristics, including high gloss and build, excellent leveling properties, and easy construction. The coatings also have excellent protective and covering power, ensuring long-lasting bright color.

Faralli 2K Solid Colors are specifically designed to provide a high-quality finish that looks great and is highly durable. The coatings have a high solid content, which contributes to their excellent build and protective properties. Additionally, their leveling properties make them easy to apply, ensuring a smooth, even finish.

Overall, Faralli 2K Solid Colors are an excellent choice for anyone looking for a high-quality coating option that delivers excellent performance and long-lasting protection. Whether you're painting an intermediate car, MPV, or bus, these coatings are sure to meet your needs and provide a beautiful, durable finish that will last for years to come.

2K Fuchsia is a high performance paint commonly used in the painting of cars, motorcycles and other vehicles. Here are the features and benefits of 2K Fuchsia:

Unique Color: 2K Fuchsia has a unique color that can give a vehicle a unique look and enhance the vehicle's visual appeal.

High brightness: 2K fuchsia has high brightness, which can improve the glossiness of the vehicle surface, making it look more smooth and textured.

Strong Weather Resistance: 2K Fuchsia is made of high-quality materials with excellent weather resistance, which can maintain good appearance and color stability even in harsh climate conditions.

Strong wear resistance: 2K Fuchsia's coating is very hard and wear-resistant, which can effectively protect the vehicle surface from scratches, abrasions and other damages.

Ease of application: 2K fuchsia is easy to apply, can be applied by spraying or brushing, and has fast drying characteristics, making the application process more efficient.

To sum up, 2K fuchsia has the characteristics of unique color, high brightness, strong weather resistance, strong wear resistance and easy construction. It is a very excellent coating and is suitable for coating a variety of vehicles.

2K Automotive Paint Construction Process

Substrates	Well-Sanded, Completely dried and good existing finishes as below: A original paint B. Old paint firm C. 1K or 2k primer				
Surface Cleaning	Wash by warm soap, remove wax, silicon and other contaminations with degreaser, sanding with P800-P1000, wash with clean water then keep dry; again with degreaser.				
Mixing Ratio	Faralli 2K Solid Colors	Hardener	Thinner		
	2	1	0.2-0.4		
15	Faralli 2K Solid Colors	MS120 Fast Hardener	602 Fast Thinner		
15-30	Faralli 2K Solid Colors	MS120 Standard Hardener	602 Standard Thinner		
30	Faralli 2K Solid Colors	MS120 Slow Hardener	602 Slow Thinner		
Spray Viscosity	16-19s to drop off, in 4# viscosity cup, at 25°C,				
Pot-life	At 25°C 2 hours with fast hardener. 4 hours with standard or slow hardener.				
ReTreatment	There are particles or runs after spray, sand affected area with P2000 sand paper after thorough drying, then polish to solve the problem.				
Spray Gun Set Up	Gravity Feed: 1.2-1.5mm 3-5kg/cm 2 Suction Feed: 1.4-1.6mm 3-5kg/cm 2				
Spray Technology	Coats&Thickness: 2-3 coats, total 35-50um Flash-Off Time: At 25°C, 5-10 minutes between two coats, Air-Drying Time: Allow 10-15 minutes air drying time before force drying				
Drying Time	Temperature	Dust Free	Tack Free	Dry To Handle	Dry To Test
	+25°C	40 minutes	2 hours	9 hours	6 Days
	+70°C	5 minutes	10 minutes	25 minutes	50 Minutes
Shelf Life	2 years in original sealed can, cool and dry place at 25 .				
Package	1L×12 or 3.75L×4				

Note:

1. The substrate must be cleaned and sanded before spray, wet sanding P800-1000 and then dry.
2. At ambient temperature higher than 30 , add appropriate Retarder Solvent into thinner to avoid blushing. For more details, please refer to technical data sheet of Retarder Solvent.
3. The products mixed with hardener should be used up soon and can not be restore for future use; clean equipments immediately with thinner after application, otherwise it is very difficult to be cleaned after dry.





2K
221

2K FUCHSIA

PRODUCT FEATURES

- WITH A PURPLISH HUE, IT IS DEEPER THAN ROSE RED, AND A MORE PURPLISH ROSE RED



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province