

UV Resistant Auto Acrylic Paint Mildewproof Anti Oxidation OEM

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Faralli
- Certification: ISO,MSDS,SGS
- Model Number: 228
- Minimum Order Quantity: 100 L
- Price: 3.26USD-5USD
- Packaging Details: 1L*12tins, 4L*6tins, 4L*4tins, 0.5L*24tins,10L, 20L, 200L
- Delivery Time: 5-8days
- Payment Terms: T/T
- Supply Ability: 500000L/month



Product Specification

- Application Method: Brush, Roller, Or Spray
- Coverage: 400 Sq. Ft. Per Gallon
- Product Name: Car Paint Topcoat
- VOC Level: Low
- Color: Color Chart And Customized
- Cleanup: Soap And Water
- Fade Resistance: Yes
- Solvent Resistance: Yes
- Coating Thickness: 3-4 Mills
- Feature: Long Lasting, Moisture Resistant, Easy To Clean, Fast Dry, Smooth
- Usage: Car Paint
- Highlight: UV Resistant Auto Acrylic Paint, professional auto paint, automotive base coat paint



More Images



for more products please visit us on refinishcarpaint.com

Product Description

Dark Yellow Auto Paint | High Gloss Finish & UV Resistance OEM Acrylic Paint

Product Description

2K topcoats provide excellent protection against chemicals, gasoline, and harsh weather conditions, making them a great choice for long-lasting automotive refinish jobs, as well as new paint jobs.

To apply 2K topcoats, first sand and dry the existing finish, and then apply a 1K or 2K primer. This will ensure proper adhesion and a smooth finish.

High durability: 2K automotive paint is highly durable and can withstand the wear and tear of everyday use. It is resistant to chipping, fading, and scratches, ensuring that your vehicle's paint job remains looking new for longer.

High gloss finish: 2K automotive paint delivers a high gloss finish that enhances the appearance of your vehicle. The coating creates a mirror-like effect that reflects light, making your car look sleek and polished.

Chemical resistance: 2K automotive paint is resistant to a wide range of chemicals, including gasoline, oil, and other automotive fluids. This makes it an ideal coating option for vehicles that are exposed to harsh chemicals on a regular basis.

UV resistance: 2K automotive paint is also resistant to UV radiation, which can cause fading and discoloration of your vehicle's paint job over time. This ensures that your car's paint job remains vibrant and bright for longer.

Easy application: 2K automotive paint is easy to apply, whether you're using a spray gun or a brush. This makes it a popular choice for both professional painters and DIY enthusiasts.

Overall, 2K automotive paint offers a range of advantages that make it an excellent choice for anyone looking to enhance the appearance and durability of their vehicle's paint job. Its high gloss finish, chemical and UV resistance, and ease of application make it a popular choice for automotive painting projects.

Product introduction

Double - component solid paint for medium - and upper-class body painting, the film is hard and glossy, Protective and overprotective. Bright and lasting color, Suitable for the automotive body renovation and repair.

Product characteristics

- ◆ Excellent leveling, rendering perfect coating appearance.
- ◆ High covering power, reduce finished product, improve efficiency.
- ◆ The color is rich and complete to meet the changing color of the car.
- ◆ High gloss, high fullness, excellent mirror effect.
- ◆ Excellent weathering resistance and yellowing properties, endowing the superior performance of the paint film.

Physical parameters

Appearance status	All sorts of color
gloss	highlight
specific gravity	1.0~1.4kg/L (depend on the color)
Nonvolatile component	60±10% (depend on the color)
viscosity	White yellow orange red lemon yellow, etc 200±20S, Other colors 150±20S (-4cups, 25)
auxiliary product	
2 k solid color paint	2K solid paint mixing with each other
thinner	Advanced thinner (A380, A381, A382)
Hardener	Paint Hardener (A210, A211, A212)

Construction parameters

	2 k solid color paint	100 volume
Mix proportion	High concentration hardener	50 volume
	Advanced thinner	20-30 volume
pot life	4 hours 25	
Spraying viscosity	16~20 seconds (-4cups, 25)	
Spraying tool	Upper pot spray gun diameter of 1.2 ~ 1.5mm	The lower pot nozzle diameter is 1.2 ~ 1.7mm
Spraying pressure	Gun pressure for 3-5KG/c	
Spraying method	Double or triple single spray, The gun is 15~20cm. Each layer of volatilization time is 10~15 minutes (25)	
drying time	At 25 , 30 minutes of non-stick dust. Hard dry: 24 hours/25 or 1 hour/60	
Using range	After the P800 #, P1000 # sand paper is sanded, or the paint surface and primer surface after oil pollution	

Packing specification

4L*4; 1L*12

storage

The storage period of the open tank is 5 years





2K
222

2K IRON OXIDE RED

PRODUCT FEATURES

- WITH A YELLOW HUE, IT IS USED FOR FINE-TUNING OR BLENDING COLORS WITH LOWER CHROMA, WITH GOOD HIDING POWER



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province