

# Advanced Raw Materials Auto Paint High Application HS 1K Crystal Red Car

# **Basic Information**

. Place of Origin: **GUANGDONG CHINA** 

Brand Name: Ferrari series · Certification: ISO,SGS,MSDS

Model Number: X-02 • Minimum Order Quantity: 100 L

• Price: 3.26USD-5USD

0.5L/1L/4L/10L/20L/200L · Packaging Details:

• Delivery Time: 7-30days Payment Terms: T/T

. Supply Ability: 50000L/month



# **Product Specification**

Main Raw Materials: Acrylic Resin, Polyurethane Resin

Feature: High Leveling, high Glossy, high

Fullness,good Covering,high Adhesion

Transparent, transparent With Light Yellow Color:

Substrate: 1k Base Coat Shelf Time: 2 Years, at 20 • Component Style: Bi-component

• High Light: Anti Scratch Auto Base Paint, Oil Based Auto

Base Paint, Acrylic Car Primer High

. Highlight: 1K Crystal Red Car Paint,

**Advanced Raw Materials Car Paint** 



# More Images



## **Product Description**

### Advanced Raw Materials Auto Paint High Application HS 1K Crystal Red Car Paint

#### **Product Description**

Crystal red pearl coating is a high-end automotive coating with unique performance and characteristics. Firstly, the crystal red pearl coating has a pearl luster, which is a mixture of various pigments and special pearl powder, which can create a three-dimensional and layered feeling on the surface of the car body. In addition, crystal red pearl paint has the characteristics of bright colors and high color saturation, which can attract people's attention and add bright colors to vehicles.

The crystal red pearl coating also has good weather resistance and can resist the erosion of harsh environments such as ultraviolet radiation, oxidation, and acid rain, maintaining a long-lasting aesthetic effect. During the construction process, crystal red pearl coating is easy to apply and can be completed in a short time, improving work efficiency. In addition, the surface of the crystal red pearl coating is smooth and delicate, with a comfortable feel, which can enhance the grade and taste of the vehicle.

The crystal red pearl coating also has good scratch resistance, which can effectively prevent scratches and wear on the surface of the car body and maintain its aesthetics. At the same time, the color of the crystal red pearl paint will change with the changes in angle and light, making the surface of the vehicle appear in various colors, which is very eye-catching.

Overall, crystal red pearl coating is a high-end automotive coating with various outstanding characteristics, including pearl luster, bright color, good weather resistance, easy construction, comfortable texture, and scratch resistance. It can enhance the appearance and quality of vehicles and is a very popular coating in the field of automotive beauty and decoration.

	Well-Sanded, Completely dried and good existing finishes as bellow:	
ouboti atoo	A original paint B. Old paint firm C. 1K or 2k primer	
	Wash by warm soap, remove wax, silicon and other contaminations with degreaser, sandingwith P800-P1000,	
	wash with clean water then keep dry;again with degreaser.	
Mixing Rati	1K Crystal Pearl Colors X-02, Car Basecoat Colors	Thinner
0	1	1
15	1K Crystal Pearl Colors X-02	602 Fast Thinner
15-30	1K Crystal Pearl Colors X-02	602 StandardThinner
	1K Crystal Pearl Colors X-02	602 Slow Thinner
Spray Visco	14-16s to drop off, in 4# viscositycup at 25°C,	
,		
ReTreatme nt	After spray, allow 10-20 minutesair-drying time,then spray clear coat at once.	
Spray	Gravity Feed: 1.2-1.5mm 3-5kg/cm 2	
Gun Set Up	Suction Feed: 1.4-1.6mm 3-5kg/cm 2	
	Coats&Thickness: 2-3 coats, total 15-20um.	
nology	Flash-Off Time: At 25°C, 5-10 minutes between two coats, it depends on temperature and paint film.	
Shelf Life	2 years in original sealed can, cool and dry place at 25.	
Package	IL×12 or 3.75L×4	
Noto:		

#### Note

- 1. The substrate must be cleaned and sanded before spray, wet sanding P800-1000 and then dry.
- 2. At ambient temperature higher than 30, add appropriate Retarder Solvent into thinner to avoid blushing. For more details, please refer to technical data sheet of Retarder Solvent.
- 3. To avolid problems of mottling or poor adhesion, the metallic paint film should be 15-25um.

















Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province