



## Nontoxic Copper Car Pearl Paint Weatherproof Anti UV Glossy Finish

### Our Product Introduction

for more products please visit us on [refinishcarpaint.com](http://refinishcarpaint.com)

#### Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: P-305
- Minimum Order Quantity: 200Boxes
- Price: 4.64USD-6.92USD
- Packaging Details: Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500 boxes per day




#### Product Specification

- Application: Spray
- Chemical Resistance: Yes
- Coverage: 10-12 Sq. Ft.
- Fade Resistance: Yes
- Finish: Glossy
- Heat Resistance: Yes
- Number Of Coats: 2-3
- Product Name: Car Pearl Paint
- Scrub Resistance: Yes
- Sheen: High Gloss
- UV Resistance: Yes
- Water Resistance: Yes
- Highlight: quick car paint repair,  
Car Pearl Paint Weatherproof,  
Anti UV Copper Pearl Auto Paint



#### More Images



## Product Description

### Meklon High-end P-305 Copper Pearl Car Paint with Pearl Texture and Copper Sheen

Pearl car paint is a unique and high-end car paint color, with copper color on the front, golden yellow on the side, medium grain, opaque and good hiding power.

#### Advantage:

**Pearl texture:** Tiny copper-colored pearl particles are added to the copper pearl car paint, giving the paint surface a rich pearl texture. These pearl particles will produce subtle light and shadow effects under sunlight, making the color of the car body appear layered and three-dimensional. The texture of copper pearls gives a unique and fashionable feeling.

**Copper Sheen:** Copper Pearl car paint exhibits a warm, rich copper sheen. Copper is a unique metallic color that contrasts with common automotive paint colors, making the vehicle more visually striking and unique.

**Highly reflective:** Copper pearl car paint has good light reflective properties, which can reflect most of the light, making the surface of the car body look bright and shining. This highly reflective property makes the vehicle more dazzling in the sun, adding a sense of luxury and luxury.

**RARE AND UNIQUE:** Copper pearl car paint is relatively rare and unique due to its high manufacturing process and material cost. Car owners who choose copper pearl car paint can show their individuality and distinctive taste, making their vehicles stand out among many fleets.

**Strong weather resistance:** copper pearl car paint usually adopts high-quality materials and advanced coating technology, and has good weather resistance. It resists sunlight, rain, dirt and other external elements, maintaining the gloss and color stability of the paint finish.










#### PROSHICHE 1K Basecoat Colors:

Operation Parameter		
Substrates	The surface of old paint or primer after polishing.	
Surface Cleaning	Sanding with the sandpaper or removing the oil, wax and silicon with Degreaser.	
Mixing Ratio	PROSHICHE 1K metallic paint 1 (Volume)	PROSHICHE high performance and P-602 universal thinner 1-1.2 (Volume)
Pot Life at 25°C	4 hours	
Spraying Viscosity	14~18 seconds (Tu-4 cup viscosity, 25°C)	
Spray Gun Set Up	Gravity feed: 1.2~1.5mm	
	Suction feed: 1.2~1.7mm	
	The pressure of spray gun is 3~5 kg/cm <sup>2</sup>	
Coats & Thickness	2-3 coats, 10-20um	
Flash-off Time	At 25°C, 2-3 minutes	
Drying Time	At 25 °C, after 15 minutes, spray varnish within 1 hours	

#### Operation parameter:

	Ambient Temperature	Basecoat Colors	Thinner
Mixing Ratio	<15°C	1	1-1.2
	15-30°C	1K metallic paint	DF501, DF101K
	15-30°C	1K metallic paint	DF502, DF101B
	>30°C	1K metallic paint	DF503, DF101M
Pot Life	24 Hours, 25°C		
Spray Gun Set Up	Gravity feed: 1.2~1.5mm		
	Suction feed: 1.2~1.7mm		
	The pressure of spray gun is 3-5 kg/cm <sup>2</sup>		
Spray-Painted Method	Thin spray 2 ~3 layers with a air pressure of 3.5 kg, the volatilization time is 2 ~ 3 minutes (25°C), spraying distance is 15~20cm. After covered completely, spray the last layer with 2 kg air pressure. After volatilize for 5 ~ 10 minutes but not more than 1 hour, spray varnish.		
Film Thickness	10~20 micron		
Drying Time	At 25 °C, after 15 minutes, spray varnish within 1 hour.		
Range of Application	The surface of old paint or primer after polishing with the sandpaper or removing the oil.		
Others	After spraying 1K metal paint, should spray varnish within 1 hour as much as possible, to ensure the accuracy and repeatability of color formula, stir equably before application.		

#### Picture:

	Surface Cleaning: Use a Degreasing Cleaner to Remove Wax, Oil, and Other Impurities.		
	The Mixing Ratio (Volume Ratio)		
	Clear Coat	+	Drying Agent
	100		50
	<15°C	p-8000	p-8001
	18-24°C	p-8000	p-8002
	25-30°C	p-8000	p-8002
	> 30°C	p-8000	p-8003
 	Spray Viscosity: 14-16 Seconds(23°C, coating-4 cups) Available Time: At 23°C, P-8001 High-solid Quick-Drying Agent: 2 hours; P-8002 High Solid Standard Drying Agent and P-8003 High Solid Slow Drying Agent: 4 hours		
	Recommended Spray Tool and Air Pressure:		
	RP Spray Gun: Caliber: 1.3mm Air Pressure: 2.0-2.5 (bar)		
	HVLP Spray Gun: Caliber: 1.3mm Air Pressure: 1.8-2.0 (bar)		
 	Number of Spray Layers/Film Thickness: 2-3Level,40-60um Flash Time: At 23°C, Flash Dry Between Layers for 5-10 Minutes Rest Time: After 15-20 Minutes you can Heat up and Bake.		
	Drying Time:		
	Temperature	No Stick Time	Polishable time
	15°C	80 minutes	15 hours
	23°C	70 minutes	6 hours
	60°C	15 minutes	40 minutes



P305

COPPER PEARL

#### PRODUCT FEATURES

- THE FRONT IS RED COPPER, THE SIDE IS GOLDEN, THE PARTICLES ARE MEDIUM OPAQUE, AND THE HIDING POWER IS GOOD



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province