



## Orange Red Acrylic Clear Coat Automotive Painting Waterproof Nontoxic

### Our Product Introduction

#### Basic Information

- Place of Origin: GUANGDONG CHINA
- Brand Name: Ferrari series
- Certification: ISO,SGS,MSDS
- Model Number: F-135
- Minimum Order Quantity: 100 L
- Price: 3.26USD-5USD
- Packaging Details: 0.5L/1L/4L/10L/20L/200L
- Delivery Time: 7-30days
- Payment Terms: T/T
- Supply Ability: 50000L/month



#### Product Specification

- Main Raw Materials: Acrylic Resin,Polyurethane Resin
- Feature: High Leveling,high Glossy,high Fullness,good Covering,high Adhesion
- Certification: Pigment
- Substrate: 1k Base Coat
- Coating Type: Acrylic
- Mildew Resistant: Yes
- Transport Package: In Standard Export Cartons
- Dry Film Thickness: 1.5-2.0 Mills
- Coating Material: Acrylic
- Color: 1K Orange Red
- Highlight: auto body paint repair, Acrylic Clear Coat Automotive Waterproof, auto repair paint



#### More Images



## Product Description

### Super High Gloss Car Paint 1K orange red Base Coat Automotive Paint Pintura

#### Product Introduction

Meklon-Coat Basecoat is a highly versatile automotive paint basecoat designed for easy mixing and application. It offers excellent coverage and ensures optimal color match, making it ideal for imitating OEM solid, metallic, and pearl color effects. For best results, Meklon-Coat Basecoat should be used in combination with Meklon-Coat clearcoat to provide enhanced durability and longevity. This combination ensures a robust and long-lasting paint finish that can withstand various environmental conditions.

Prior to application, proper surface preparation is crucial. Old or original paintwork should be thoroughly sanded and cleaned to create a smooth and even surface. Primer-surfacer or surfacer can be applied, either sanded and cleaned or left unsanded in a wet-on-wet process. It is essential to ensure that surfaces are correctly prepared and cleaned to achieve optimal adhesion and a flawless finish.

When it comes to repair areas, sanding should be performed using P500-P600 grit (by machine) or P800-P1000 grit (by hand) to achieve the desired smoothness. After sanding, thorough cleaning of the repair areas is necessary to remove any contaminants or debris.

Meklon-Coat Basecoat offers an array of impressive features. It forms a hard paint film with excellent leveling performance, facilitating easy application. The basecoat exhibits strong adhesion and exceptional outdoor weather resistance, ensuring long-lasting protection against the elements. Additionally, it has a prolonged anti-oxidation time, further contributing to its durability. Meklon-Coat Basecoat is compatible with various plain colors, metallic effects, and pearl effects, allowing for creative customization options. It provides excellent adhesion between layers, ensuring a seamless and professional finish.

In summary, Meklon-Coat Basecoat is a versatile automotive paint basecoat with exceptional coverage and color-matching capabilities. When used in conjunction with Meklon-Coat clearcoat, it offers enhanced durability. Proper surface preparation is essential, and the basecoat exhibits a range of desirable features, including a hard paint film, easy application, strong adhesion, excellent weather resistance, and compatibility with different color effects. Choose Meklon-Coat Basecoat for a high-quality and long-lasting automotive paint solution.

#### Specification:

Product name	1K BASE COAT 1K Orange Red
Mixing ratio	1: 1-1.2 100 parts 1K Base coat 100-120 parts Thinner
Spray coats	Spray 2-3 layers, the flash-off time is 5 to 8 mins.
Dry Time	15 min(20°C)
Shelf Life	2 years in original sealer in cool and dry place at 20°C
Packaging (per carton)	1L*12can, 4L*4can
Product advantages	Extra fast drying and high quality finishing. Good color covering power and leveling. Varied color cover full range with high color saturation.
Instructions	Spray
Brand Name	Meklon

#### Application method

spray gun	Gravity gun	Suction gun
	gun nozzle: 1.2mm, gun pressure: 2.0-3.0 MPa	gun nozzle: 1.5mm, gun pressure: 2.0-3.0 Mpa
substrate	dry 1K primer surface with smooth effect	
Paint preparation	1k paint- thinner-EX10/EX20/EX30	
mix ratio	1 : 1 (base paint : thinner)	
spraying layers	2-3 coats	
flash off time	3-5 mins , 20-25	
surface dry time	15-20mins	
Time to Polish	1h, P1000 sanded paper	
Relationship between drying temperature and time of 1K base coat		
Tenmperture	Surface Drying time	Time to Polish
25	10-15 mins	1 hour
35	5-10 mins	40 mins
60	3-5 mins	15 mins



**1K  
135P**

**1K FUCHSIA**

**PRODUCT FEATURES**

- ORANGE-RED YELLOWISH PHASE,  
BRIGHT AND BRIGHT, HIGH CHROMA,  
LEADED CHROME





**1K  
135P**

**1K FUCHSIA**

**PRODUCT FEATURES**

- ORANGE-RED YELLOWISH PHASE,  
BRIGHT AND BRIGHT, HIGH CHROMA,  
LEADED CHROME







1K  
135P

1K FUCHSIA

PRODUCT FEATURES

- ORANGE-RED YELLOWISH PHASE,  
BRIGHT AND BRIGHT, HIGH CHROMA,  
LEADED CHROME



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province