

Mud Yellow 1K Car Paint Basecoat Mildew Resistant Acrylic Coating

Our Product Introduction

Basic Information

- Place of Origin: GUANGDONG CHINA
- Brand Name: Ferrari series
- Certification: ISO,SGS,MSDS
- Model Number: F-136
- Minimum Order Quantity: 100 L
- Price: 3.26USD-5USD
- Packaging Details: 0.5L/1L/4L/10L/20L/200L
- Delivery Time: 7-30days
- Payment Terms: T/T
- Supply Ability: 50000L/month



Product Specification

- Main Raw Materials: Acrylic Resin,Polyurethane Resin
- Feature: High Leveling,high Glossy,high Fullness,good Covering,high Adhesion
- Certification: Pigment
- Substrate: 1k Base Coat
- Coating Type: Acrylic
- Mildew Resistant: Yes
- Transport Package: In Standard Export Cartons
- Dry Film Thickness: 1.5-2.0 Mills
- Coating Material: Acrylic
- Color: 1K Mud Yellow
- Highlight: **Mud Yellow Car Paint Basecoat, car primer, 1K Acrylic Coating For Cars**



More Images



for more products please visit us on refinishcarpaint.com

Product Description

China Popular 1K Mud Yellow Base Coat Auto Paint Pintura Car Paint

Product Introduction

Meklon-Coat Basecoat stands out as a highly versatile automotive paint basecoat specifically engineered for effortless mixing and application. Its remarkable coverage ensures flawless results and guarantees an optimal color match, making it the perfect choice for replicating OEM solid, metallic, and pearl color effects.

To achieve the best outcome, it is recommended to pair Meklon-Coat Basecoat with Meklon-Coat clearcoat, amplifying the overall durability and longevity of the paint finish. This powerful combination creates a robust and long-lasting protective layer that can endure a wide range of environmental conditions.

Prior to applying the basecoat, meticulous surface preparation is paramount. Thoroughly sanding and cleaning the existing or original paintwork is essential to establish a smooth and uniform canvas. The application of primer-surfacer or surfacer, whether sanded and cleaned or left unsanded in a wet-on-wet process, contributes significantly to the achievement of impeccable adhesion and a flawless final appearance.

When addressing repair areas, sanding with precision, utilizing P500-P600 grit (by machine) or P800-P1000 grit (by hand), is crucial to attain the desired level of smoothness. Subsequently, comprehensive cleaning of the repaired sections becomes imperative to eliminate any form of contamination or debris that may compromise the end result.

Meklon-Coat Basecoat boasts an array of impressive features that elevate its performance. It forms a robust paint film that exhibits exceptional leveling properties, facilitating effortless application. The basecoat exhibits a superior level of adhesion, ensuring a strong bond with the surface, while its outstanding resistance to outdoor elements guarantees enduring protection. Additionally, its extended anti-oxidation time further enhances its durability and longevity. By seamlessly blending with a diverse range of plain colors, metallic effects, and pearl effects, Meklon-Coat Basecoat unleashes limitless creative possibilities for customization. Its exceptional inter-layer adhesion ensures a flawlessly smooth and professional finish.

In summary, Meklon-Coat Basecoat represents a versatile solution in the realm of automotive paint basecoats, offering unparalleled coverage and precise color matching capabilities. When combined with Meklon-Coat clearcoat, its durability is further enhanced. Adhering to meticulous surface preparation, this basecoat delivers outstanding features, including a resilient paint film, effortless application, strong adhesion, exceptional weather resistance, and compatibility with an extensive range of color effects. Make Meklon-Coat Basecoat your preferred choice for an automotive paint solution that guarantees high quality and long-lasting performance.

Specification:

Product name	1K BASE COAT 1K Mud Yellow
Mixing ratio	1: 1-1.2 100 parts 1K Base coat 100-120 parts Thinner
Spray coats	Spray 2-3 layers, the flash-off time is 5 to 8 mins.
Dry Time	15 min(20°C)
Shelf Life	2 years in original sealer in cool and dry place at 20°C
Packaging (per carton)	1L*12can, 4L*4can
Product advantages	Extra fast drying and high quality finishing. Good color covering power and leveling. Varied color cover full range with high color saturation.
Instructions	Spray
Brand Name	Meklon

Application method

	Gravity gun	Suction gun
spray gun	gun nozzle: 1.2mm, gun pressure: 2.0-3.0 MPa	gun nozzle: 1.5mm, gun pressure: 2.0-3.0 MPa
substrate	dry 1K primer surface with smooth effect	
Paint preparation	1K Mud Yellowpaint-thinner-EX10/EX20/EX30	
mix ratio	1 : 1 (base paint : thinner)	
spraying layers	2-3 coats	
flash off time	3-5 mins , 20-25	
surface dry time	15-20mins	
Time to Polish	1h, P1000 sanded paper	
Relationship between drying temperature and time of 1K base coat		
Tenmperture	Surface Drying time	Time to Polish
25	10-15 mins	1 hour
35	5-10 mins	40 mins
60	3-5 mins	15 mins



1K
136P

1K MUD YELLOW

PRODUCT FEATURES

- WITH RED PHASE, LOW CHROMA, GOOD HIDING POWER, GOOD WEATHER RESISTANCE





**1K
135P**

1K FUCHSIA

PRODUCT FEATURES

- ORANGE-RED YELLOWISH PHASE,
BRIGHT AND BRIGHT, HIGH CHROMA,
LEADED CHROME





1K
135P

1K FUCHSIA

PRODUCT FEATURES

- ORANGE-RED YELLOWISH PHASE,
BRIGHT AND BRIGHT, HIGH CHROMA,
LEADED CHROME



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province