



ISO9000 Polyester Auto Body Filler Putty For Car Repair Odorless Waterproof

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Faralli
- Certification: ISO9000
- Model Number: F-350 Body Filler
- Minimum Order Quantity: 200Boxes
- Price: 4.05USD-5.34USD
- Packaging Details: Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500 boxes per day



Product Specification

- Adhesion: Good
- Color: Dust
- Compatibility: Good
- Coverage: High
- Density: Medium
- Drying Time: Medium
- Flexibility: High
- Impact Resistance: High
- Sandability: Good
- Weatherability: Good
- Viscosity: Medium
- Highlight: mixing 2k paint, professional clear coat, oem clear coat



for more products please visit us on refinishcarpaint.com

Product Description

Professional Auto Primer Filler Putty for Car Repair

Product description

Quick-drying, easy-to-sand, easy-to-scratch one-component eye-filling product. Used in conjunction with the intermediate paint, used to fill the fine blisters and other defects before spraying the top paint, Resting, playing the role of filling, sealing and enhancing the adhesion between the paint film layers, thereby improving the appearance of the paint film and the overall performance of the paint film. main

Used for painting and repairing other industrial parts such as car bodies, trunks and parts. It is matched with one-component or two-component intermediate coating of the Porsche series

Painted surface, hardened and polished old paint surface, not suitable for metal surface, can not replace putty.

Products and additives: Composed of acrylic resin, pigments, fillers, etc.

Applicable surface: Used for clean one-component or two-component primer surface, treated old paint surface

Surface treatment: After sanding the old paint surface and intermediate coating surface, thinly scrape P-5900 to fill the eye gray product

The mixing ratio: Can be used directly

Construction method: Tools used: gray knife or flexible blade; the substrate must be dusted and dried before construction

Construction process: Suitable for squeegee, thin squeegee 1-2 layers, pay attention not to thick squeegee or large area squeegee at one time

Film thickness: Dry film does not exceed 0.1mm

Scraper cleaner: Use Porsche's solvent or thinner

Drying time: At 20°C, the surface is dry for 10-15 minutes. When scraping thick parts, the polishing time can be extended accordingly. After 20 /35 minutes, it can be polished with 600#-800# wet sanding, and the top coat can be sprayed after the water vapor dries. If the bottom is polished, 1K or 2K intermediate coating can be sprayed locally to ensure the smoothness and beauty of the paint film.

Recoat ability: After sanding the old paint surface or intermediate coating, P-5900 Eye Filler can be recoated with the following products after flashing dry for 10-15 minutes at 20 :

Single (double) component middle coating

Single (two) component top coat

Packing: 1Kg round can, 300 toothpaste tube

colour: Red Grey

Shelf life: P-5900 Eye Filling: Storage period of 2 years at room temperature without opening the package

Our benefit

In comparison to the traditional putties used in my country, such as tung oil putty, perchlorethylene putty, alkyd putty, etc., putty contains fine gray matter, is quick to dry, has strong adhesion, and is extremely hard. It is also easy to scrape, fill, and polish.





Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong
Province