



Heatproof 2K Automotive Clear Coat UV Resistant Multipurpose

Basic Information

Place of Origin: GUANGDONG CHINA
 Brand Name: Meshilianke series
 Certification: ISO,SGS,MSDS

Model Number: 8600Minimum Order Quantity: 100 L

• Price: 3.26USD-5USD

• Packaging Details: 0.5L/1L/4L/10L/20L/200L

Delivery Time: 7-30daysPayment Terms: T/T

Supply Ability: 50000L/month



Product Specification

Main Raw Materials: Acrylic Resin, Polyurethane Resin

• Feature: High Leveling, high Glossy, high

Fullness,good Covering,high Adhesion

Color: Transparent,transparent With Light Yellow

Substrate: 1k Base CoatShelf Time: 2 Years,at 20Component Style: Bi-component

High Light: Anti Scratch Auto Base Paint, Oil Based Auto

Base Paint, Acrylic Car Primer High

Adhesion

Product Name: Car Clear Coat Varnish

• Highlight: auto body car paint, metallic color paint for car,

1k car paint



Product Description

Car Refinish Paint Wholesale Fast Drying 2K Clear Coat Top Coat Automotive Paint

The Clear Coat

High hardness, high gross, alcohol and gasoline resistance, protection, durability, and brightness

To meet the needs of our customers, we offer three types of high performance varnish: economic, standard, and high solid content, all of which have high hardness, high gloss, and resistance to alcohol and gasoline. The clear coat can give protection, durability, and brightness after spraying on the 1K base coat. After two wet sprays, the crystal gleaming and smooth effect can be attained.

Spray: Wet spray two to three layers, with a 5-10 minute flash-off period between layers.

Applicable time: 2 hours at 20 °C

Drying time: 40 minutes for surface dry, 12 hours for thorough dry at 20 °C.40 minutes baking time at 60 °C

Туре	Clear Coat					
Substrates	1K Basecoat					
Mixing Ratio	Clear Coat(2)	Hardener(1)		Thinner(0.2-0.	Thinner(0.2-0.5)	
<15°C	8600 Clear Coat	120 Fast Har	120 Fast Hardener		602 Fast Thinner	
15-30°C	8600 Clear Coat	120 Standard	120 Standard Hardener		602 Standard Thinner	
>30°C	8600 Clear Coat	120Slow Hard	120Slow Hardener		602 Slow Thinner	
Spray Viscosity	16-19s to drop off, in 4# viscosity cup at 25°C					
Re- Treatment	There are particles or runs after spray, sand affected area with P2000 sand paper after thorough dring, then polish to solve it.					
Spray Gun Set Up	Gravity Feed: 1.2-1.5mm 4-5kg/cm² Gravity Feed: 1.4-1.6mm 4-5kg/cm²					
Spray Technology	Coats & Thickness: 2-3 coats, total 25-35um Flash-Off Time: At 25°C, 5-10 minutes between two coats Air-Drying Time: Allow 10-15 minutes air drying before forcedrying					
	Temperature	Dust Free	Tack Free	Dry to Handle	Dry to Test	
Drying Time	25°C	30minutes	2 hours	8 hours	6 days	
	70°C	5 minutes	10 minutes	25 minutes	60minutes	
OEM ODM As customers' orde		er	·			
Shelf Life	2 years in original s	2 years in original sealed can, cool and dry place at 25°C				
Package Size	5I *4 Tins or 2.5I *8	5L*4 Tins or 2.5L*8 Tins or 5L+2.5L+1L				

PREPARE THE SURFACE:

- 1. The surface should be clear of dust, grease, and oil.
- 2. Sand the old varnish surfaces with 1200 grit sandpaper before applying the clear coat.

Polishing: It is advisable to polish after the paint has dried overnight.

Product Description:

The varnish products made by Meklon automotive paint provide a variety of advantages and impacts, especially in the following areas:

Meklon automotive paint varnish solutions successfully protect the surface of the car from environmental dangers including UV radiation, acid rain, oxidation, and corrosion, extending the paint's life and reducing wear and scratches on the surface.

Enhancement of Gloss: The varnish product has a high gloss, which may reflect more light and color, giving the surface of the automobile a more brilliant appearance and increasing the car's quality and value.

Packing

- 1. Each can is 1L, and there are 12 cans in a carton.
- 2. Each can is 3.75L, and there are four cans in a carton.
- 3. Each can is 4L and comes in a carton of four.
- 4. Each can is 18L, and there are two cans in each carton.

After-Sales Support

Meklon offers skilled technical assistance, paint mixing training, paint spraying training, and other services.

Our Services and Products

- 1. Good goods at a reasonable price.
- 2. The color mixing method has been revised.
- 3. We attend trade exhibitions all around the world to advertise our products and to support our distributors in promoting in their individual markets.
- 4. We visit our distributors and significant clients to acquire information about automobile painting trends and suggestions for improving our product development.
- 5. To protect the safety of our customers' containers, we handle all export procedures.





+8613392100968

Meklonpaint@gzmeklon.com

refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province