

# Stable Base Coat Car Clear Coat Varnish Mildewproof Anti Scratch

## **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- · Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



**GUANGDONG CHINA** 

Meshilianke series

- 100 L 3.26USD-5USD
  - 0.5L/1L/4L/10L/20L/200L

50000L/month

- 7-30days
- T/T



# **Product Specification**

- Main Raw Materials:
- Feature:
- Color:
- Substrate:
- Shelf Time:
- Component Style:
- High Light:
- Product Name:
- Highlight:

- Acrylic Resin, Polyurethane Resin High Leveling, high Glossy, high Fullness,good Covering,high Adhesion
- Transparent, transparent With Light Yellow
- 1k Base Coat
- 2 Years, at 20
- **Bi-component**
- Anti Scratch Auto Base Paint, Oil Based Auto Base Paint, Acrylic Car Primer High Adhesion
- Car Clear Coat Varnish
  - special car paint, mixing base coat paint, 1k basecoat car paint



Our Product Introduction

### Automotive Paint Colors Car Paint 1K Basecoat Automotive Spray Car Paint Clear Varnish

Clear Coat: To meet the needs of various customers, we offer three types of high performance varnish: economic, standard, and high solid content, all of which have high hardness, high gloss, and resistance to alcohol and gasoline. The clear coat can give protection, durability, and brightness after spraying on the 1K base coat. After two wet sprays, the crystal gleaming and smooth effect can be attained.

Temperature & Match	Temperat ure	Clear Coat	Hardener	Thinner
	115	Clear Coat	Economic/Standard/High Solid Type Fast Dry Hardener	Fast Dry Thinner
			Economic/Standard/High Solid Type Standard Hardener	Standard Thinner
	25-35		Economic/Standard/High Solid Type Slow Dry Hardener	Slow Dry Thinner
Mixing Ratio		2	1	0.2-0.5

Spray: Wet spray two to three layers, with a 5-10 minute flash-off period between layers.

Applicable time: 2 hours at 20 °C

Drying time: 40 minutes for surface dry, 12 hours for thorough dry at 20 °C.40 minutes thorough drying at 60 °C.

Polishing: It is advisable to polish after the paint has dried overnight.

1L\*15, 5L\*4 packing

High-quality, anti-yellowish hardener. We have three types: Economic, Standard, and High Solid Content (HS), as well as three models: Fast Dry, Standard, and Slow Dry. It is appropriate for 2K tinters, 2K ready mixed paint, and clear coat.

Thinner: Thinner is classified as Fast Dry, Standard, or Slow Dry. It is used in 2K paint, 1K paint, clear coat, 2K primer, and other products. It has a good dissolving rate and promotes bonding.

### PREPARE THE SURFACE:

1. The surface should be clear of dust, grease, and oil.

2. Sand the old varnish surfaces with 1200 grit sandpaper before applying the clear coat.

Polishing: It is advisable to polish after the paint has dried overnight.

#### **Product Description:**

Meklon automotive paint varnish products offer a variety of benefits and impacts, particularly in the following areas:

Meklon automobile paint varnish solutions successfully protect the car's surface against environmental hazards such as UV radiation, acid rain, oxidation, and corrosion, extending the paint's life and decreasing surface wear and scratches.

Gloss Enhancement: The varnish product has a high gloss, which may reflect more light and color, giving the surface of the automobile a more brilliant appearance and boosting the quality and worth of the car.

Our Products and Services

1. Good products at an affordable price.

2. The color mixing procedure has been updated.

3. We attend trade shows all around the world to promote our products and to assist our distributors in promoting in their respective markets.

4. We visit our distributors and key clients to learn about automotive painting trends and get feedback on how to improve our product development.

5. We handle all export procedures to ensure the safety of our customers' containers.

