



Stable And Weather Resistant Multifunctional Polyester Putty For Automotive Body Filling

Our Product Introduction

for more products please visit us on refinishcarpaint.com

Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: p-512
- Minimum Order Quantity: 50L
- Price: 2.73USD-5.56USD
- Packaging Details: Can/Cartron
- Delivery Time: 7-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500 boxes per day



Product Specification

- Adhesion: Excellent
- Application: Various
- Color: Yellow
- Coverage: 2.5-3.0 M2/kg
- Density: 85% Solid
- Shelf Life: 8 Months
- Shelf: Dry And Cool
- Highlight: color correction paint, solvent basecoat paint, 1k 2k paint



More Images



Product Description

Meklon Car Polyester Putty Repair Paint Rice Golden Gray 85% Solid Content

Product Parameters

Product Name	530R rice golden gray	Product Packaging	12 cans in a box
Solid Content	85% or more	Product Color	light yellow
Shelf Life	8months	Material	Putty
Application	car furniture putty repair	Usage Ratio	100g ash: 2g hardener
Product Features	Alloy fiber ash is specially designed for the automotive repair market to repair deep pits on the surface of all automotive alloy substrates, filling and repairing.		
Applicable Substrates	iron plates, aluminum, glass fiber reinforced plastics, welds and old paint layers, and deep pits and holes on the surface of general plastic parts.		


Note: The actual product is mainly received in kind, and there are differences in different batches, which will not affect the use.

Product Display



Affordable

Small quantity and large area
take a small part and stir it evenly
then apply it on the extended area
of the object the construction surface is large,
and the material loss is small



Easy to polish

Fine texture of car putty
Not prone to sanding after drying
No bubbles left



All-round anti-rust

Metal will rust after long-term use.
After polishing with putty,
scrape off the putty to restore the luster of the metal



Strong Adhesion

Good viscosity, suitable for various top coats
can be firmly attached to the real object
making the coated object bright and smooth


4 Elements



Easy to polish
Easy to wet or dry
sanding without
using sandpaper
the surface is
smooth and clean
after sanding



Scratch property
The paste is
delicate has no
crust, it is easy to
scrape apply
without curling or
sagging



Layer appearance
Uniform and flat
color
No obvious coarse
grains and holes
No cracks after
drying
No dust
phenomenon



Simple
construction
Epair it by yourself
according to actual



Mildew and moisture proof
The putty batch is scraped
up to play the role of
isolating the air from
entering, effectively
preventing
the incorporation of water.



Fill in uneven areas
Adjust the unevenness of
the surface of the object
remove the paint, fill it up
and repair it.



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province