



ISO 9001 1K Car Paint Hardener Transparent Color Resin Material

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: MK-800X
- Minimum Order Quantity: 200Boxes
- Price: 4.64USD-6.92USD
- Packaging Details: Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500 boxes per day



Product Specification

- Features: High Hardness
- Brand: MESHILIANKE
- Color: Transparent
- Name: Enviromentally Hardener
- Material: Resin
- Net Weight: 0.95kG
- Shelf Life: 2 Years
- Storage Temperature: Room Temperature
- Highlight: **ISO 9001 Car Paint Hardener,
Car Paint Hardener Transparent,
Resin Auto Paint Hardener**



for more products please visit us on refinishcarpaint.com

Product Description

Wholesale Price Supply ISO 9001 1K Silver Pink Mother Series Acrylic Car Paint Hardener

product description:

Meishilianke, Feriia, Meishilianke, Meiguanda, and Meklon are just a few of the six brands that the Meklon vehicle paint business produces. Each brand has its own distinctive packaging and features. The company's research and development team is made up of its own R&D engineers, who have created vehicle paint products ranging in quality from low to high in accordance with standards.

The business manufactures a low-to-medium quality automotive curing agent called MK-800X Environmentally Hardener. It is economical and appropriate for some markets with moderately high price demands. It is a low-to-medium priced product because to its cost, but even so, we guarantee the quality and gloss of all of our products.

Product Details:

Product name: Enviromentally Hardener Model : MK-800X	
Product features	1 environmentally friendly and mirror-smooth 2 resistant to corrosion caused by acid, salt, chemical solvents, and oil, especially strong 3 flexibility, abrasion resistance, and hardness.
Application	Suitable for cars, buses, trucks, ships, planes, tanks, etc.
Application Method	Spray/Roll/brush
Technical Parameter	Mixing Ratio: paint : Hardener = 2 : 1 Coverage: 3-3.5sqm/kg
Construction process	1 Before painting, polish and clean the floor. 2 VIT General Purpose Epoxy Primer WGM-9563 to prime the floor 3 Apply the middle layer using a primer/paint and quartz mortar combination. 4 Clean and polish the surface. Use General Purpose Epoxy Floor Top Paint WGM-9562 to paint once or twice.

Drying Time			
Temperature	Dust Free	Dry to Handle	Thorough Dry
20°C	30 minutes	10 hours	1 day
60°C	15 minutes	1 hours	1 hour

Sand ability and Polish ability	wet sanding P800 P1000 sand paper if need polish
Shelf Life	5 years in original sealed
Packaging	1L*12 tins /ctn 4L*4tins /ctn

If you're interested, get in touch with us so we can send you some samples for free.
If you have a favorite type of packaging, we can make it for you



Customs feedback



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province