



Waterproof Automotive Clear Coat And Hardener Stable Alkali Resistant

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: MK-120X
- Minimum Order Quantity: 200Boxes
- Price: 4.64USD-6.92USD
- Packaging Details: Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500 boxes per day



Product Specification

- Features: High Hardness
- Brand: MESHILIANKE
- Color: Transparent
- Name: Enviromentally Hardener
- Material: Resin
- Net Weight: 0.95kG
- Shelf Life: 2 Years
- Storage Temperature: Room Temperature
- Highlight: 2 color car paint, automotive enamel primer, mixing paint with hardener



Product Description

High Quality Acrylic Car Refinish Paint 1K Basecoat/Topcoat and Standard Thinner/Hardener

product description:

The Meklon automotive paint company offers six brands, including Meishilianke, Feriia, Meishilianke, Meiguanda, and Meklon. Every brand has unique packaging and features of their own. The company's in-house R&D engineers make up the research and development team, and they have produced car paint products with a range of quality from low to high in compliance with standards.

The company produces MK-120X Environmentally Hardener, a low-to-medium quality automobile curing agent. It fits some markets with somewhat high price needs and is cost-effective. Due to its cost, it is a low- to medium-priced product; nonetheless, we still guarantee the quality and gloss of all of our goods.

Features: We provide three types of high performance varnish in order to suit a variety of consumers. These types are the economical type, the standard type, and the high solid content type. All of them have high hardness, high gloss, and resistance to alcohol and gasoline. The clear coat may provide the 1K base coat the protection, toughness, and brilliance that it needs to be sprayed on. After two wet sprays, the result will be smooth and crystal clear.

	Temperature	Clear Coat	Hardener	Thinner
Temperature & Match	15	Economic/Standard/High Solid Type Clear Coat	Economic/Standard/High Solid Type Fast Dry Hardener	Fast Dry Thinner
	15-25	Economic/Standard/High Solid Type Clear Coat	Economic/Standard/High Solid Type Standard Hardener	Standard Thinner
	25-35	Economic/Standard/High Solid Type Clear Coat	Economic/Standard/High Solid Type Slow Dry Hardener	Slow Dry Thinner
Mixing Ratio		2	1	0.2-0.5

Spray: Wet spray in two to three layers, with a five to ten minute flash-off period between each layer.

applicable time: two hours at 20 °C

Drying Time: At 20 °C, surface drying takes 40 minutes, and thorough drying takes 12 hours. For 40 minutes, thoroughly dry at 60 °C.

It is advised to polish the surface once it has dried overnight.

Arrangement: 1L*15, 5L*4

Hardener

High-quality, anti-yellowing features. We provide three types: Economic, Standard, and High Solid Content (HS), as well as three models: Fast Dry, Standard, and Slow Dry. It is appropriate for clear coat, 2K ready-mixed paint, and 2K tinters.

Mixing Ratio: Please refer to the Clear Coat

How to Apply:

It is advised to apply Fast Dry Hardener below 15 °C.

Standard Hardener: It should be used between 15 and 30 degrees Celsius.

Use of the slow dry hardener is advised above 30 °C.

0.5L*30, 0.5L*24, 1L*15, 1L*12, 2.5L*8, and 5L*4 bottles

Storage Time: Original unopened items can be kept for over two years at 20 °C.

Get in contact with us if you're interested, and we'll send you some samples without charge.

We can create your preferred style of packaging if you have one.

Customs feedback



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province