



Solid Color Car Paint Hardener Alcohol Resistant Multipurpose

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: MK-520X
- Minimum Order Quantity: 200Boxes
- Price: 4.64USD-6.92USD
- Packaging Details: Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500 boxes per day



Product Specification

- Features: High Hardness
- Brand: MESHILIANKE
- Color: Transparent
- Name: Enviromentally Hardener
- Material: Resin
- Net Weight: 0.95kG
- Shelf Life: 2 Years
- Storage Temperature: Room Temperature
- Highlight: **Solid Car Paint Hardener, cheap automotive clear coat, car solid paint**



Product Description

Chinese Manufacturer Fast Hardener Used for Cold Area for Car Spray Paint

Product Description:

The Meklon auto paint factory offers six brands, including Meishilianke, Feriia, Meishilianke, Meiguanda, and Meklon. Every brand has unique packaging and other traits. The company's in-house R&D engineers make up the research and development team, and they have produced vehicle paint products with a range of quality from low to high that adhere to standards.

Features: We offer three distinct high performance varnishes to satisfy a variety of consumers. The regular type, the high solid content type, and the economical kind fall into these three categories. They are all exceptionally resistant to alcohol and gasoline, extremely glossy, and long-lasting. The clear coat may provide the protection, toughness, and brightness that the 1K base coat needs to be put on. After two wet sprays, the product will be slick and perfectly clear.

Product Description

Hardener

attributes of excellent anti-yellowing quality. In addition to three models—Fast Dry, Standard, and Slow Dry—we provide three types—Economic, Standard, and High Solid Content (HS). Clear coat, 2K ready-mixed paint, and 2K tinters are all suitable for it.

Mixing Ratio:

Temperature& mixed	Temperature	Clear Coat	Activator/ Hardener	Thinner
Temperature& mixed	<15°C	BS/ES Clear Coat	120 Fast Dry Activator	602 Fast Dry Thinner
Temperature& mixed	15-25°C	BS/ES Clear Coat	120 Standard Activator	602 Standard Thinner
Temperature& mixed	25-35°C	BS/ES Clear Coat	120 Slow Dry Activator	602 Slow Dry Thinner
Mixing Ratio		2	1	0.3-0.5

How to Apply:

It is advised to apply Fast Dry Hardener below 15 °C.

Standard Hardener: It should be used between 15 and 30 degrees Celsius.

Use of the slow dry hardener is advised above 30 °C.

0.5L*30, 0.5L*24, 1L*15, 1L*12, 2.5L*8, and 5L*4 bottles

Storage Time: Original unopened items can be kept for over two years at 20 °C.

Customs feedback





Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province