



Practical Car Polyester Putty Gasoline Resistant Harmless For Auto Body

Our Product Introduction

for more products please visit us on refinishcarpaint.com

Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: 5006+5007
- Minimum Order Quantity: 200Boxes
- Price: 4.34USD-6.52USD
- Packaging Details: Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T, T/T
- Supply Ability: 500 boxes per day



Product Specification

- Brand: CarCharm
- Application Method: Brush, Roller, Or Spray
- Application Temperature: 50-90°F
- Cleanup: Soap And Water
- Coverage: 400-500 Sq. Ft.
- Dry Time: 1-2 Hours
- Durability: High
- Finish: Glossy
- Sheen: High
- VOC Content: Low
- Highlight: acrylic automotive primer, one car body and paint, home and auto paint



More Images



Product Description

Quick Drying Two Component Polishability Gasoline resistance:

Product Name:	Quick Drying Two Component
Net Weight:	1.2KG+0.3KG
Coating Thickness:	50-100um
Storage Temperature:	5-25
UV Resistance:	High UV Resistance

The carcharm series products are a sub-brand of China Meklon, and the quality is endorsed by China's top 20 companies. Customize paint products according to customers' industry needs, customize various light industrial paint products, and have a strong after-sales service team technical support to overcome various paint problems.

product description:

Test items:	unit:	standard requirement:
The status of materials in the container	There should be no foreign matter, no lumps, and it should be easy to stir into a viscous liquid.
color and appearance	Gray-white colour, flat varnish, matte or semi-gloss
Drying time (actual)	h	≤24
Drying		≤1[(120±2)]°C
Pencil hardness		≥B
Polishability:		Easy sanding non-stick sandpaper
Gasoline resistance		6h no foaming, no wrinkling, slight discoloration allowed
Salt spray resistance		168h 2mm away from one side of the cutting line, pass the first grade

Use ratio:

Features: It has excellent adhesion, salt spray resistance, temperature resistance, moisture resistance, anti-itching, etc. It also has excellent isolation effect.

Usage: Used as heavy rust and anti-corrosion for steel plates, aluminum plates, stainless steel, fiberglass and galvanized steel plates.

Drying: 10 minutes surface drying at 20C, 5 hours solid drying.

Grinding: 15 hours at 20C.

Packing: 1L x12

	508 (epoxy primer)	12X Crystal Hardener	602 Universal Thinner
weight ratio	4	1	1.5
Volume ratio	3	1	1.5

Demonstration effect:



Substrate Cleaning



Scribble Putty



spray surface paint



Spray epoxy primer

Packaging display:



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province