



Practical Acrylic Car Paint Hardener Alkali Resistant Harmless

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: MK-720X
- Minimum Order Quantity: 200Boxes
- Price: 4.64USD-6.92USD
- Packaging Details: Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500 boxes per day



Product Specification

- Features: High Hardness
- Brand: MESHILIANKE
- Color: Transparent
- Name: Enviromentally Hardener
- Material: Resin
- Net Weight: 0.95kG
- Shelf Life: 2 Years
- Storage Temperature: Room Temperature
- Highlight: car primer coat, auto paint and repair, easy repair automotive paint



Product Description

Acrylic Car Spray Coating 2K Hot Selling Good Application Auto Paint Hardener

Product Description:

Hardener

High and medium solid composition, strong anti-yellowing ability are features. We provide three types: Economic, Standard, and High Solid Content (HS), as well as three models: Fast Dry, Standard, and Slow Dry. It is appropriate for clear coat, 2K ready-mixed paint, and 2K tinters.

Mixing Ratio:

| Temperature & mixed | Temperature | Clear Coat | Activator/ Hardener | Thinner |
|---------------------|-------------|------------------------|---------------------------------|-------------------------------|
| Temperature & mixed | <15°C | MESHILIANKE Clear Coat | MEISHILIANKE Fast Dry Activator | MEISHILIANKE Fast Dry Thinner |
| Temperature & mixed | 15-25°C | MESHILIANKE Clear Coat | MEISHILIANKE Standard Activator | MEISHILIANKE Standard Thinner |
| Temperature & mixed | 25-35°C | MESHILIANKE Clear Coat | MEISHILIANKE Slow Dry Activator | MEISHILIANKE Slow Dry Thinner |
| Mixing Ratio | | 2 | 1 | 0.3-0.5 |

How to Use:

It is advised to apply Fast Dry Hardener below 15 °C.

Standard Hardener: It should be used between 15 and 30 degrees Celsius.

Use of the slow dry hardener is advised above 30 °C.

0.5L*30, 0.5L*24, 1L*15, 1L*12, 2.5L*8, and 5L*4 bottles

Storage Time: Original unopened items can be kept for over two years at 20 °C.

SURFACE PREPARATION:

1. The surface must be spotless and free of grease, oil, and dust.
2. Before applying the clear coat, old varnish surfaces must be sanded using grit sandpaper number 1200.

2-3 coats, 40-60 m, depending on the thickness Allow 5 to 10 minutes between coats during flash time.

Using a spray to apply

Weapon Nozzle:

(Gravity Spray Gun) 1.2-1.4mm

(Suction Spray Gun) 1.3-1.5mm

- 3-4 bar spraying pressure.

- Ford Cup #4 at 20 °C: 13-18 s spraying viscosity

- Three coats is the maximum number.

| Drying Time | Temperature | Dust Free | Tack Free | Complete Dry |
|-------------|-------------|-----------|------------|--------------|
| Drying Time | 20°C | 1h | 2-3 hours | 24h |
| Drying Time | 60°C | 5 minutes | 10 minutes | 60 minutes |

Customs feedback





+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong
Province