



Durable Nontoxic Car Paint Hardener Mildewproof For 2K Clear Coating

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: MK-1000X
- Minimum Order Quantity: 200Boxes
- Price: 4.64USD-6.92USD
- Packaging Details: Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500 boxes per day



Product Specification

- Features: High Hardness
- Brand: MESHILIANKE
- Color: Transparent
- Name: Enviromentally Hardener
- Material: Resin
- Net Weight: 0.95kG
- Shelf Life: 2 Years
- Storage Temperature: Room Temperature
- Highlight: auto coat paint, truck primer paint, customize car paint



Product Description

Standard/Fast/Slow Hardener for 2K Clear Coatings with Temperature Match

Product Description:

In the process of preparing automobile paint, MK-1000X special hardener for automotive paint is frequently employed as a drying aid. The major component of MK-1000X hardener is aliphatic isocyanate. Paint coatings benefit from the following properties when aliphatic polyisocyanates are used: gloss retention, non-yellowing, chemical resistance, aesthetics, abrasion resistance, durability, and impact resistance. Typically, our hardener is used with 2K paint and 2K primer. The prepared paint will harden if the hardener and 2K paint are not well mixed and used within an hour of preparation.

HARDENER

Features:

1. A variety of highly HS to moderately MS concentrated catalysts with outstanding yellow resistance.
2. Especially designed for 2K top coat, 2K clear coatings, and 2K priming.
3. Each hardener (Standard Hardener, Fast Hardener, and Slow Hardener) has three different drying speeds to accommodate various materials and application needs.

4, Mixing Ratio

Thinner is equivalent to 2:1:0.3-0.5 in terms of clear coat/K paint hardener/activator/catalyst/curing chemicals.

Furthermore, the mixing ratio might result in a 3:1, 4:1, or 5:1 ratio.

How to select a hardener or catalyst at various temperatures

name	temperature
fast dry hardener/ activator	below 15
standard dry hardener/ activator	between 15 to 30
slow dry hardener/ activator	above 30

Storage :

Keep in a tightly covered container and in a dry and ventilated environment, avoiding exposure in sun directly. Temperature above 10 is recommended, between 15 and 30 optimal.

Our Services

1. OEM support is offered. We can design and make goods for customers that want to use their own branding.
2. Prompt Shipping. After the order is confirmed, we can finish making the items and deliver/ship them in 7 to 10 days.
3. We will make the goods in accordance with the customers' exact specifications, quality standards, and personal needs.
4. We give out free gifts to our clients. If the clients have their own brand, it will be featured on the promotional items along with their name and logo.
5. We'll provide the best customer service we can.

FAQs

1. Are you a factory or trade company?

A: We are a famous paint manufacturer with over 20 years of experience. Our primary products are industrial paint, wood paint, plastic paint, and paint for cars. In addition to paint, we are able to provide a variety of automobile maintenance supplies, including undercoating, rubbing compound, spray guns, polishing pads, wool pads, abrasive paper, masking tape, filters, strainers, putty spatulas, and more.

2. What is your car paint system?

A: We manufacture the medium solid (MS) and high solid (HS) systems of acrylic automobile repair paint.

3. What is the applicable range of your products?

A: a car, a truck, a guardrail, a billboard, etc. made of metal.

4. Does your company can provide the samples to test? What is the minimum order quantity?

A: We can offer the samples without charge. The order minimum is 100 cartons.

5. Does your company provide the after-sales service.

A: Yes, if there is a request, our engineers can visit the customers and provide the professional solution.

6. If I come to China, how can I find your factory and visit?

A: We warmly welcome your visit to our factory and company. Our driver can go to the airport or the appointed place to pick you up to our factory.



Guangzhou Meklon Chemical Technology Co., Ltd.



+861339210068



Meklonpaint@gzmeklon.com



refinishcarpaint.com



+86 1882 18888



menonpaint@genmenon.com



remnantcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong
Province