



## Moistureproof Car Paint Thinner Multipurpose Nontoxic Anti Acid

### Our Product Introduction

#### Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: P-601
- Minimum Order Quantity: 200Boxes
- Price: 1.64USD-2.31USD
- Packaging Details: Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500 boxes per day



#### Product Specification

- Brand: MESHILIANKE
- Code: MK-601
- Name: Universal Thinner
- Color: Transparent
- Dry Time: Fast/Standard/Slow
- Flash Point: 25°C
- Type: Liquid
- Net Weight: 0.9KG
- Highlight: tinting automotive paint,  
mixing clear coat with paint,  
metallic base coat paint



## Product Description

### Automotive Refinish 2K Pure Color Standard Fast Drying Auto Paint with Epoxy Thinner

#### Product Description:

MK-601 Universal Thinner provides low to medium quality at a very affordable price for the price-conscious market. The MK-601 Universal Thinner's characteristics and capabilities are as follows:

MK-601 Universal Thinner has numerous applications, including single coatings and multiple coats, for a variety of vehicle paints. The paint is successfully thinned, simplifying application.

Effective Thinning: MK-601 Universal Thinner thins paint effectively, easing application while maintaining the performance and quality of the paint.

The MK-601 Universal Thinner, despite being a low- to medium-grade product, is still of sufficient quality for use in price-sensitive sectors.

Cost-performance ratio and very low price make the MK-601 Universal Thinner an excellent choice for markets with stringent spending restrictions.

MK-601 Universal Thinner is a thinner with a wide application range, high thinning performance, and quick drying. The product is of a low to medium grade, but despite that, it meets quality criteria, and the cost is very affordable. Furthermore, the price/performance ratio is comparatively high, making it suitable for markets with more stringent pricing requirements.

Usage	Reduce the application viscosity, increase the smoothness and gloss of paint film, Good solubility.
	Fast Drying THinner Fast drying thinner with very fast evaporation speed, suitable for spot repair or application below 15°C.
	Standard drying thinn Standard drying thinner,with medium evaporation speed , suitable for spot repair or application at 15-30°C.
Characteristi er c	Slow drying thinner Slow drying thinner,with slow evaporation speed, suitable for spot repair or overall refinish, application above 30°C.
Note	If the temperature or humidity are too high, 10 -30% Retarder Solvent can be added.
Shelf Life	2 years in original sealed can, cool and dry place at 20°C.
Package	4L×6 or 2L×12 or 0.5L×15 or 1L×15

**Instructions:** Prior to spraying, thinner and one thousandth of a color of paint should be blended equally.

#### Precautions:

1. When using automotive paint thinner, safety issues need to be taken into account. Automobile paint thinners are dangerous and combustible goods. They must be stored in a warehouse with sufficient air circulation, a suitable temperature, and isolating fire and heat sources in order to lower the risk of burning.
2. After the thinner has been added, the vehicle paint must be properly swirled to attain a suitable working viscosity.
3. Work in a well-ventilated environment as the diluent includes hazardous compounds and has a pungent odor.
4. Steer clear of acidic chemicals since they can chemically react with one another.
5. Combining several diluents could result in dangerous chemical reactions and, in the worst cases, explosions.
6. Keep flammable materials away from thinner
7. Wash your hands right away after using them to avoid leaving a stench behind and harming your skin.



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com



+86 1882 10000



mekonpaint@mekon.com



remnantcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong  
Province