



SGS Oilproof Lacquer Thinner On Car Paint , Mildewproof Paint Thinner Automotive

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: P-602
- Minimum Order Quantity: 200Boxes
- Price: 1.64USD-2.31USD
- Packaging Details: Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500 boxes per day



Product Specification

- Brand: Faralli
- Code: F-602
- Name: Universal Thinner
- Color: Transparent
- Dry Time: Fast/Standard/Slow
- Flash Point: 25°C
- Type: Liquid
- Net Weight: 0.9KG
- Highlight: oilproof lacquer thinner on car paint,
Oilproof Lacquer Thinner On Car Paint,
premium automotive paint



Product Description

Standard Drying Transparent Thinner Auto Car Refinish Automotive Paint

Product Description:

Our thinners are produced especially for the MK-Thinner line of paints. Customers can select from a variety of variants, including quick-drying, standard, and slow-drying, to respond to the building environment's varying temperatures. It can make paint less viscous and perform better at leveling paint.

F-602 Universal Thinner provides low to medium quality at a very affordable price for the price-conscious market. The following are the features and abilities of F-602 Universal Thinner:

There are numerous applications for F-602 Universal Thinner, including the usage with single and double layers of a variety of vehicle paints. The paint is successfully thinned, simplifying application.

Effective Thinning: F-602 Universal Thinner thins paint effectively, making application easier while maintaining paint performance and quality.

The F-602 Universal Thinner, despite being a low- to medium-grade product, is still of sufficient quality for use in price-sensitive sectors.

Cost-performance ratio and very low pricing make the F-602 Universal Thinner an excellent choice for markets with stringent spending restrictions.

A thinner with a broad application range, good thinning performance, and quick drying is F-602 Universal Thinner. Although the product is of low to medium grade, it nevertheless satisfies the standards in terms of quality, and the price is extremely reasonable. Additionally, the price/performance ratio is relatively high, making it appropriate for markets with higher pricing needs.

1. Surface Should Be Clean And Free Of Dust, Grease And Oil.
2. Old Varnish Surfaces Must Be Sanded Using Grit Sandpaper Number 1200, Before Applying The Clear Coat.

Temperature& mixed	Temperature	Clear Coat	Activator/ Hardener	Thinner
Temperature& mixed	<15	MEISHILIANKE Clear Coat	MEISHILIANKE Activator	MEISHILIANKE Thinner
Temperature& mixed	15-25	MEISHILIANKE Coat	MEISHILIANKE Standard Activator	MEISHILIANKE Thinner
Temperature& mixed	25-35	MEISHILIANKE Coat	MEISHILIANKE Slow Dry Activator	MEISHILIANKE Thinner
Mixing Ratio		2	1	0.3-0.5

Instructions: Before being sprayed, thinner and one thousandth of a color of paint should be mixed equally.

Precautions:

1. When using automotive paint thinner, safety issues need to be taken into account. Automobile paint thinners are dangerous and combustible goods. They must be stored in a warehouse with sufficient air circulation, a suitable temperature, and isolating fire and heat sources in order to lower the risk of burning.
2. After the thinner has been added, the vehicle paint must be properly swirled to attain a suitable working viscosity.
3. Work in a well-ventilated environment as the diluent includes hazardous compounds and has a pungent odor.
4. Steer clear of acidic chemicals since they can chemically react with one another.
5. Combining several diluents could result in dangerous chemical reactions and, in the worst cases, explosions.
6. Keep flammable materials away from thinner



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province