



ISO Water Based Car Paint Thinner Mildew Resistant Practical

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: P-603
- Minimum Order Quantity: 200Boxes
- Price: 1.64USD-2.31USD
- Packaging Details: Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500 boxes per day



Product Specification

- Brand: MEISHILIANKE
- Code: F-603
- Color: Transparent
- Dry Time: Fast/Standard/Slow
- Flash Point: 25°C
- Type: Liquid
- Net Weight: 0.9KG
- Highlight: **ISO Car Paint Thinner,
Car Paint Thinner Mildew Resistant,
Practical Water Based Car Paint Thinner**



Product Description

High Solid Acrylic Fast Dry Clear Coat 2K Auto Primer Hardener Automotive Paint

Product Description:

Our thinners are produced especially for the MK-Thinner line of paints. Customers can select from a variety of variants, including quick-drying, standard, and slow-drying, to respond to the building environment's varying temperatures. It can make paint less viscous and perform better at leveling paint.

For the budget-conscious market, MK-603 ADVANCED Thinner offers low to medium quality at a very reasonable cost. The characteristics and skills of MK-603 ADVANCED Thinner are as follows:

There are several uses for MK-603 ADVANCED Thinner, which offers low to medium quality for the budget-conscious market at a very cheap cost. The characteristics and skills of MK-603 ADVANCED Thinner are as follows:

F-602 Universal Thinner has a wide range of uses, including the application of single and double coats of various vehicle paints. Successful thinning of the paint makes application easier.

Effective Thinning: MK-603 ADVANCED Thinner thins paint efficiently, facilitating application while preserving paint quality and performance.

Advanced MK-603 Even though thinner is a low- to medium-grade product, it nevertheless has acceptable quality for usage in industries where cost is an important factor.

MK-603 ADVANCED Thinner is a thinner with a wide application range, outstanding thinning performance, and quick drying. The product is of a low to medium grade, but despite that, it meets quality criteria, and the cost is very affordable. Furthermore, the price/performance ratio is comparatively high, making it suitable for markets with more stringent pricing requirements.

Series Thinner Characteristic:

1. Premium thinner
2. Developed specifically for primer, basecoat, and topcoat
3. Fast, regular, and slow drying speeds are available to accommodate various products
4. Various application temperatures and specifications.

Usage	Reduce the application viscosity, increase the smoothness and gloss of paint film, Good solubility.	
Characteristic	Fast Drying THinner	Fast drying thinner with very fast evaporation speed, suitable for spot repair or application below 15°C.
	Standard drying thinner	Standard drying thinner, with medium evaporation speed, suitable for spot repair or application at 15-30°C.
	Slow drying thinner	Slow drying thinner, with slow evaporation speed, suitable for spot repair or overall refinish, application above 30°C.
Note	If the temperature or humidity are too high, 10-30% Retarder Solvent can be added.	
Shelf Life	2 years in original sealed can, cool and dry place at 20°C.	
Package	4L×6 or 2L×12 or 0.5L×15 or 1L×15	

Precautions:

1. When using automotive paint thinner, safety issues need to be taken into account. Automobile paint thinners are dangerous and combustible goods. They must be stored in a warehouse with sufficient air circulation, a suitable temperature, and isolating fire and heat sources in order to lower the risk of burning.
2. After the thinner has been added, the vehicle paint must be properly swirled to attain a suitable working viscosity.
3. Work in a well-ventilated environment as the diluent includes hazardous compounds and has a pungent odor.
4. Steer clear of acidic chemicals since they can chemically react with one another.
5. Combining several diluents could result in dangerous chemical reactions and, in the worst cases, explosions.
6. Keep flammable materials away from thinner





+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong
Province