

Harmless Heatproof Auto Base Paint , Practical White Base Coat Car Paint

Our Product Introduction

Basic Information

- Place of Origin: GUANGDONG CHINA
- Brand Name: MEISHILIANKE series
- Certification: ISO,SGS,MSDS
- Model Number: MK-102
- Minimum Order Quantity: 100 L
- Price: 3.26USD-5USD
- Packaging Details: 0.5L/1L/4L/10L/20L/200L
- Delivery Time: 7-30days
- Payment Terms: T/T
- Supply Ability: 50000L/month



Product Specification

- Main Raw Materials: Acrylic Resin,Polyurethane Resin
- Feature: High Leveling,high Glossy,high Fullness,good Covering,high Adhesion
- Certification: Pigment
- Substrate: 1k Base Coat
- Coating Type: Acrylic
- Mildew Resistant: Yes
- Transport Package: In Standard Export Cartons
- Dry Film Thickness: 1.5-2.0 Mills
- Coating Material: Acrylic
- Color: 1K Scarlet
- Highlight: car paint damage repair, oem auto paint, auto primer paint



for more products please visit us on refinishcarpaint.com

Product Description

Chinese Factory 1K Coating Car Paint Color Mixing System for Auto Refinish Paint

Product Introduction

base coat of 1k

One-component universal vehicle body refinish paint series made with foreign raw ingredients from acrylic and polyurethane resins. It offers metallic glitter effect for vehicle painting, making the automobile body more three-dimensional, accentuating the sumptuous nature, and is appropriate for high-end car painting. It includes plain paint, silver powder paint, and pearl paint color masterbatch. It may also be used for specialized primers for luxury automobiles, commercial vehicles, spraying new autos, and restoring older cars.

Meklon Coat Basecoat offers excellent coverage and adequate metal orientation for enhancing OEM solid, metal, and pearl color effects in car paint. It is very easy to mix and apply.

The highest color accuracy is provided by Meklon Coat basecoat.

A Meklon Coat basecoat and a Meklon Coat clearcoat must be applied together for durability.

Old or original painting has to be scrubbed and carefully cleaned.

Unhanded surface or primer application using the wet on wet technique Surfaces that have been cleaned, sanded, and primed Surfaces must be well cleaned and prepared before usage.

Cleaning and sanding of damaged areas should be done using P500-P600 (by machine) or P800-P1000 (by hand).

A hard paint film, good leveling capabilities, ease of construction, strong adhesion, exceptional exterior weather resistance, a protracted anti-oxidation time, the ability to be blended with a variety of simple colors, metal effects, and pear effects, and excellent layer adhesion are all characteristics of the product.

Specification:

Product name	1K BASE COAT 1K Scarlet
Mixing ratio	1: 1-1.2 100 parts 1K Base coat 100-120 parts Thinner
Spray coats	Spray 2-3 layers, the flash-off time is 5 to 8 mins.
Dry Time	15 min(20°C)
Shelf Life	2 years in original sealer in cool and dry place at 20°C
Packaging (per carton)	1L*12can, 4L*4can
Product advantages	Extra fast drying and high quality finishing. Good color covering power and leveling. Varied color cover full range with high color saturation.
Instructions	Spray
Brand Name	Meklon

Application method

spray gun	Gravity gun	Suction gun
	gun nozzle: 1.2mm, gun pressure: 2.0-3.0 MPa	gun nozzle: 1.5mm, gun pressure: 2.0-3.0 MPa
substrate	dry 1K primer surface with smooth effect	
Paint preparation	1K Mud Yellowpaint-thinner-EX10/EX20/EX30	
mix ratio	1 : 1 (base paint : thinner)	
spraying layers	2-3 coats	
flash off time	3-5 mins , 20-25	
surface dry time	15-20mins	
Time to Polish	1h, P1000 sanded paper	
Relationship between drying temperature and time of 1K base coat		
Tenmperture	Surface Drying time	Time to Polish
25	10-15 mins	1 hour
35	5-10 mins	40 mins
60	3-5 mins	15 mins

Meklon Coat Basecoat is a highly functional basecoat for automobile paint that is easy to mix and apply. It is perfect for recreating OEM solid, metallic, and pearl color effects because to its outstanding coverage, which ensures faultless results and the best color match.

Combining Meklon Coat Basecoat and Meklon Coat Clearcoat will increase durability and lifetime. Together, these two strong forces provide a durable layer of protection that can withstand a variety of environmental factors.

Prior to applying the basecoat, the metallic surface must be properly cleaned. The existing or original paints are completely sanded and cleaned to create a smooth and uniform canvas. Applying prime surface or a surface that has been sanded, cleaned, or left unhandled during a wet on wet operation improves good adhesion and a faultless finished look.





Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong
Province