

## Glossy 1K 2K Car Paint Basecoat Multipurpose Polyurethane Resin

### Basic Information

- Place of Origin: GUANGDONG CHINA
- Brand Name: MEISHILIANKE series
- Certification: ISO,SGS,MSDS
- Model Number: MK-109
- Minimum Order Quantity: 100 L
- Price: 3.26USD-5USD
- Packaging Details: 0.5L/1L/4L/10L/20L/200L
- Delivery Time: 7-30days
- Payment Terms: T/T
- Supply Ability: 50000L/month



### Product Specification

- Main Raw Materials: Acrylic Resin, Polyurethane Resin
- Feature: High Leveling, High Glossy, High Fullness, Good Covering,high Adhesion
- Certification: Pigment
- Substrate: 1k Base Coat
- Coating Type: Acrylic
- Mildew Resistant: Yes
- Transport Package: In Standard Export Cartons
- Dry Film Thickness: 1.5-2.0 Mills
- Coating Material: Acrylic
- Highlight: **Glossy Car Paint Basecoat, 2K Car Paint Basecoat, auto paint**



## Product Description

### Car Paint Auto Base Paints Automotive Refinish Paint 1k Basecoat

#### Product Introduction

We provide a complete line of mixing and tinting tools. Includes 1K and 2K primer surfaces, epoxy primers, plastic primers, and other primers. It also includes transparent coatings, hardeners, thinners, binders, 1K basecoat toners (solid, silver, and pearl colors), and 2K topcoat toners.

Our system also provides all of the automobile industry's recipes, including those for Nissan, Honda, Toyota, Ford, Chrysler, Fiat, Peugeot, Citroen, Renault, and other manufacturers.

Meklon

1. MeklonCar Paint is a low strength intermix solution with a complete range of tinting and mixing technologies.

2. Meklon includes primers (1K and 2K primer surfaces), epoxy primers, plastic primers, and primer surfaces. It also includes clear coats, hardeners, thinners, binders, 1K basecoat toners (solid, silver, and pearl colors), and 2K topcoat toners.

Type	1K basecoat color paint	
Substrates	Well-sanded, completely dried and good existing finishes as: A. original paint B. old paint firm C. 1K or 2K primer	
Surface Cleaning	Wash by warm soap, remove wax, silicon and other contaminations with degreaser, sanding with P800-P1000, wash with clean water then keep dry, again with degreaser.	
Mixing Ratio	Basecoat	Thinner
<15°C	1K basecoat color paint	602 Fast Thinner
15-30°C	1K basecoat color paint	602 Standard Thinner
>30°C	1K basecoat color paint	602 Slow Thinner
Spray Viscosity	14-16s to drop off, in 4# viscosity cup at 25°C	
Re-Treatment	After Spray, allow 10-20 minutes air-drying time, then spray clear coat at once.	
Spray Gun Set Up	Gravity Feed: 1.2-1.5mm 3-5kg/cm <sup>2</sup> Gravity Feed: 1.4-1.6mm 3-5kg/cm <sup>2</sup>	
Spray Technology	Coats & Thickness: 2-3 coats, total 15-20um. Flash-Off Time: At 25°C, 5-10 minutes between two coats, it depends on temperature and paint film.	
Shelf Life	2 years in original sealed can, cool and dry place at 25°C	
OEM/ODM	As customers' order	
Package Size	1L*12 Tins or 3.75L*4 Tins	



#### Product Details

MEISHILIANKE is the main brand of automotive refinish paint under Meklonpaint. It provides a complete color mixing system and a full range of refinish paint products and additives to provide customers with various ideal solutions. Xuchuang's repair paint mainly includes 1K primer, 2K topcoat, varnish, hardener, thinner, 2K primer, putty and additives.

With premium product quality and complete color formulas, we have exported Meklonpaint automotive coatings to more than 80 countries around the world.

MK-109 1K is a Phthalocyanine blue with green phase that is blue on the side and greenish on the front.

We utilize premium raw materials from BASF, MERCK, ECKART, EASTMAN, DSM, BYK, and BAYER, as the largest Chinese buyer. We have been using ISO9001 and ISO16949 standards for 15 years, employing nearly 30 people in the QC department for meticulous quality control from raw materials to finished products.



For over 20 years, a respected paint company has been offering industrial paint, wood paint, plastic paint, and automobile paint. They also offer vehicle maintenance products like undercoating, rubbing compound, sprayers, polishing pads, wool pads, abrasive paper, masking tape, filters, strainers, and putty spatulas. They manufacture medium solid (MS) and high solid (HS) systems of acrylic automotive repair paint. Their products include car, truck, metal surface products, guardrail, and billboard. Samples can be provided for free, with a minimum order quantity of 100cartons. After-sales service is provided by engineers who can visit customers for professional solutions. If visiting China, a driver can pick you up at the airport or an appointed place.





Type	1K Basecoat Colors	
Substrates	Well-sanded, completely dried and good existing finishes as: A. original paint B. old paint firm C. 1K or 2K primer	
Surface Cleaning	Wash by warm soap, remove wax, silicon and other contaminations with degreaser, sanding with P800-P1000, wash with clean water then keep dry, again with degreaser.	
Mixing Ratio	Basecoat	Thinner
<15°C	1K basecoat colors	62 Fast Thinner
15-30°C	1K basecoat colors	62 Standard Thinner
>30°C	1K basecoat colors	62 Slow Thinner
Spray Viscosity	14-16s to drop off, in 4# viscosity cup at 25°C	
Re-Treatment	After Spray, allow 10-20 minutes air-drying time, then spray clear coat at once.	
Spray Gun Set Up	Gravity Feed: 1.2-1.5mm 3-5kg/cm <sup>2</sup> Gravity Feed: 1.4-1.6mm 3-5kg/cm <sup>2</sup>	
Spray Technology	Coats & Thickness: 2-3 coats, total 15-20um. Flash-Off Time: At 25°C, 5-10 minutes between two coats, it depends on temperature and paint film.	
Shelf Life	2 years in original sealed can, cool and dry place at 25°C	
OEM/ODM	As customers' order	
Package Size	1L*12 Tins or 3.75L*4 Tins	



**Guangzhou Meklon Chemical Technology Co., Ltd.**



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province