

## Waterproof Base Coat Car Spray Paint Multifunctional Harmless

Our Product Introduction

for more products please visit us on [refinishcarpaint.com](http://refinishcarpaint.com)

### Basic Information

- Place of Origin: GUANGDONG CHINA
- Brand Name: MEISHILIANKE series
- Certification: ISO,SGS,MSDS
- Model Number: MK-110
- Minimum Order Quantity: 200 L
- Price: 3.26USD-5USD
- Packaging Details: 0.5L/1L/4L/10L/20L/200L
- Delivery Time: 7-30days
- Payment Terms: T/T
- Supply Ability: 50000L/month



### Product Specification

- Main Raw Materials: Acrylic Resin,Polyurethane Resin
- Feature: High Leveling,high Glossy,high Fullness,good Covering,high Adhesion
- Coating Material: Acrylic
- Substrate: 1k Base Coat
- Coating Type: Acrylic
- Certification: Pigment
- Mildew Resistant: Yes
- Transport Package: In Standard Export Cartons
- Dry Film Thickness: 1.5-2.0 Mills
- Service: Provide Samples, Color Cards, Related Materials, As Well As OEM And ODM
- Highlight: **spray car paint, single stage car paint, oem car paint**



### More Images



## Product Description

### 1K Blue High Quality Good Coverage Automotive Coating Car Paint Auto Refinish

Type	1K Blue basecoat color paint	
Substrates	Well-sanded, completely dried and good existing finishes as: A. original paint B. old paint firm C. 1K or 2K primer	
Surface Cleaning	Wash by warm soap, remove wax, silicon and other contaminations with degreaser, sanding with P800-P1000, wash with clean water then keep dry, again with degreaser.	
Mixing Ratio	<a href="#">Basecoat</a>	<a href="#">Thinner</a>
<15°C	1K Blue basecoat color paint	602 Fast Thinner
15-30°C	1K Blue basecoat color paint	602 Standard Thinner
>30°C	1K Blue basecoat color paint	602 Slow Thinner
Spray Viscosity	14-16s to drop off, in 4# viscosity cup at 25°C	
Re-Treatment	After Spray, allow 10-20 minutes air-drying time, then spray clear coat at once.	
Spray Gun Set Up	Gravity Feed: 1.2-1.5mm 3-5kg/cm <sup>2</sup> Gravity Feed: 1.4-1.6mm 3-5kg/cm <sup>2</sup>	
Spray Technology	Coats & Thickness: 2-3 coats, total 15-20um. Flash-Off Time: At 25°C, 5-10 minutes between two coats, it depends on temperature and paint film.	
Shelf Life	2 years in original sealed can, cool and dry place at 25°C	
OEM/ODM	As customers' order	
Package Size	1L*12 Tins or 3.75L*4 Tins	

For more than 20 years, a reliable paint supplier has offered industrial paint, wood paint, plastic paint, and vehicle paint. They sell equipment for servicing automobiles in addition to undercoating, rubbing compound, sprayers, polishing pads, wool pads, abrasive paper, masking tape, filters, strainers, and putty spatulas. They provide medium solid (MS) and high solid (HS) systems of acrylic car repair paint. Its products include cars, trucks, metal objects with smooth surfaces, fences, and billboards. With a 100 carton minimum order, free samples are offered. After-sales assistance is provided by engineers who may go to clients' locations to give qualified solutions. A driver will pick you up at the airport or another designated spot if you're going to China.

Meklon Car Paint, The Automotive Refinish manufacturer Looking for Agent / Dealer / Distributor

Please Tell Us Your Requirement, We Will Contact You ASAP

We are specialized in full range of auto paint products, including 1K basecoat, 2K single-stage paints, clearcoats, hardeners, 2K primers, reducer, 2K polyester putty, 1K body filler etc.

With 102 basic tinters, we have developed more than 150000 color formulations, covering almost each car maker around the world. Formulation program including PC version, APP version, Website online version are well used among end-user clients.

[Our OEM color chips contain more than 8000 colors, and our chromatic color chips contain more than 8500 colors.](#)



**Guangzhou Meklon Chemical Technology Co., Ltd.**



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province