



Brilliant Blue Car Paint Basecoat Acrylic Spray Weatherproof

Our Product Introduction

Basic Information

- Place of Origin: GUANGDONG CHINA
- Brand Name: MEISHILIANKE series
- Certification: ISO,SGS,MSDS
- Model Number: MK-111
- Minimum Order Quantity: 100 L
- Price: 3.26USD-5USD
- Packaging Details: 0.5L/1L/4L/10L/20L/200L
- Delivery Time: 7-30days
- Payment Terms: T/T
- Supply Ability: 50000L/month



Product Specification

- Main Raw Materials: Acrylic Resin,Polyurethane Resin
- Feature: High Leveling,high Glossy,high Fullness,good Covering,high Adhesion
- Certification: Pigment
- Substrate: 1k Base Coat
- Coating Type: Acrylic
- Mildew Resistant: Yes
- Transport Package: In Standard Export Cartons
- Dry Film Thickness: 1.5-2.0 Mills
- Coating Material: Acrylic
- Highlight: car paint, automotive paint, auto body paint



Product Description

Wholesale Automotive High Varnish Auto Refinish Car Spray Paint

Product Introduction

Meklon Paint

1. Meklon Car Paint is an intermix system with low strength and a full complement of tinting and blending capabilities.
2. MeklonPaint consists of clear coats, hardeners, thinners, binders, pearl colors, silver colors, 1K basecoat toners, 2K topcoat toners, primers (1K primer surfacer, 2K primer surfacer, epoxy primer, and plastic prime), and primer surfaces.

Type	1K brilliant blue basecoat color paint	
Substrates	Well-sanded, completely dried and good existing finishes as: A. original paint B. old paint firm C. 1K or 2K primer	
Surface Cleaning	Wash by warm soap, remove wax, silicon and other contaminations with degreaser, sanding with P800-P1000, wash with clean water then keep dry, again with degreaser.	
Mixing Ratio	Basecoat	Thinner
<15°C	1K brilliant blue basecoat color paint	602 Fast Thinner
15-30°C	1K brilliant blue basecoat color paint	602 Standard Thinner
>30°C	1K brilliant blue basecoat color paint	602 Slow Thinner
Spray Viscosity	14-16s to drop off, in 4# viscosity cup at 25°C	
Re-Treatment	After Spray, allow 10-20 minutes air-drying time, then spray clear coat at once.	
Spray Gun Set Up	Gravity Feed: 1.2-1.5mm	3-5kg/cm ²
	Gravity Feed: 1.4-1.6mm	3-5kg/cm ²
Spray Technology	Coats & Thickness: 2-3 coats, total 15-20um. Flash-Off Time: At 25°C, 5-10 minutes between two coats, it depends on temperature and paint film.	
Shelf Life	2 years in original sealed can, cool and dry place at 25°C	
OEM/ODM	As customers' order	
Package Size	1L*12 Tins or 3.75L*4 Tins	




Quality of the Product and Certificates

We are using the top raw materials from companies like BASF, MERCK, ECKART, EASTMAN, DSM, BYK, and BAYER, among others. As BASF's strategic partner, we are the largest Chinese purchaser of BASF raw materials. For the past 15 years, the organization has been adopting ISO9001 and ISO16949 processes. The QC department alone employs close to 30 employees, and thorough quality control is practiced from raw materials to completed goods.



For more than 20 years, a reliable paint supplier has offered industrial paint, wood paint, plastic paint, and vehicle paint. They sell equipment for servicing automobiles in addition to undercoating, rubbing compound, sprayers, polishing pads, wool pads, abrasive paper, masking tape, filters, strainers, and putty spatulas. They provide medium solid (MS) and high solid (HS) systems of acrylic car repair paint. Its products include cars, trucks, metal objects with smooth surfaces, fences, and billboards. With a 100 carton minimum order, free samples are offered. After-sales assistance is provided by engineers who may go to clients' locations to give qualified solutions. A driver will pick you up at the airport or another designated spot if you're going to China.


Performance is Always Perfect



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong
Province