



## Practical Automotive Clear Base Coat , Mildewproof Acrylic Clear Coat For Cars

Our Product Introduction

### Basic Information

- Place of Origin: GUANGDONG CHINA
- Brand Name: MEISHILIANKE series
- Certification: ISO,SGS,MSDS
- Model Number: MK-112
- Minimum Order Quantity: 100 L
- Price: 3.26USD-5USD
- Packaging Details: 0.5L/1L/4L/10L/20L/200L
- Delivery Time: 7-30days
- Payment Terms: T/T
- Supply Ability: 50000L/month



### Product Specification

- Main Raw Materials: Acrylic Resin,Polyurethane Resin
- Feature: High Leveling,high Glossy,high Fullness,good Covering,high Adhesion
- Certification: Pigment
- Substrate: 1k Base Coat
- Coating Type: Acrylic
- Mildew Resistant: Yes
- Transport Package: In Standard Export Cartons
- Dry Film Thickness: 1.5-2.0 Mills
- Coating Material: Acrylic
- Highlight: professional car paint,  
Acrylic Automotive Clear Base Coat , 2k paint



for more products please visit us on [refinishcarpaint.com](http://refinishcarpaint.com)

## Product Description

### High Quality Refinishing 1K Transparent Blue Basecoat Clear Reflective Spray Paint

#### Product Introduction

We offer a full complement of mixing and tinting equipment.contains clear coatings, hardeners, thinners, binders, 1K basecoat toners (solid, silver, and pearl colors), 2K topcoat toners, 1K and 2K primer surfaces, epoxy primers, plastic primers, and other primers.

Additionally, our system offers all of the recipes for the automotive industry, including those for Nissan, Honda, Toyota, Ford, Chrysler, Fiat, Peugeot, Citroen, Renault, and others.

Meklonpaint

1. MeklonCar Paint features a full range of tinting and mixing systems and is a low strength intermix system.

2. MeklonCar Paint consists of clear coats, hardeners, thinners, binders, solid, silver, and pearl colored 1K basecoat toners, 2K topcoat toners, primers (1K primer surfacer, 2K primer surfacer, epoxy primer, and plastic prime), primer surfaces, and primers.

Type	1K Transparent Blue basecoat color paint	
Substrates	Well-sanded,completely dried and good existing finishes as: A. original paint B.old paint firm C.1K or 2K primer	
Surface Cleaning	Wash by warm soap, remove wax, silicon and other contaminations with degreaser, sanding with P800-P1000, wash with clean water then keep dry, again with degreaser.	
Mixing Ratio	Basecoat	Thinner
<15°C	1K Transparent Blue basecoat color paint	602 Fast Thinner
15-30°C	1K Transparent Blue basecoat color paint	602 Standard Thinner
>30°C	1K Transparent Blue basecoat color paint	602 Slow Thinner
Spray Viscosity	14-16s to drop off, in 4# viscosity cup at 25°C	
Re-Treatment	After Spray, allow 10-20 minutes air-drying time,then spray clear coat at once.	
Spray Gun Set Up	Gravity Feed: 1.2-1.5mm 3-5kg/cm <sup>2</sup> Gravity Feed: 1.4-1.6mm 3-5kg/cm <sup>2</sup>	
Spray Technology	Coats & Thickness: 2-3 coats, total 15-20um. Flash-Off Time: At 25°C, 5-10 minutes between two coats, it depends on temperature and paint film.	
Shelf Life	2 years in original sealed can, cool and dry place at 25°C	
OEM/ODM	As customers' order	
Package Size	1L*12 Tins or 3.75L*4 Tins	

Note:

1. The substrate must be cleaned and sanded before spray, wet sanding P800-1000 and then dry.
2. At ambient temperature higher than 30 , add appropriate Retarder Solvent into thinner to avoid blushing. For more details, please refer to technical data sheet of Retarder Solvent.
3. To avoid problems of mottling or poor adhesion, the metallic paint film should be 15-25um.



### **Our Advantages**

The reason you choose us:

1. Competitive price with good quality;
2. Very good package, store products better in your country;
3. We have over 26 years experience, support you professional technical;
4. Fast delivery time, let you get products quickly after make order;
5. Reliable Manufacturer because our products quality approved by over 800 customers.



### **FAQ**

Q: Do you have any certificates concerning the quality?

A: Yes, our products are certified by ISO 9001:2008, ISO/TS 16949:2009.

Q: What kind of materials do you use for your automotive paint?

A: We use high quality raw materials for our automotive paint.

Q: How about your delivery time?

A: 20 - 25 days after order confirmed.

Q: Where are your product distributed?

A: Our product are distributed all over the world. Main overseas markets are Africa, Middle East, Central Asia, North America, Eastern Europe, Oceania etc.

Q: Are you trading company or manufacturer ?

A: we are manufacturer. Our factory is in Guangzhou, Guangdong, China. Welcome to pay a visit to our factory.





Performance is Always Perfect



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province