



Basic Information

Place of Origin: GUANGDONG CHINA
Brand Name: MEISHILIANKE series
Certification: ISO,SGS,MSDS

Model Number: MK-113Minimum Order Quantity: 100 L

• Price: 3.26USD-5USD

• Packaging Details: 0.5L/1L/4L/10L/20L/200L

Delivery Time: 7-30daysPayment Terms: T/T

Supply Ability: 50000L/month



Product Specification

Main Raw Materials: Acrylic Resin, Polyurethane Resin

• Feature: High Leveling,high Glossy,high

Fullness,good Covering,high Adhesion

Certification: PigmentSubstrate: 1k Base CoatCoating Type: Acrylic

Mildew Resistant:
Yes

• Transport Package: In Standard Export Cartons

Dry Film Thickness: 1.5-2.0 MilsCoating Material: Acrylic

Highlight: vehicle paint, clear coat for car, truck paint



Product Description

Hot Selling Best Auto Paint Car Refinish Paint for Cars Price

Product Introduction

Meklon Paint

- 1. Meklon Car Paint is an intermix system with low strength and a full complement of tinting and blending capabilities.
- 2. Meklon Paint consists of clear coats, hardeners, thinners, binders, pearl colors, silver colors, 1K basecoat toners, 2K topcoat toners, primers (1K primer surfacer, 2K primer surfacer, epoxy primer, and plastic prime), and primer surfaces.

Characteristic: Meklon 1K Lake blue Colors with excellent leveling property, easy construction, excellent adhesion power and covering power, can match all kinds of solid colors, metallic and pearl effect. Mainly applies to intermediate cars, MPV and bus.

	Well-Sanded, Completely dried and good existing finishes as bellow:	
	A original paint B. Old paint firm C. 1K or 2k primer	
Surface Cle	Wash by warm soap, remove wax, silicon and other contaminations with degreaser, sandingwith P800-P1000,	
	wash with clean water then keep dry;again with degreaser.	
Mixing Rati	Meklon1K Lake Blue Car Basecoat Colors	Thinner
0	1	1
15	Meklon1K Lake Blue Car Basecoat Colors	602-1Fast Thinner
15-30	Meklon1K Lake Blue Car Basecoat Colors	602-2 StandardThinner
1		602-3 Slow Thinner
Spray Visco	14-16s to drop off, in 4# viscositycup at 25°C,	
, ,		
ReTreatme nt	After spray, allow 10-20 minutesair-drying time,then spray clear coat at once.	
Spray	Gravity Feed: 1.2-1.5mm 3-5kg/cm 2	
Gun Set Up	Suction Feed: 1.4-1.6mm 3-5kg/cm 2	
	Coats&Thickness: 2-3 coats, total 15-20um.	
nology	Flash-Off Time: At 25°C, 5-10 minutes between two coats, it depends on temperature and paint film.	
Shelf Life	2 years in original sealed can, cool and dry place at 25.	
Package	1L×12 or 3.75L×4	
Note:	-	

- Note:
- 1. The substrate must be cleaned and sanded before spray, wet sanding P800-1000 and then dry.
- 2. At ambient temperature higher than 30, add appropriate Retarder Solvent into thinner to avoid blushing. For more details, please refer to technical data sheet of Retarder Solvent.
- 3. To avolid problems of mottling or poor adhesion, the metallic paint film should be 15-25um.



We offer a full complement of mixing and tinting equipment.contains clear coatings, hardeners, thinners, binders, 1K basecoat toners (solid, silver, and pearl colors), 2K topcoat toners, 1K and 2K primer surfaces, epoxy primers, plastic primers, and other

primers.

Additionally, our system offers all of the recipes for the automotive industry, including those for Nissan, Honda, Toyota, Ford, Chrysler, Fiat, Peugeot, Citroen, Renault, and others.

- 1. Meklon Car Paint features a full range of tinting and mixing systems and is a low strength intermix system.
- 2. Meklon Car Paint contains clear coats, hardeners, thinners, binders, 1K basecoat toners (solid, silver, and pearl colors), 2K topcoat toners, primers (1K primer surfacer, 2K primer surfacer, epoxy primer, and plastic prime), and ancillaries.



For over 20 years, a reliable paint supplier has offered industrial, wood, plastic, and vehicle paint, as well as equipment for servicing automobiles. They provide medium solid and high solid acrylic car repair paint systems for cars, trucks, metal objects, fences, and billboards. A minimum order of 100 cartons is required, and free samples are available. After-sales assistance is provided by engineers who can visit clients' locations for qualified solutions. A driver is available for travel to





Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com