



## 2K High Solid System Auto Refinish Paint With Excellent Covering Power

Our Product Introduction

for more products please visit us on [refinishcarpaint.com](http://refinishcarpaint.com)

### Basic Information

- Place of Origin: GUANGDONG CHINA
- Brand Name: Meklon
- Certification: ISO,SGS,MSDS
- Model Number: 106
- Minimum Order Quantity: 200L
- Price: USD3.06/L-10.5/L
- Packaging Details: 1L\*12,4\*4,20L,200L
- Delivery Time: 5-8 work days
- Payment Terms: T/T
- Supply Ability: 500000L/month



### Product Specification

- Material: Acrylic Resin
- Usage: Car Paint, Plastic Coating
- Application Method: Spray
- State: Liquid Coating
- Brand: Honda
- Shelf Life: 3 Years
- Port: Hong Kong, Huangpu, Shekou, Nansha
- HS Code: 320890
- High Light: Honda Ready Mixed Car Paint
- Coverage: Various Coverage
- Highlight: **High Solid Auto Refinish Paint, Auto Refinish Paint 2K**



### More Images



## Product Description

### 1K 2K High Solid System Auto Refinish Paint with Excellent Covering Power

#### Product Description:

We are introducing our advanced car paint, specifically designed to meet your automotive painting needs. Our car paint offers a range of features and benefits that ensure a superior painting experience.

**Eco-Friendly Paint Remover:** Our car paint includes an eco-friendly paint remover, allowing for easy removal of old paint layers without harming the environment. It provides a safe and sustainable solution for paint removal.

**Non-Corrosive and User-Friendly:** Our car paint is non-corrosive, ensuring the safety of both the user and the vehicle being painted. It is easy to use, making the painting process more efficient and convenient.

**Free from Harmful Materials:** Our car paint does not contain acid, benzene, or other harmful materials. This ensures a safer working environment and reduces the risk of health hazards associated with traditional paint products.

**Reutilization Capability:** The paint film and paint slag can be easily cleaned from the solution, allowing for the reutilization of our car paint. This feature enhances cost-effectiveness and reduces waste.

**Efficient Paint Removal:** Our car paint is capable of quickly removing various types of finishing paint, including phenolic resin, acrylic, epoxy, polyurethane, and premier paint. It ensures efficient and thorough paint removal, saving time and effort.

#### Features of our car paint:

**High Solids:** Our car paint is formulated with high solids content, ensuring excellent coverage and a smooth, even finish. This results in a visually appealing and professional-looking paint job.

**High Build:** The high build property of our car paint allows for the creation of thick paint layers, providing enhanced protection and durability for the painted surface. It helps to hide imperfections and provides a smooth and uniform appearance.

**Good Hiding Power:** Our car paint has excellent hiding power, effectively concealing underlying layers and creating a solid, opaque finish. This ensures a flawless and vibrant color result.

**ISO TS 16949 Certified:** Our car paint is ISO TS 16949 certified, meeting the highest quality standards for automotive coatings. This certification guarantees the reliability and performance of our product.

**Customized Colors:** We offer a wide range of customizable colors, allowing you to choose the perfect shade for your vehicle. Whether you prefer bold and vibrant tones or subtle and elegant hues, our car paint can be tailored to your preferences.

Substrates		Dried and sanded existing finishes or primer	
Substrates treatment		Remove paint dust and contamination with degreaser	
Mixing Ratio			
Name	2K Solid color	Hardener	Thinner
Volume Ratio	2 parts	1 parts	0.3-0.5 parts
Port life		4 hours@20°C	
Viscosity		Solid colour: 110-120S Silver colour:180-220S	
Period of Coats		2-3 coats	
Flash-off time		10-15 Minutes	
Each thickness		40-60 Micron	
Spray Pressure		Gravity type: 1.2–1.5 mm, 3.4Pa Suction type:1.4-1.6mm	

Drying Time			
Temperature	Dust Free	Dry to Handle	Thorough Dry
20°C	30 minutes	10 hours	1 day
60°C	15 minutes	1 hours	1 hour
Sand ability and Polish ability	wet sanding P800 P1000 sand paper if need polish		
Shelf Life	5 years in original sealed		
Packaging	1L*12 tins /ctn 4L*4tins /ctn		

#### Package, Storage, and Transportation:

Our car paint is available in two packaging options: 200 kg/barrel or 25 kg/barrel, providing flexibility based on your specific needs. To ensure the longevity and quality of the paint, it is essential to follow proper storage and transportation guidelines.

**Storage Period:** Our car paint has a recommended storage period of approximately 12 months when stored in closed containers. It is crucial to keep the containers in a shady and dry place to prevent exposure to direct sunlight and moisture, which can affect the paint's performance.

#### Question & Answers about Car Paint:

Do you have formulas for mixing the car paint?

Yes, we provide formulas for mixing the car paint. We offer both on-line formulas and CD-ROMs containing detailed instructions for achieving the desired paint consistency and color.

Do we need to add a binder to the paint?

No, our car paint does not require the addition of binders. It is formulated as a complete paint system, eliminating the need for additional binders. Simply follow the provided mixing instructions for optimal results.

Can you supply promotional materials to us?

Yes, we can supply promotional materials to support your marketing efforts. We offer tint charts, color cards, posters, T-shirts, pens, catalogs, mixing machines, and tin openers free of charge. These materials can help showcase the range and quality of our car paint products.

Do you have any certificates concerning the quality?

Yes, our products are certified by ISO TS 16949:2002, which ensures adherence to strict quality management standards. Additionally, we hold the quality management system certificate issued by SG, further validating the quality of our car paint.

What kind of materials do you use for your automotive paint?

We utilize high-quality raw materials for our automotive paint. Our resin is sourced from Akzo Nobel, pigment from BASF, hardener from Bayer, additive from Clariant, and solvent from Exxon. These trusted suppliers ensure the reliability and

performance of our car paint.

How about your delivery time for car paint?

We strive to deliver our car paint products efficiently. Typically, the delivery time is 10 working days after receipt of the deposit.

We prioritize prompt and reliable service to meet your painting project timelines.



**Guangzhou Meklon Chemical Technology Co., Ltd.**



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province