

## OEM 1K Tinters Refinish Car Paint Acrylic Repair Base Spray Coat

#### **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 200L
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



### **Product Specification**

- Material:
- Usage:
- Application Method:
- State:
- Brand:
- Shelf Life:
- Port:
- HS Code:
- High Light:
- Coverage:
- Highlight:
- Acrylic Resin Car Paint, Plastic Coating Spray Liquid Coating Honda 3 Years Hong Kong, Huangpu, Shekou, Nansha 320890

**GUANGDONG CHINA** 

ISO,SGS,MSDS

USD3.06/L-10.5/L 1L\*12,4\*4,20L,200L

5-8 work days

500000L/month

Meklon

114

T/T

- Honda Ready Mixed Car Paint
- Various Coverage
  - 1K Tinters Refinish Car Paint, OEM Refinish Car Paint





# More Images

for more products please visit us on refinishcarpaint.com



#### 1K Tinters: Auto Body Acrylic Repair Base Spray Coat Car Paint for Automotive Refinishing

**Product Description** 

Highly Concentrated Tinters Series (HS Car Paint Series)

To address diverse customer requirements, our company proudly introduces the Addition brand – a highly concentrated universal tinters series known as the HS series. This innovative series allows the blending of HS tinters with various binders to produce 2K tinters, 1K tinters, 1K silver paint tinters, and 1K pearl paint tinters. The Addition HS car paint series boasts a comprehensive selection, comprising over 70 types of HS tinters, including HS solid color tinters, HS silver tinters, and HS tinters, among others.

By pairing these HS tinters with different binders, you can achieve a spectrum of finishes, ranging from solid color paint to metallic glitter and pearl effect surface coatings. The Addition HS car paint series offers numerous advantages, including a minimal amount of resin content, broad compatibility with the majority of resins, excellent stability, easy dispersion with resin, very high covering power, a complete range, and competitive pricing. Crucially, our customers have the flexibility to seamlessly replace the DuPont Central series with our Addition HS car paint series. Moreover, customers can integrate our HS tinters into DuPont's pre-existing mixed paint formula system. Elevate your automotive refinishing projects with the versatility and cost-effectiveness of the Addition HS car paint series.

| Substrates           |                | Dried and sanded existing finishes or primer              |          |               |  |  |  |
|----------------------|----------------|---|----------|---------------|--|--|--|
| Substrates           |                | Dheu and sanded existing linishes of primer               |          |               |  |  |  |
| Substrates treatment |                | Remove paint dust and contamination with degreaser        |          |               |  |  |  |
| Mixing Ratio         |                |   |          |               |  |  |  |
| Name                 | 2K Solid color |   | Hardener | Thinner       |  |  |  |
| Volume Ratio         | 2 parts        |   | 1 parts  | 0.3-0.5 parts |  |  |  |
| Port life            |                | 4 hours@20ºC  |          |               |  |  |  |
| Viscosity            |                | Solid colour: 110-120S<br>Silver colour:180-220S          |          |               |  |  |  |
|                      |                | Sliver colour: 180-2205                                   |          |               |  |  |  |
| Period of Coats      |                | 2-3 coats   |          |               |  |  |  |
| Flash-off time       |                | 10-15 Minutes   |          |               |  |  |  |
| Each thickness       |                | 40-60 Micron  |          |               |  |  |  |
| Spray Pressure       |                | Gravity type: 1.2–1.5 mm, 3.4Pa<br>Suction type:1.4-1.6mm |          |               |  |  |  |

| Drying Time                     |            |     |  |              |  |  |  |
|---------------------------------|------------|-----|--|--------------|--|--|--|
| Temperature                     | Dust Free  |     | Dry to Handle                                    | Thorough Dry |  |  |  |
| 20ºC                            | 30 minutes |     | 10 hours   | 1 day        |  |  |  |
| 60ºC                            | 15 minutes |     | 1 hours  | 1 hour       |  |  |  |
| Sand ability and Polish ability |            | wet | wet sanding P800 P1000 sand paper if need polish |              |  |  |  |
| Shelf Life                      |            |     | 5 years in original sealed                       |              |  |  |  |
| Packaging                       |            |     | 1L*12 tins /ctn 4L*4tins /ctn                    |              |  |  |  |

Our Services

**OEM Service:** 

Elevate your brand with our OEM service. We specialize in designing and manufacturing products under your brand, providing a unique and personalized touch to your offerings.

Fast Delivery:

Efficiency is our priority. Benefit from our fast delivery service, ensuring production completion and goods shipment within 7 to 10 days post order confirmation. Stay on track with your timelines seamlessly.

Customized Production:

Your vision, our priority. We tailor our production to meet your specific requests, ensuring adherence to quality and any special requirements you may have.

Promotional Gifts:

Enjoy promotional gifts as part of our customer-centric approach. For those with their own brand, these gifts can be customized with your brand name and design, adding a personal touch to your promotional efforts.

Full Customer Support:

Your success is our goal. Experience comprehensive support from us, ensuring your needs are met at every stage. Whether it's production, customization, or logistics, we are here to assist you.











