



## Bi - Component 1K Automotive Paint Auto Body Acrylic Repair Base Spray Coat

Our Product Introduction

for more products please visit us on [refinishcarpaint.com](http://refinishcarpaint.com)

### Basic Information

- Place of Origin: GUANGDONG CHINA
- Brand Name: Meklon
- Certification: ISO,SGS,MSDS
- Model Number: 120
- Minimum Order Quantity: 200L
- Price: USD3.06/L-10.5/L
- Packaging Details: 1L\*12,4\*4,20L,200L
- Delivery Time: 5-8 work days
- Payment Terms: T/T
- Supply Ability: 500000L/month



### Product Specification

- Material: Acrylic Resin
- Usage: Car Paint, Plastic Coating
- Application Method: Spray
- State: Liquid Coating
- Brand: Honda
- Shelf Life: 3 Years
- Port: Hong Kong, Huangpu, Shekou, Nansha
- HS Code: 320890
- High Light: Honda Ready Mixed Car Paint
- Coverage: Various Coverage
- Highlight: **Bi Component 1K Automotive Paint, Acrylic 1K Automotive Paint**



### More Images



## Product Description

### 1K Auto Body Acrylic Repair Base Spray Coat From Meklon Automotive Paint Supplier

#### Highly Concentrated Tinters Series (HS Car Paint Series)

To address diverse customer needs in the automotive refinishing industry, our company introduces the Addition brand - a highly concentrated universal tinters series known as the HS series. By combining HS tinters with different binders, you can create 2K tinters, 1K tinters, 1K silver paint tinters, and 1K pearl paint tinters. The Addition HS car paint series features over 70 varieties of HS tinters, including HS solid color tinters, HS silver tinters, and more. Paired with different binders, you can achieve surfaces with solid color, metallic glitter, and pearl effects. Boasting advantages like minimal resin content, wide compatibility, excellent stability, easy resin dispersion, very high covering power, a complete range, and competitive pricing, our Addition HS car paint series allows customers to seamlessly replace the DuPont Central series. Customers can also integrate our HS tinters into DuPont's pre-existing mixed automotive paint formula system.

#### MS Car Paint Series - 2K Solid Color Tinters

#### Features:

It is a bi-component automotive refinish paint series, offering a high-quality single coat system suitable for cars. Curable under room temperature or low-temperature baking, it boasts fast drying, high hardness, high gloss, bright color, excellent covering power, and easy spraying.

#### Mixing Ratio:

2K Tinters: Hardener: Thinner = 2: 1: 0.2-0.5 (volume ratio)

#### Applicable Period:

At 20 °C, for about 3 hours.

#### Drying Time:

At 20 °C, 40 minutes for surface dry, 12 hours for thorough dry. With 60 °C baking, 40 minutes for thorough dry.

#### Package:

1L \*12, 1L \*6, 4L \*4

#### Storage Period:

At 20 °C with original seal, can store more than 18 months.

#### 1K Tinters

#### Features:

A high-quality automotive base coat series, offering a two-coat and three-coat system suitable for cars. Includes silver, pearl, or solid color tinters. Boasts excellent covering power, metallic effect, and easy spraying.

#### Mixing Ratio:

1K Tinters: Thinner = 1: 1-1.2 (volume ratio)

#### Spraying:

Wet spray for two to three layers, with a flash-off time between layers of 5-15 minutes.

#### Package:

1L \*12, 1L \*6, 4L \*4

#### Storage Period:

At 20 °C with original seal, can store more than 18 months.

#### Note:

For spraying a large automotive area, we recommend adding 5% hardener, then spraying varnish.

Substrates	Dried and sanded existing finishes or primer		
Substrates treatment	Remove paint dust and contamination with degreaser		
Mixing Ratio			
Name	2K Solid color	Hardener	Thinner
Volume Ratio	2 parts	1 parts	0.3-0.5 parts
Port life		4 hours@20°C	
Viscosity		Solid colour: 110-120S Silver colour:180-220S	
Period of Coats		2-3 coats	
Flash-off time		10-15 Minutes	
Each thickness		40-60 Micron	
Spray Pressure		Gravity type: 1.2-1.5 mm, 3.4Pa Suction type:1.4-1.6mm	

Drying Time			
Temperature	Dust Free	Dry to Handle	Thorough Dry
20°C	30 minutes	10 hours	1 day
60°C	15 minutes	1 hours	1 hour
Sand ability and Polish ability	wet sanding P800 P1000 sand paper if need polish		
Shelf Life	5 years in original sealed		
Packaging	1L*12 tins /ctn 4L*4tins /ctn		

#### OEM Design and Manufacturing:

Tailored OEM service for customers to design and create products under their own brands.

#### Swift Delivery:

Production completion and goods delivery within 7 to 10 days post order confirmation for efficient service.

Customized Production:

Adherence to customers' requests, ensuring quality and meeting special requirements in product production.

Promotional Gifts with Branding:

Provision of promotional gifts with customers' own brand name and design for brand enhancement.

Comprehensive Customer Support:

Full support provided to meet customer needs effectively.





**Guangzhou Meklon Chemical Technology Co., Ltd.**



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province