



Low Odor Concentration Auto Base Coat Protection lemon yellow Car Paint

Our Product Introduction

for more products please visit us on refinishcarpaint.com

Basic Information

- Place of Origin: GUANGDONG CHINA
- Brand Name: Meklon
- Certification: ISO,SGS,MSDS
- Model Number: 121
- Minimum Order Quantity: 200L
- Price: USD3.06/L-10.5/L
- Packaging Details: 1L*12,4*4,20L,200L
- Delivery Time: 5-8 work days
- Payment Terms: T/T
- Supply Ability: 500000L/month



Product Specification

- Material: Acrylic Resin
- Usage: Car Paint, Plastic Coating
- Application Method: Spray
- State: Liquid Coating
- Brand: Carcharm
- Shelf Life: 3 Years
- Port: Hong Kong, Huangpu, Shekou, Nansha
- HS Code: 320890
- High Light: Honda Ready Mixed Car Paint
- Coverage: Various Coverage
- Highlight: **lemon yellow Car Paint,**
Low Odor Concentration Car Paint



More Images



Product Description

Low Odor Concentration Auto Base Coat Protection lemon yellow Car Paint

Automotive Paint Basecoat:

Elevate your automotive finish with Meklon-COAT basecoat, a cutting-edge product color system boasting over 60 base colors, including 16 Pearlescent, iridescent, and tinted metallic toners, as well as 6 xirallc options. This high-pigmented system not only ensures economic use but also delivers greater coverage, saving both time and resources. With only 2 coats required and minimal waiting time for the top coat application, experience efficiency like never before.

Surface Preparation:

Ensure optimal results by thoroughly sanding old paint surfaces and appropriately priming and preparing surfaces.

Suitable Substrates:

Meklon-COAT General 1K or 2K primers

- OEM Primer, sanded

Meklon-COAT General Polyester Putties

- Bare metal substrates must be pre-primed with wash primer YX-95

Product Features:

Our Meklon paint basecoat promises a hard paint film, exceptional leveling performance, easy construction, and strong adhesion. With excellent outdoor weather resistance and a prolonged anti-oxidation time, this one-component base paint can be seamlessly mixed with a variety of plain colors, metal effects, and pearl effects. Experience superb adhesion between layers, ensuring a lasting and visually appealing finish for your automotive projects. Choose Meklon for automotive paint excellence.



Application method

spray gun	Gravity gun	Suction gun
	gun nozzle: 1.2mm, gun pressure: 2.0-3.0 MPa	gun nozzle: 1.5mm, gun pressure: 2.0-3.0 Mpa
substrate	dry 1K primer surface with smooth effect	
Paint preparation	1k paint- thinner-EX10/EX20/EX30	
mix ratio	1 : 1 (base paint : thinner)	
spraying layers	2-3 coats	
flash off time	3-5 mins , 20-25	
surface dry time	15-20mins	
Time to Polish	1h, P1000 sanded paper	
Relationship between drying temperature and time of 1K base coat		
Tenmperture	Surface Drying time	Time to Polish
25	10-15 mins	1 hour

35	5-10 mins	40 mins
60	3-5 mins	15 mins

Safety Instructions:

For professional use only. KEEP OUT OF REACH OF CHILDREN. WARNING! FLAMMABLE CONTENTS. VAPOR AND SPRAY MIST CAN BE HARMFUL. MAY CAUSE SKIN AND EYE IRRITATION. Do not handle Prospray automotive paint products until the Material Safety Data Sheets (MSDS) have been thoroughly read and understood. Ensure that all employees are adequately trained on Material Safety Data Sheets and all chemicals, including automotive paint, with which they come into contact. Wear protective clothing, gloves, and eye safety with a side shield when handling and applying automotive paint products. This data sheet information is provided in good faith but without warranty. The information contained herein represents the current state of our knowledge and serves as a guide to our Prospray automotive paint products and their uses; it is not intended to insure specific product properties or their particular applications. Follow all warnings on Prospray automotive paint product labels.

Storage Guidelines:

Keep Prospray automotive paint products in a tightly covered container and in a dry and well-ventilated environment, avoiding direct exposure to sunlight. Maintaining temperatures above 10 is recommended, with an optimal range between 15 and 30 .
Note: Always adhere to safety protocols when handling automotive paint products, and ensure compliance with recommended storage conditions for optimal performance in automotive refinishing projects.



FAQ:

Q1: Are you trading company or manufacturer ?

A: Yes, we are. Our facotry is in Shaoguan, Guangdong, China. It takes one and half hour by car from Guangzhou airpoat to our factory.

Q2: Do you provide samples ? is it free or extra ?

A: According to the actual situaton, we can provied free samples.

Q3: Can you manufacturer the paint under my brand and my logo?

A: We could help to pack and deliver under your brand, but we would require some license from you and we have requirement for the order quantity..

For details, please contact us to get our OEM Cooperation Terms.

Q4: Is your car paint suitable for our weather?

A: This has been tested by our national wide customers and oversea markets. What's more, we can adjust the formula as per the climate condition of each local market.

Q5: Can you do customized colors?

A:Yes, we can, but we need the color sample from buyers. Or maybe you can send a picture for us for reference.

Q6: What free advertising materials would you give us if I send you an order? And how many pieces would you give free?

A:We could arrange free advertising materials such as mixing machine, balance/scale, spray gun, display racks, T-shirt, cap, CDs, posters, tinting maps,TDS, color reference cards, mixing rulers...etc.

While the quantity we could offer free is basing on your order amounts.



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province