



High Hardness And High UV Resistant Auto Refinish Paint 2K Topcoat Though Black Car Paint

Our Product Introduction

for more products please visit us on refinishcarpaint.com

Basic Information

- Place of Origin: GUANGDONG CHINA
- Brand Name: Meklon
- Certification: ISO,SGS,MSDS
- Model Number: 203
- Minimum Order Quantity: 200 cartoon
- Price: USD3.06/L-10.5/L
- Packaging Details: 1L*12,4*4,20L,200L
- Delivery Time: 5-8 work days
- Payment Terms: T/T
- Supply Ability: 500000L/month



Product Specification

- Material: Acrylic Resin
- Usage: Car Paint, Plastic Coating
- Application Method: Spray
- State: Liquid Coating
- Brand: CarCharm
- Shelf Life: 3 Years
- HS Code: 320890
- High Light: Honda Ready Mixed Car Paint
- Coverage: Various Coverage
- Highlight: **High Hardness Auto Refinish Paint,
Auto Refinish Paint Black Color**



More Images



Product Description

Hot Selling Auto Refinish Paint 2K Topcoat High Quality Though black Car Paint

Product Description

Solvent-Based Paint White Black Yellow Silver Auto Refinish Paint

Our car paint is solvent-based acrylic system that has very good weather resistance. The high gloss can last many years. We have various 2K and 1K colors: white, black, yellow, silver, and pearls. The main characteristics of our paint is high solid content, high thickness, and very good coverage.

2K PAINTS

Mixing ratio (2k paints: Activator/hardener: Thinner = 2: 1: 0.3-0.5)

For clear coat and hardener, except of 2:1, we also make a 4:1 or 5:1 mixing ratio.

Application method: Stir evenly before applying. Spray 2–3 coats. You can polish after 15 hours at 22°C and 30 minutes at 70°C.

SURFACE PREPARATION

1. Surface Should Be Clean And Free Of Dust, Grease And Oil.
2. Old Varnish Surfaces Must Be Sanded Using Grit Sandpaper Number 1200, Before Applying The Clear Coat.

Product Name	Features
2K Color Tinters	Fast Drying, High Hardness, High Gloss, Bright Color, Excellent Covering Power, Easy Spraying
1K Color Tinters	Excellent Covering Power, Metallic Effect, Easy Spraying
Clear Coat	High Hardness, High Gloss, Resistance To Alcohol And Gasoline, Protection, Durability And Brightness
Thinner	Good Dissolution, Promote Bonding
Hardener	High Quality, Excellent Anti-Yellowish, Heat Resistance, and High Solid Content
1K Primer	Fast Drying, Easy sanding, Excellent Filling Power, and good adhesion to the top coat
2K Primer	High Filling Power, Excellent Inter-Layer Adhesion, Fast Drying, Easy Sanding, Improved Fullness, Brightness And Gloss The Top Coat)
Epoxy Primer	Outstanding Isolation, Resistance to Salt Spray, Anti-moisture, Anti-bubbling, and Resistant Moist Heat
2K Binder	Improve The Gloss, Help Leveling
1K Binder	Boost the application, increase adhesion, and quicken the drying time of the 1K metallic paint film.
Matte Black Primer	High Blackness, Fast Drying, and Adhesion
Matte Agent	Reduce Brightness, Good Matting Effect
Poly Putty	Good Filling Power, Easy Application, Fast Dry (In Normal Temperature), No Crack, No Collapse, Easy Sanding, Excellent Adhesion

Product Code & Name	MK-202 2K Tinting Extra white
Product Description	Acrylic single-component basecoat
Color Description	Brownish red, purplish red on the front and darker on the sides
Package cans	1L round, 4L round cans
Package cartons	1L*12 (carton size: 45*35*15cm) 4L*4 (carton size: 35*35*20cm)
Solid content	2.5%
Viscosity (T-4 cup) at 25	240s-300s
Mixing ratio	202: thinner = 1 : 1-1.2
Spraying method	Spray 2 to 3 layers, the flash-off time is 5 to 10 minutes.
Scope of application	Cars, mechanical equipment, advertising signboards, hardware accessories, guardrails, doors, windows, and other metal surface products.



Application method

Spray gun	Gravity gun	Suction gun
	Gun nozzle: 1.2mm, Gun pressure: 2.0-3.0 MPa	Gun nozzle: 1.5mm, Gun pressure: 2.0-3.0 Mpa
Substrate	dry 1K primer surface with smooth effect	
Paint preparation	1k paint- thinner-EX10/EX20/EX30	
Mix ratio	1 : 1 (base paint : thinner)	
Spraying layers	2-3 coats	
Flash off time	3-5 mins , 20-25	
Surface dry time	15-20mins	
Time to Polish	1h, P1000 sanded paper	
Relationship between drying temperature and time of 1K base coat		
Tenmperture	Surface Drying time	Time to Polish
25	10-15 mins	1 hour
35	5-10 mins	40 mins
60	3-5 mins	15 mins

Our Comprehensive Services

1. Swift and Efficient Delivery: Experience the convenience of our fast delivery service. Once your order is confirmed, we commit to completing production and shipping the goods within 7 to 10 days.
2. Customized Production: Tailoring products to meet your specific requests and quality standards is our specialty. We pride ourselves on meeting unique requirements to ensure your complete satisfaction.
3. Branded Promotional Gifts: Add a personalized touch with promotional gifts customized to your needs. For those with their own brand, these gifts will prominently feature your brand name and design, enhancing your promotional efforts.
4. Dedicated Customer Support: Count on us for unwavering support. Our dedicated customer support team is ready to assist you with any inquiries, concerns, or special requests, ensuring a seamless experience.



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province