



## 1K Young Green Pearl Basecoat For Durable And Long Lasting Automotive Paint

Our Product Introduction

for more products please visit us on [refinishcarpaint.com](http://refinishcarpaint.com)

### Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: K-313
- Minimum Order Quantity: 100Boxes
- Price: 2.73USD/L-5.56USD/L
- Packaging Details: 1L\*12 Tins or 3.75L\*4 Tins,20L,200L
- Delivery Time: 10-15 Working Days
- Payment Terms: T/T
- Supply Ability: 1000 Boxes/day



### Product Specification

- Brand: Meishilianke
- Color: Young Green Pearl
- Color Level: Good Coverage,High Gloss
- Dry Film Thickness: 1.5-2.0 Mills
- Finish: Glossy
- Main Raw Materials: Acrylic Resin, Polyurethane Resin
- Net Weigh: 0.95KG
- Shelf Life: 2 Years In Original Sealed Can, Cool And Dry Place At 25°C
- Color Formula System: Meklonpaintmix
- OEM/ODM: As Customers' Order
- Highlight: **1k basecoat car paint, Automotive Green Pearl Basecoat**



### More Images



## Product Description

### China Automotive Paint Factory - Direct Wholesale, Providing Samples

#### Company Introduction

We are a Chinese automotive paint manufacturer, my name is Sally. We were established in 2014 and have been here for 10 years.

We have a professional team, complete departments such as Research, production, sales, after-sales, etc.

Our Research team comes from PPg and has many years of experience and outstanding contributions.

#### Product Specifications

Type	1K Young Green Pearl	
Substrates	Well-sanded,completely dried and good existing finishes as: A. original paint B.old paint firm C.1K or 2K primer	
Surface Cleaning	Wash by warm soap, remove wax, silicon and other contaminations with degreaser, sanding with P800-P1000, wash with clean water then keep dry, again with degreaser.	
Mixing Ratio	Basecoat	Thinner
<15°C	1K Basecoat 1K Copper Pearl	602 Fast Thinner
15-30°C	1K Basecoat 1K Copper Pearl	602 Standard Thinner
>30°C	1K Basecoat 1K Copper Pearl	602 Slow Thinner
Spray Viscosity	14-16s to drop off, in 4# viscosity cup at 25°C	
Re-Treatment	After Spray, allow 10-20 minutes air-drying time,then spray clear coat at once.	
Spray Gun Set Up	Gravity Feed: 1.2-1.5mm 3-5kg/cm <sup>2</sup> Gravity Feed: 1.4-1.6mm 3-5kg/cm <sup>2</sup>	
Spray Technology	Coats & Thickness: 2-3 coats, total 15-20um. Flash-Off Time: At 25°C, 5-10 minutes between two coats, it depends on temperature and paint film.	



If you are interested, you can contact me anytime  
**whatapp: +8613822162990**



**Guangzhou Meklon Chemical Technology Co., Ltd.**



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province