



## High Coverage High Extra White Automotive Refinish Paint With Low Voc

### Our Product Introduction

for more products please visit us on [refinishcarpaint.com](http://refinishcarpaint.com)

#### Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: L-201
- Minimum Order Quantity: 200L
- Price: 2.73/LUSD-5.56/LUSD
- Packaging Details: Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 200Lper day




#### Product Specification

- Brand: Meklon
- Name: High Density Extra White
- Specification: 1Lx12
- Package: Can And Carton
- Net Weight: 1.2KG
- Application: Brush, Roller, Or Spray
- Coverage: High
- Durability: Long-lasting
- Fade Resistant: Yes
- Heat Resistance: Yes
- State: Liquid Coating
- Type: Automotive Paint
- Voc: Low
- Highlight: **High Extra White Automotive Refinish Paint, Low Voc Automotive Refinish Paint**



#### More Images



## Product Description

### High Coverage High Extra White Automotive Refinish Paint With Low Voc

#### Supply manufacturer introduction:

Meklon is a car paint manufacturer. The offices are located in Guangzhou and Shaoguan respectively. The 3,000 square meters of production workshop and storage area provide ample space and advanced facilities for the production of car paint.

#### Production advantages:

Meklon's factory has advanced production equipment and a complete production chain. Every link from raw materials to car paint products is strictly controlled, and product quality is guaranteed. 100 experienced operators work diligently and skillfully in their respective positions, providing a solid manpower guarantee for efficient production. There are 20 laboratory R&D personnel. The R&D engineers have rich experience and expertise, and are committed to developing car paint products with excellent quality and performance, and constantly exploring and innovating. Our R&D results are remarkable, and the color matching rate of finished paint is as high as 98%, which can accurately meet the color needs of various types of cars.

#### Featured highlights:

Meklon has engineers who have been deeply involved in the world's top car paint professional field for 30 years. They bring superb technology and provide valuable experience and unique perspectives. At the same time, we are equipped with mixing formula software, and professionals will explain in detail so that customers can better understand and use our products. In addition, the perfect after-sales service system allows customers to have no worries. Whether it is questions during the use of the product or subsequent maintenance needs, we can respond in time and provide effective solutions.

#### Warehouse:

We have a 500 square meter warehouse with excellent safety hazards. Employees will regularly inspect the warehouse to ensure that the inventory products are safely stored and meet customer needs at any time. In addition, Meklon provides OEM services. You can send us the brand design drawings that need to be customized and give us a letter of authorization. We will customize the brand you want for you, or we have professional designers. You can tell us your ideas and needs, and we will let the designer customize it for you. Choosing Meklon automotive paint is choosing quality, innovation, and professionalism. We will continue to be committed to providing high-quality paint products for the automotive industry and work with customers to create a better future.

#### product description:

2K High Density Extreme White Automotive Refinish Paint is a high quality automotive paint with the following features:  
High Density Extreme White The color of this paint is very pure and bright, giving an excellent visual effect to the car's surface. It provides excellent coverage and color saturation, allowing the refinished area to match the original paint exactly.

Product Name:	P-201 High Density Extra White	Specifications:	1L/4L/5L
Features:	Durable, high covering power, high sun protection	Scope of application:	Cars, ships, vehicle, tanks
Color:	White	VOC	low
Drying time::	surface drying time is 2 hours, actual drying time is 24 hours	Mixing ratio:	paint:curing agent:thinner=2:1:0.3
Storage method:	Store in a cool, dry, ventilated and dark place	Sales scope:	global

construction substrate:	A. Original paint layer;		B. Old car paint film;	C. Intermediate paint film; Note that the construction substrate needs to be carefully polished, the surface is dry and in good condition	
Substrate treatment:	Before spraying the substrate, the substrate must be cleaned, degreased with degreaser, and polished with 800#~1000# sandpaper. Clean it after polishing, and use degreaser to remove oil again.				
Construction ratio:	Temperature 15 Color paint 100 parts MK12X quick-drying hardener agent 50 parts MK602 quick-drying thinner 15-30 parts		Temperature 15 -30 Color paint 100 parts P-12X standard hardener 50 parts P-602 standard diluent 15-30 parts		
	Temperature 30 Color paint 100 parts 12X slow drying hardener 50 parts 602 slow drying thinner 15-30 parts				
Viscosity:	16 seconds to 19 seconds, spray 4# viscosity cup (at normal temperature)				
Process::	The spraying process uses wet spraying to spray 2 to 3 layers on the surface of the substrate. Pay attention to leaving 5 to 10 minutes of evaporation time between each two layers. After spraying, the paint film needs to stand for 10 to 15 minutes. Then bake. Thickness in dry film state: 35~50 microns				
Re-construction:	After spraying, any areas with particles and sags should be wet-smoothed and polished with 2000# sandpaper after they are completely hardened.				
spray tools:	Gravity spray gun (top pot) 1.2-1.5mm 3-5kg/cm2				
	Suction spray gun (bottom) 1.4-1.6mm 3-5kg/cm2				
Use time after mixing:	After mixing the components, they need to be used within 4 hours				
Usage amount:	The thickness of a single coating is 35 microns. The paint is calculated based on a conversion rate of 70%. The theoretical value of the mixed paint spray area is: 8 square meters/liter, and the original unmixed 13 square meters/liter.				
Drying time:	ambient temperature	Non-stick time	Dry to touch time	Available assembly time	Complete drying time
	Normal temperature 25	40 minutes	2 hours	9 hours	6 days
	Bake at 70	5 minutes	10 minutes	25 minutes	50minutes

Product expiration date:	Validity period of 1-3 years, the product should be placed in a cool and dry place at 20
Product packaging specifications:	1L×12 cans/box; 4L×4 cans/box;5L×4 cans/box

2K means that this paint is a mixture of two components, mainly including base paint and curing agent. This coating system provides increased durability and chemical resistance, allowing the repaired part to maintain a good appearance for a long time..

Meklon automotive paint has excellent weather and abrasion resistance and is resistant to UV radiation, acid rain, corrosion and general scratches. Specific prices will vary based on net weight and capacity. Generally speaking, we use 1.2KG/can, and there are 12 cans in a carton. The high-quality 2K high-density extremely white car refinishing paint is relatively expensive because it has better performance and quality assurance. You can contact our sales staff for specific prices. It is recommended to consult a professional or dealer before purchasing to obtain the most accurate price information.

If you are interested, please consult Sally: +8613822162990.

#### Product display:



#### Factory Tour:



**Guangzhou Meklon Chemical Technology Co., Ltd.**



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province