



## Special White Car Repair Paint With High Coverage High Temperature Resistance

### Our Product Introduction

#### Basic Information

- Place of Origin: China
- Brand Name: CarCharm
- Certification: ISO,MSDS,SGS
- Model Number: C-202 Extra White
- Minimum Order Quantity: 200L
- Price: 2.73USD/L-5.56USD/L
- Packaging Details: Box/Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 200L per day



#### Product Specification

- Brand: CarCharm
- Code: C-202
- Product Name: Extra White
- Application humidity: Less Than 85%
- Chemical Resistance: Yes
- Coverage: Up To 50 Sq. Ft. Per Can
- High Light: 2k Top Coat
- Voc: Low VOC
- Highlight: **Special White Car Repair Paint,  
High Coverage Car Repair Paint,  
Car Repair Paint High Temperature Resistance**



#### More Images



## Product Description

### C-202 Extra white car repair paint, high coverage high temperature resistance environmental protection

#### product description:

2K Extra White Automotive Paint is a pure white paint that provides outstanding brightness and shine. It has a distinct white appearance and is a two-part system consisting of a base paint mixed with a hardener. This paint has the following characteristics:

**Durability:** 2K Extra Whit automotive paint offers exceptional durability, resisting scratches, scuffs and chemicals from daily use. It retains its bright appearance for a long time and is not prone to fading or yellowing.

**Gloss:** The paint provides excellent gloss, making the vehicle surface look very smooth and glossy. It reflects light, creating a bright effect and adding a luxurious feel to the vehicle.

|                     |   |   |                                    |
|---------------------|---|---|------------------------------------|
| Product Name:       | P-202 Extra White   | Specifications:   | 1L/4L/5L                           |
| Features:           | Durable, high covering power, high sun protection   | Scope of application:   | Cars, ships, vehicle, tanks        |
| Color:              | White   | voc   | low                                |
| Drying time:        | surface drying time is 2 hours, actual drying time is 24 hours  | Mixing ratio:   | paint:curing agent:thinner=2:1:0.3 |
| Storage method:     | Store in a cool, dry, ventilated and dark place   | Sales scope:  | global                             |
| Construction ratio: | Temperature 15<br>Color paint 100 parts<br>MK12X quick-drying hardener agent 50 parts<br>MK602 quick-drying thinner 15-30 parts | Temperature 15 -30<br>Color paint 100 parts<br>P-12X standard hardener 50 parts<br>P-602 standard diluent 15-30 parts |                                    |
|                     | Temperature 30<br>Color paint 100 parts<br>12X slow drying hardener 50 parts<br>602 slow drying thinner 15-30 parts             |   |                                    |

|              | ambient temperature   | Non-stick time | Dry to touch time | Available assembly time | Complete drying time |
|--------------|-----------------------|----------------|-------------------|-------------------------|----------------------|
| Drying time: | Normal temperature 25 | 40 minutes     | 2 hours           | 9 hours                 | 6 days               |
|              | Bake at 70            | 5 minutes      | 10 minutes        | 25 minutes              | 50minutes            |

**Construction performance:** This paint has good construction performance and is easy to apply and spray. It provides even coverage and cures to a strong coating.

**Application with 2KExtra White automotive paint** requires the following steps: Clean the vehicle surface: Use car wash liquid and water to clean the vehicle surface to ensure it is clean and dust-free.

**Mask and Protect:** Use plastic wrap, newsprint, or a professional masking product to cover the area around your vehicle to prevent spray paint from reaching unwanted areas.

**Grinding and polishing:** Use sandpaper and polishing tools to remove old paint, blemishes, and oxides from the vehicle's surface to smooth the surface.

**Mix paint:** 2K automotive paint is a two-part system paint, usually mixed with a base paint and a hardener. Follow the paint manufacturer's instructions for mixing the base paint and hardener in the correct proportions.

**Spraying operation:** Spray with an airbrush: Pour the mixed 2K automotive paint into the paint cup of the airbrush.

**Spraying Tips:** Keep the distance between the spray gun and the vehicle surface even, usually at a distance of 20-30 cm, to ensure even coverage of the coating. Multiple coats of spraying are usually required, with appropriate drying time between each coat. This ensures a smooth and even coating.

**Curing:** After applying the final coat of paint, wait for the coating to cure according to the paint manufacturer's recommendations. This usually takes some time to ensure the coating is completely dry and cured.

We were established in 2014 and have been here for 10 years. We have a professional team, complete departments such as research team, production, sales, after-sales, etc.

Our research team comes from PPG and has many years of experience and outstanding contributions. We have 5 brands and also support customized brands. There are many dealers who customize their own brands in our factory. If you are interested, you can contact our sales staff at any time.Sally, whatsapp+8613822162990

#### Product display:



**Factory Tour:**





**Warehouse display:**





**Guangzhou Meklon Chemical Technology Co., Ltd.**



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province