



## Car Clear Coat Universal Thinner High Transparency Abrasion Resistance And Corrosion Resistant

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: M-602
- Minimum Order Quantity: 200L
- Price: 2.73USD/L-5.56USD/L
- Packaging Details: Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500 boxes per day



### Product Specification

- Brand: Faralli Series
- Color: Transparent
- Name: Universal Thinner
- Net Weigh: 0.95KG
- Chemical Resistance: Good
- Drying Time: Fast/Standard/Slow
- Durability: High
- Ease Of Application: Easy
- Finish: Glossy
- Highlight: **Abrasion Resistance Car Clear Coat,  
Universal Thinner Car Clear Coat,  
High Transparency Car Clear Coat**



### More Images



F-602 Fast Drying Thinner	The fastest volatilization speed, a special thinner for 1K base paint, suitable for local repair or construction at temperatures below 15°C.
F-602 Universal Thinner	Medium volatilization speed, universal thinner for 1K base paint and 2K products, suitable for local repair or construction at 15-25°C.
F-602 Slow Drying Thinner	The volatilization speed is slightly slower. It is a slow-drying thinner for 1K base paint and 2K products. It is suitable for partial repair, whole vehicle spraying or construction at a temperature of 25-30 °C.
F-602 Slow Slow Drying Thinner	It has the slowest volatilization speed and is a special thinner for 1K products. It is suitable for whole vehicle spraying, large area construction or construction at temperatures higher than 30°C.

for more products please visit us on [refinishcarpaint.com](http://refinishcarpaint.com)

## Product Description

### Car Clear Coat Universal Thinner High Transparency Abrasion Resistance

#### Company Profile

Meklon car paint manufacturer is a company focused on producing high-quality car paint, with 6 brands, namely CarCharm, poshiche, feriiia, Meishilianke, Meiguanda and Meklon, each brand has its own unique packaging and characteristics. The company has its own R&D team, including R&D engineers, who have developed car paint products from low to high quality according to the standards. M-8300 Silver Diamond Clear Coat is a medium quality automotive paint product from this company.

#### Manufacturer



#### Product Description

Model NO.	F-602
Certification	ISO14001, ISO9001
Substrate	Iron
Components	Solvent
Formation Mechanism	Conversion Type
Delivery	7 - 14 Days After Order Confirmed
Shelf Life	2 Years
Usage	Car Refinish Paint
Transport Package	Standard Export Carton with Pallets
Specification	1L, 3.75L / 2L, 2.5L / 4L, 5L
Trademark	Meklon
Origin	China
HS Code	3208
Production Capacity	2000

Meklon's high-quality selection uses thinners specifically designed for use in automotive paints.

Meklon Automotive Paint Thinner is precisely formulated and tested to ensure compatibility with the brand's basecoats, topcoats and clearcoats. Choosing a brand-recommended thinner ensures a high-quality finish and durability.

Organic solvents such as toluene, xylene, etc. are widely used to dilute automotive paint. They have good solubility and volatility and can effectively dilute the paint to a concentration suitable for spraying. However, you need to pay attention to safety measures when working with organic solvents and ensure that you operate in a well-ventilated environment.

In addition to diluting the paint's concentration, additives and conditioners are sometimes needed to improve the finish and properties. For example,

rheology modifiers can adjust the viscosity and fluidity of paint fluids for better spray performance. Additives such as anti-sedimentants, antioxidants and desiccants can improve the quality and durability of the paint film.

#### Shipping Photos



**Product Picture**



<b>F-602</b> Fast Drying Thinner	The fastest volatilization speed, a special thinner for 1K base paint, suitable for local repair or construction at temperatures below 15°C.
<b>F-602</b> Universal Thinner	Medium volatilization speed, universal thinner for 1K base paint and 2K products, suitable for local repair or construction at 15-25°C.
<b>F-602</b> slow Drying Thinner	The volatilization speed is slightly slower. It is a slow-drying thinner for 1K base paint and 2K products. It is suitable for partial repair, whole vehicle spraying or construction at a temperature of 25-30 °C.
<b>F-602</b> Extra Slow Drying Thinner	It has the slowest volatilization speed and is a special thinner for 2K products. It is suitable for whole vehicle spraying, large-area construction or construction at temperatures higher than 30°C.



**Guangzhou Meklon Chemical Technology Co., Ltd.**



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province