



Multi Color Optional Weather Resistant Metal Car Paint 1K Pure Black Car Paint

Our Product Introduction

for more products please visit us on refinishcarpaint.com

Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: 1K 137 Pure Black
- Minimum Order Quantity: 50L
- Price: 2.73USD/L-5.56USD/L
- Packaging Details: Can/Carton
- Delivery Time: 7-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500 boxes per day



Product Specification

- Manufacture: Meklon
- Product: 1K Repair Paint
- Sheen: High
- Package Size: 1LX12
- Resistance: Various Resistance
- Application Temperature: 50-90°F
- Compatibility: Suitable For All Car Models
- Weather Resistance: Yes
- Voc Level: Low
- Voc Content: Low
- Voc: Low
- Highlight: Wholesale Car Paint, Good Metallic Car Paint, 1K Pure Black Car Paint



More Images



Product Description

Good Metallic Car Paint Price 1K Pure Black Wholesale Car Paint

Manufacturer introduction

Guangzhou Meklon Chemical Technology Co., Ltd. was established in 2014 with 25 subsidiaries and established a complete and scientific production chain.

We specialize in the production of automotive paints, industrial paints, putty, Clear Coat and Hardener special curing agents for automotive paints, and automotive care products. Special unsaturated resin, various cans, cartons, etc.

Our sales network covers more than 65 countries and has more than 1,500 customers in China.

We have established good business relationships with well-known automobile manufacturers, shipbuilding and machinery manufacturers. Our products have been favored by customers at home and abroad for many years.



Product Description

Meklon 1K Pure Black Restoration Automotive Paint offers excellent high hiding properties. It effectively covers blemishes and imperfections on the vehicle's surface during the repair process, including scratches, scrapes and small dents, allowing the repaired area to blend perfectly with the surrounding paint surface without visible marks.

Pure black car paint has excellent adhesion and adheres firmly to the vehicle surface. This means that the repaired paint surface will not peel or fade easily, and will have good durability and long-term aesthetic effect. Whether in high or low temperatures or harsh weather conditions, our 1K Solid Black Restoration Auto Paint maintains consistent performance.

Meklon's 1K Pure Black Restoration Automotive Paint has excellent leveling properties. It flows evenly and spreads flat across the vehicle's surface, resulting in a smooth, streak-free repair. This not only improves the cosmetic quality of the restoration, but also reduces subsequent polishing and finishing work.

1K pure black car repair paint can be sprayed alone or mixed with other colors and sprayed with other colors. Regarding the mixing function, we have finished paints matching the colors of each car model. We have APP system software. You can download the MekloncolorMix query formula. We also have matching Color cards, color charts, etc. If necessary, please feel free to contact our sales staff at any time.

Best of all, our 1K Solid Black Restoration Car Paint is affordable. We focus on providing high-quality products at affordable prices, allowing you to perform automotive restoration and maintenance at a more competitive cost. This not only helps reduce your costs but also improves your business effectiveness.

Instructions For Use

Type	1K Transparent Blue basecoat color paint	
Substrates	Well-sanded, completely dried and good existing finishes as: A. original paint B. old paint firm C. 1K or 2K primer	
Surface Cleaning	Wash by warm soap, remove wax, silicon and other contaminations with degreaser, sanding with P800-P1000, wash with clean water then keep dry, again with degreaser.	
Mixing Ratio	Basecoat	Thinner
<15°C	1K Transparent Blue basecoat color paint	602 Fast Thinner
15-30°C	1K Transparent Blue basecoat color paint	602 Standard Thinner
>30°C	1K Transparent Blue basecoat color paint	602 Slow Thinner
Spray Viscosity	14-16s to drop off, in 4# viscosity cup at 25°C	
Re-Treatment	After Spray, allow 10-20 minutes air-drying time, then spray clear coat at once.	
Spray Gun Set Up	Gravity Feed: 1.2-1.5mm 3-5kg/cm ² Gravity Feed: 1.4-1.6mm 3-5kg/cm ²	

Spray Technology	Coats & Thickness: 2-3 coats, total 15-20um. Flash-Off Time: At 25°C, 5-10 minutes between two coats, it depends on temperature and paint film.
Shelf Life	2 years in original sealed can, cool and dry place at 25°C
OEM/ODM	As customers' order
Package Size	1L*12 Tins or 3.75L*4 Tins



Client Feedback

1. The quality of your car paint is outstanding! We have been using your products and have always been very satisfied. Its adhesion is very strong, and the repaired part perfectly matches the original color without any color difference.
2. Our customers rave about the restoration results and their vehicles look like new. "
- 3."We are very impressed with the covering power of your car paint. We have used other brands of paint in the past but were unable to cover blemishes and scratches on the car body effectively. However, after using your product, we found that it can easily Cover up these issues to give your restored vehicle an unparalleled look."
4. "We are continually amazed at the durability of your car's paint. Even in adverse weather conditions, the paint film remains in excellent condition with no signs of peeling or peeling. This gives our customers peace of mind knowing that Their vehicles look great in all conditions."
5. "We particularly like the ease of application of your car paint. It is easy to apply to the body and has a short drying time. This greatly improves the efficiency of our operations and reduces waiting time. Our staff is very happy with this I am very satisfied with the convenience and would like to continue using your product."



Transportation



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province