

## Ready Mixed Car Paint Audi LX9C White Auto Painting Coat

Our Product Introduction

for more products please visit us on [refinishcarpaint.com](http://refinishcarpaint.com)

### Basic Information

- Place of Origin: China
- Brand Name: Audi
- Certification: ISO,MSDS,SGS
- Model Number: LX9C
- Minimum Order Quantity: 200L
- Price: 2.73USD/L-5.56USD/L
- Packaging Details: Box/Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500 boxes per day



### Product Specification

- Features: Fast Dry, Good Adhesion, High Gloss
- Manufacture: Meklon
- Product Name: Audi LX9C White
- Code: LX9C
- Net Weight: 0.95KG
- Shelf Life: 2-3 Years
- Material: Acrylic Resin
- Dry Time: 30 Minutes
- Other Names: Automotive Finish Paint
- Effect: Fast Drying ,high Hardness,bright Color
- Size: 11 Oz.
- Port: Hong Kong, Huangpu, Shekou, Nansha
- Mildew Resistance: Yes
- Highlight: Ready Mixed Car Paint,  
Audi LX9C White Auto Painting Coat,  
White Auto Painting Coat



### More Images



## Product Description

### MeklonReady Mixed Car Paint Audi LX9C White Auto Painting coat

#### Manufacturer introduction:

Meklon has a professional methods team dedicated to developing and improving automotive coating formulations and manufacturing processes. The company has a modern factory equipped with advanced equipment and production lines for the production of various types of automotive coatings, which are sold in more than 30 countries around the world. It currently has 6 brands, and other brands can be customized at any time.



#### product description:

Meklon as a car paint manufacturer, our factory produces Audi LX9C White car paint. This paint has been carefully developed and tested many times to ensure a high-quality finish for your vehicle. Whether it is beautiful appearance or painting quality, Audi LX9C White car paint is the perfect choice.

Our engineers use careful blending and strict quality control to ensure a consistent, vibrant white color in every batch. Whether under different lighting conditions or on different models, Audi LX9C White car paint can show excellent color consistency.

Our Audi LX9C White car paint offers excellent paint quality. Its excellent adhesion and durability can effectively protect your vehicle's surface from damage from daily use and the external environment. We use advanced formulations and production processes to ensure you get long-lasting, durable coatings.

Audi LX9C White automotive paint is suitable for the painting needs of various models. Whether your vehicle is a sedan, SUV, sports car or something else, our Audi LX9C White automotive paint can give it a great look. Our paint formulations are carefully developed by our engineers to ensure a perfect match for the bodywork of every car model.

Our factory adheres to high standards of quality control and principles. Our Audi LX9C White car paint undergoes rigorous quality testing to ensure every bottle of paint meets the highest standards. We are committed to providing reliable products that meet our customers' needs for quality coatings.

Mixed formula	
Car brand:	Audi
Applicable models:	Audi LY9C
Color name:	Ibis White
Year:	2020 Models
Depth:	Standard
Remark: Construction process: paint and thinner 1:1, wet spray twice, medium wet spray Twice, mist once, and varnish twice.	

Color Matching System			
Serial number	Color masterbatch number	Weight (g)	Cumulative amount (g)
Extra White	202	99.69	99.69
2K Pure Black	237	0.2	99.89
Standard Blue	206	0.03	99.92
Lemon Yellow	214	0.06	99.98
Iron Oxide Red	222	0.02	100
Total:100g			
Recipe weight:100g			

#### When spraying Audi LX9C White car paint, please follow the following application methods:

Before you start painting, make sure the car body surface is clean, smooth and make any necessary repairs. To clean the car body, you can use car detergent and a cleaning sponge to thoroughly remove dust, dirt and grease. When repairing the bodywork, repair any dents or scratches and sand thoroughly to ensure a smooth surface.

According to the Audi LX9C White car paint, mix the paint and thinner according to the specified ratio. Make sure to formulate in the correct proportions for optimal spray results.

Use professional spray equipment such as spray guns and spray systems. Make sure the equipment is clean and properly set up and adjusted according to the spray equipment's instruction manual. Adjust gun pressure and spray pattern for proper spray results.

Skilled spraying techniques are essential to obtain good coating results. During the spraying process, maintain uniform spray

thickness and appropriate spray angle. Use steady hand gestures to avoid uneven application or dripping. Before each spray application, make sure the spray gun is at an appropriate distance from the car body.

**Multi-layer spraying:** Usually, painting the car body requires multiple layers of spraying to obtain the ideal painting effect. Sufficient drying time should be allowed between each coat. Determine the drying time between each coat according to the Audi LX9C White automotive paint instruction manual.

**Environmental Control:** Ensure that spraying is carried out under suitable environmental conditions to avoid dust or other impurities from adhering to the wet paint. Select a clean, dry, and well-ventilated spray area. During the spraying process, pay attention to prevent dust and impurities from entering the spraying area.

**Maintenance and cleaning:** After spraying is completed, clean the spray equipment in time to prevent the paint from drying out and clogging. Use appropriate cleaning agents and methods for cleaning and maintenance according to the equipment manufacturer's recommendations.

### Storage suggestions:

The shelf life of Audi LX9C White is 2-3 years.

It is very important for Audi LX9C White car paint to be stored in a stable temperature environment. Optimal storage temperatures are usually between 5°C and 25°C. Avoid exposure to extreme temperatures, such as excessive heat or extreme cold, to prevent damage to the paint quality.

Paint is very sensitive to moisture, so contact with moisture should be avoided. When storing paint, make sure the container is tightly sealed to prevent moisture from penetrating. Consider using dehumidifiers or humidity control devices within storage areas to maintain a relatively dry environment.

Audi LX9C White car paint should be stored in a light-proof environment to reduce direct exposure to sunlight or other light sources on the paint. Sunlight and UV radiation may cause color changes or damage to paint quality.

During storage, make sure paint containers are tightly sealed and follow the storage recommendations and guidance provided by the manufacturer. If the paint container has been opened, try to use it up or transfer the remaining paint to a smaller container to reduce exposure to air.

**Avoid Vibration:** Avoid severe shock or vibration in the storage area to prevent separation or quality changes in the paint.



### Preparation:

Audi LX7W Bright Silver automotive finished paint requires some special painting techniques or equipment during the construction process.

Before painting, the car body surface must be clean and flat, and any necessary repairs and polishing work must be carried out. This helps ensure uniformity and adhesion of the paint surface.

In order to obtain the best painting results, it is usually necessary to use professional spray equipment, such as spray guns and spray systems. These devices apply paint evenly to the car body with the right pressure and spray pattern.

The construction process requires skilled technical operations, including correct spray angle, uniform coating thickness and appropriate drying time control. Skilled painting professionals ensure the best results from your Audi LX7W Bright Silver automotive finished paint.

In order to ensure the quality of coating, construction needs to be carried out under suitable environmental conditions. This includes controlling factors such as temperature, humidity and dust to avoid adverse effects on the finish.





## Factory Tour:







Customer feedback:





**Guangzhou Meklon Chemical Technology Co., Ltd.**



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province